HISTORIC AND DESIGN REVIEW COMMISSION

January 20, 2021

HDRC CASE NO: 2020-555

ADDRESS: 505 E TRAVIS ST

LEGAL DESCRIPTION: NCB 421 BLK 24 LOT E IRR 52.13 FT OF 1 & E IRR 49.72 FT OF S

31.19 OF 2

ZONING: D,HL CITY COUNCIL DIST.:

LANDMARK: Individual Landmark

APPLICANT: Scott Welty/Welty Architecture LLC

OWNER: Walter Baudier/505 TRAVIS BUILDING LLC

TYPE OF WORK: Exterior modifications, construction of a rooftop addition

APPLICATION RECEIVED: December 03, 2020

60-DAY REVIEW: Not applicable due to City Council Emergency Orders

CASE MANAGER: Stephanie Phillips

REQUEST:

The applicant is requesting a Certificate of Appropriateness for approval to:

1. Remove an existing rooftop addition and mechanical systems and construct a partial rooftop addition.

2. Restore previously-enclosed window openings on ancillary facades.

APPLICABLE CITATIONS:

Historic Design Guidelines, Chapter 2, Exterior Maintenance and Alterations

6. Architectural Features: Doors, Windows, and Screens

A. MAINTENANCE (PRESERVATION)

- i. *Openings*—Preserve existing window and door openings. Avoid enlarging or diminishing to fit stock sizes or air conditioning units. Avoid filling in historic door or window openings. Avoid creating new primary entrances or window openings on the primary façade or where visible from the public right-of-way.
- ii. Doors—Preserve historic doors including hardware, fanlights, sidelights, pilasters, and entablatures.
- iii. *Windows*—Preserve historic windows. When glass is broken, the color and clarity of replacement glass should match the original historic glass.
- iv. Screens and shutters—Preserve historic window screens and shutters.
- v. *Storm windows*—Install full-view storm windows on the interior of windows for improved energy efficiency. Storm window may be installed on the exterior so long as the visual impact is minimal and original architectural details are not obscured.

B. ALTERATIONS (REHABILITATION, RESTORATION, AND RECONSTRUCTION)

- i. *Doors*—Replace doors, hardware, fanlight, sidelights, pilasters, and entablatures in-kind when possible and when deteriorated beyond repair. When in-kind replacement is not feasible, ensure features match the size, material, and profile of the historic element.
- ii. *New entrances*—Ensure that new entrances, when necessary to comply with other regulations, are compatible in size, scale, shape, proportion, material, and massing with historic entrances.
- iii. Glazed area—Avoid installing interior floors or suspended ceilings that block the glazed area of historic windows.
- iv. *Window design*—Install new windows to match the historic or existing windows in terms of size, type, configuration, material, form, appearance, and detail when original windows are deteriorated beyond repair.
- v. *Muntins*—Use the exterior muntin pattern, profile, and size appropriate for the historic building when replace ment windows are necessary. Do not use internal muntins sandwiched between layers of glass.
- vi. *Replacement glass*—Use clear glass when replacement glass is necessary. Do not use tinted glass, reflective glass, opaque glass, and other non-traditional glass types unless it was used historically. When established by the architectural style of the building, patterned, leaded, or colored glass can be used.

- vii. *Non-historic windows*—Replace non-historic incompatible windows with windows that are typical of the architectural style of the building.
- viii. Security bars—Install security bars only on the interior of windows and doors.
- ix. *Screens*—Utilize wood screen window frames matching in profile, size, and design of those historically found when the existing screens are deteriorated beyond repair. Ensure that the tint of replacement screens closely matches the original screens or those used historically.
- x. *Shutters*—Incorporate shutters only where they existed historically and where appropriate to the architectural style of the house. Shutters should match the height and width of the opening and be mounted to be operational or appear to be operational. Do not mount shutters directly onto any historic wall material.

Historic Design Guidelines, Chapter 3, Guidelines for Additions

2. Massing and Form of Non-Residential and Mixed-Use Additions

A. GENERAL

- i. *Historic context*—Design new additions to be in keeping with the existing, historic context of the block. For example, additions should not fundamentally alter the scale and character of the block when viewed from the public right-of-way.
- ii. *Preferred location*—Place additions at the side or rear of the building whenever possible to minimize the visual impact on the original structure from the public right of way. An addition to the front of a building is inappropriate.
- iii. *Similar roof form*—Utilize a similar roof pitch, form, and orientation as the principal structure for additions, particularly for those that are visible from the public right-of-way.
- iv. Subordinate to principal facade—Design additions to historic buildings to be subordinate to the principal façade of the original structure in terms of their scale and mass.
- v. *Transitions between old and new*—Distinguish additions as new without distracting from the original structure. For example, rooftop additions should be appropriately set back to minimize visibility from the public right-of-way. For side or rear additions utilize setbacks, a small change in detailing, or a recessed area at the seam of the historic structure and new addition to provide a clear visual distinction between old and new building forms.

B. SCALE, MASSING, AND FORM

- i. *Height*—Limit the height of side or rear additions to the height of the original structure. Limit the height of rooftop additions to no more than 40 percent of the height of original structure.
- ii. *Total addition footprint*—New additions should never result in the doubling of the historic building footprint. Full-floor rooftop additions that obscure the form of the original structure are not appropriate.

3. Materials and Textures

A. COMPLEMENTARY MATERIALS

- i. *Complementary materials*—Use materials that match in type, color, and texture and include an offset or reveal to distinguish the addition from the historic structure whenever possible. Any new materials introduced to the site as a result of an addition must be compatible with the architectural style and materials of the original structure.
- ii. *Metal roofs*—Construct new metal roofs in a similar fashion as historic metal roofs. Refer to the Guidelines for Alternations and Maintenance section for additional specifications regarding metal roofs.
- iii. *Other roofing materials*—Match original roofs in terms of form and materials. For example, when adding on to a building with a clay tile roof, the addition should have a roof that is clay tile, synthetic clay tile, or a material that appears similar in color and dimension to the existing clay tile.

B. INAPPROPRIATE MATERIALS

i. *Imitation or synthetic materials*—Do not use imitation or synthetic materials, such as vinyl siding, brick or simulated stone veneer, plastic, or other materials not compatible with the architectural style and materials of the original structure.

C. REUSE OF HISTORIC MATERIALS

i. Salvage—Salvage and reuse historic materials, where possible, that will be covered or removed as a result of an addition.

4. Architectural Details

A. GENERAL

- i. *Historic context*—Design additions to reflect their time while respecting the historic context. Consider character-defining features and details of the original structure in the design of additions. These architectural details include roof form, porches, porticos, cornices, lintels, arches, quoins, chimneys, projecting bays, and the shapes of window and door openings.
- ii. Architectural details—Incorporate architectural details that are in keeping with the architectural style of the original structure. Details should be simple in design and compliment the character of the original structure. Architectural details that are more ornate or elaborate than those found on the original structure should not be used to avoid drawing undue attention to the addition.
- iii. *Contemporary interpretations*—Consider integrating contemporary interpretations of traditional designs and details for additions. Use of contemporary window moldings and door surroundings, for example, can provide visual interest while helping to convey the fact that the addition is new.

5. Mechanical Equipment and Roof Appurtenances

A. LOCATION AND SITING

- i. *Visibility*—Do not locate utility boxes, air conditioners, rooftop mechanical equipment, skylights, satellite dishes, cable lines, and other roof appurtenances on primary facades, front-facing roof slopes, in front yards, or in other locations that are clearly visible from the public right-of-way.
- ii. *Service Areas*—Locate service areas towards the rear of the site to minimize visibility from the public right-of-way. Where service areas cannot be located at the rear of the property, compatible screens or buffers will be required.

B. SCREENING

- i. *Building-mounted equipment*—Paint devices mounted on secondary facades and other exposed hardware, frames, and piping to match the color scheme of the primary structure or screen them with landscaping.
- ii. *Freestanding equipment*—Screen service areas, air conditioning units, and other mechanical equipment from public view using a fence, hedge, or other enclosure.
- iii. Roof-mounted equipment—Screen and set back devices mounted on the roof to avoid view from public right-of-way.

6. Designing for Energy Efficiency

A. BUILDING DESIGN

- i. *Energy efficiency*—Design additions and new construction to maximize energy efficiency.
- ii. *Materials*—Utilize green building materials, such as recycled, locally-sourced, and low maintenance materials whenever possible.
- iii. *Building elements*—Incorporate building features that allow for natural environmental control such as operable windows for cross ventilation.
- iv. *Roof slopes*—Orient roof slopes to maximize solar access for the installation of future solar collectors where compatible with typical roof slopes and orientations found in the surrounding historic district.

B. SITE DESIGN

- i. *Building orientation*—Orient new buildings and additions with consideration for solar and wind exposure in all seasons to the extent possible within the context of the surrounding district.
- ii. Solar access—Avoid or minimize the impact of new construction on solar access for adjoining properties.

C. SOLAR COLLECTORS

- i. Location—Locate solar collectors on side or rear roof pitch of the primary historic structure to the maximum extent feasible to minimize visibility from the public right-of-way while maximizing solar access. Alternatively, locate solar collectors on a garage or outbuilding or consider a ground-mount system where solar access to the primary structure is limited.
- ii. *Mounting (sloped roof surfaces)*—Mount solar collectors flush with the surface of a sloped roof. Select collectors that are similar in color to the roof surface to reduce visibility.
- iii. *Mounting (flat roof surfaces)*—Mount solar collectors flush with the surface of a flat roof to the maximum extent feasible. Where solar access limitations preclude a flush mount, locate panels towards the rear of the roof where visibility from the public right-of-way will be minimized.


FINDINGS:

- a. The primary structure at 505 E Travis is a 3-story brick and cast concrete two-part commercial block building with basement attributed to Atlee B. Ayres and constructed c. 1914 for the San Antonio Light. The structure features brown brick with decorative cream-colored terra cotta belt courses, braces, frieze, and cartouche. The original first floor storefront configuration has been removed and modified. The structure is an individually listed local landmark.
- b. OPENING MODIFICATIONS The applicant has proposed to reopen previously-enclosed openings on an ancillary side façade. The openings will feature relocated original two over two steel windows or new steel windows to closely match the remaining original windows in profile, materiality, configuration, inset, and detailing. Based on the proposed proportion, location, and fenestration pattern, staff finds the proposal consistent with the Guidelines.
- c. ROOFTOP ADDITION: LOCATION The applicant has proposed to construct an addition on rooftop of the historic structure. According to Guideline 1.A.iv, setbacks and siting of the addition should incorporate a clear visual distinction between old and new building forms. The addition is set back from the primary façade and parapet. Staff finds that the addition location consistent with the Guidelines.
- d. ROOFTOP ADDITION: SCALE The proposed partial rooftop addition is 1-story. The Historic Design Guidelines state that new construction should be consistent with the height and overall scale of nearby historic buildings. Staff finds a 1-story structure consistent with the Guidelines in terms of height. Staff finds that the addition's scale is consistent with the Guidelines, and its siting result it its minimized visibility from the public right-of-way.
- e. ROOFTOP ADDITION: MATERIALITY The applicant has proposed to use painted plaster and stucco walls and a metal storefront window and door system. According to the Guidelines, materials that are compatible in type, color, and texture and distinguish the addition from the historic structure should be used whenever possible. Staff finds this materiality appropriate based on the location and scale of the addition.
- f. ROOFTOP ADDITION: FENESTRATION According to the Historic Design Guidelines, openings in new construction should use traditional dimensions and profiles found on the primary structure or within the historic district. The proposed fenestration pattern is similar to the storefront system on the first floor. Staff generally finds the requested fenestration pattern to be appropriate with the stipulations listed in the recommendation.
- g. ROOFTOP ADDITION: ARCHITECTURAL DETAILS According to the Guidelines, architectural details that are in keeping with the architectural style of the original structure should be incorporated or feature contemporary interpretations of original features. Details should be simple in design and compliment the character of the original structure. Architectural details that are more ornate or elaborate than those found on the original structure should not be used to avoid drawing undue attention to the addition. Staff finds the proposal consistent with the Guidelines.
- h. ADMINISTRATIVE APPROVAL The application submission may include documentation that qualifies for administrative approval, including the replacement of non-original windows on the front façade with historically appropriate windows; replacement of the non-original storefront system in-kind; brick façade repair; repainting of previously-painted surfaces; and the repair of the two over two steel windows on ancillary facades, which are possibly original.

RECOMMENDATION:

- Item 1, Staff recommends approval of the opening modifications based on finding b with the following stipulations:
 - i. That the applicant submits final material specifications for the windows to be used. Windows should match the existing steel windows on the same façade in size, configuration, style, detailing, and inset.
- Item 2, Staff recommends approval of the rooftop addition based on findings c through g with the following stipulations:
 - i. That the applicant submits final material specifications for all exterior materials to be used prior to the issuance of a Certificate of Appropriateness.
 - ii. That all roof vents and mechanical systems are properly screened in accordance with the UDC.

City of San Antonio One Stop



January 14, 2021

0 0.0225 0.045 0.09 mi
0 0.035 0.07 0.14 km













HISTORIC RENOVATION AND ADDITION

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205



HISTORIC RENOVATION AND **ADDITION**

TRAVIS ST. APARTMENTS

505 E. TRAVIS STREET

505 TRAVIS BAUDHAUS LLC

SAN ANTONIO, TEXAS 78205



WELTY ARCHITECTURE, LL Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

<u>OWNEK</u> NAME: BAUDHAUS LLC. CONTACT: BEAU BAUDIER / ERIC HAUSNER ADDRESS: 3330 W. Esplanade Avenue, Suite 205, Metairie, LA 70002 Email: bbaudier@dei-engr.com, ehausner@gmail.com Phone: 504-836-2155 WELTY ARCHITECTURE LLC LA License #7686 TX License #27938 Metairie, LA 70001 Email: scott@weltyarchitecture.com Cell Phone: 504-931-1665 CONTACT: TRAVIS MCLEOD, PE TMcLeod@silbereng.com 8610 BROADWAY SUITE 415 SAN ANTONIO, TX 78217 210-826-6392 WALTER BAUDIER - CONTACT 3330 W. ESPLANADE AVE., SUITE 205, METAIRIE, LA 70002 504-836-2155 DRAWING SHEET LIST DRAWINGS ISSUE DATE: OCTOBER 8, 2020 G001 COVER SHEET E100 BASEMENT PLAN - POWER E101 FIRST FLOOR PLAN - POWER G100 CODE SUMMARY PLANS E102 SECOND FLOOR PLAN - POWER G101 FIRE PROTECTION SITE PLAN E103 THIRD FLOOR PLAN - POWER G200 AREA PLANS E104 ROOF LEVEL PLAN - POWER E200 BASEMENT PLAN - LIGHTING D100 DEMO BASEMENT AND FIRST FLOOR PLAN | E201 FIRST FLOOR PLAN - LIGHTING E202 SECOND FLOOR PLAN - LIGHTING D101 DEMO SECOND AND THIRD FLOOR PLAN D102 DEMO ROOF PLAN E203 THIRD FLOOR PLAN - LIGHTING D103 DEMO ELEVATION ALAMO ST. SIDE E204 ROOF LEVEL PLAN - LIGHTING E300 ELECTRICAL DISTRIBUTION DIAGRAM D204 DEMO WEST ELEVATION E301 SCHEDULES - ELECTRICAL E400 PANELBOARD SCHEDULES S101 STRUCTURAL - GENERAL STRUCTURAL NOTES AND REMOVAL PLAN E401 PANELBOARD SCHEDULES S102 STRUCTURAL - REMOVAL PLANS E402 PANELBOARD SCHEDULES S103 STRUCTURAL - REMOVAL DETAILS E403 PANELBOARD SCHEDULES S104 STRUCTURAL - ROOF BEAM AND SLAB

A8.0 WINDOW DETAIL AND SPECIFICATIONS A8.1 INTERIOR DOORS AND TRIM A8.2 WINDOW DETAILS Z6.1 SITELINE STUDIES 2 Z6.2 SITELINE STUDIES 2 S107 STRUCTURAL - ROOF AND BEAM SLAB P100.1 BASEMENT FLOOR PLAN - UNDERGROUND S108 STRUCTURAL - ROOF AND BEAM SLAB P100.2 BASEMENT FLOOR PLAN - WASTE & VENT S109 STRUCTURAL PARAPET WALL AND - PLUMBING P100.3 BASEMENT FLOOR PLAN - WATER & GAS -S110 STRUCTURAL PENTHOUSE FRAMING P101 FIRST FLOOR PLAN - PLUMBING P102 SECOND FLOOR PLAN - PLUMNBING 3112 STRUCTURAL TYPICAL PLUMBING P103 THIRD FLOOR PLAN - PLUMBING P104 ROOF LEVEL PLAN - PLUMBING S113 STRUCTURAL TYPICAL PLUMBING P200 SCHEDULES & DETAILS - PLUMBING S114 STRUCTURAL TYPICAL SIDEWALK BEAM P201 TYPICAL ENLARGED PLANS P301 BUILDING ISOMETRIC - PLUMBING P302 BUILDING ISOMETRIC WATER AND GAS -A001 SCHEDULES - ROOM AND WALL TYPES FP101 BASEMENT & FIRST FLOOR - FIRE PROTECTION FP102 SECOND & THIRD FLOOR - FIRE PROTECTION FP103 FOURTH FLOOR & RISER DIAGRAM - FIRE PROTECTION

S105 STRUCTURAL - ROOF BEAM AND

S106 STRUCTURAL - ROOF BEAM AND

ANCHORAGE DETAILS

ANCHORAGE DETAILS

GEOFOAM DETAILS

TRENCH DETAILS

TRENCH DETAILS

AND SLAB REPAIR

A050 SITE PLAN

A100 BASEMENT PLAN

A101 FIRST FLOOR PLAN

A102 SECOND FLOOR PLAN

A103 THIRD FLOOR PLAN

A104 FOURTH FLOOR PLAN

A105 ROOF PLAN

ADDITION

A121 DIMENSIONED PLANS

A200 EXTERIOR FLEVATIONS

A203 REAR ELEVATIONS

A300 GENERAL SECTIONS

A301 GENERAL SECTIONS

A302 GENERAL SECTIONS

AND STAIR

A900 SPECIFICATIONS

A901 SPECIFICATIONS

MEP1 MEP SPECIFICATIONS

MEP2 MEP SPECIFICATIONS

A303 ROOFTOP ELEVATIONS

A002 DOOR AND WINDOW SCHEDULE

A111 ROOF DETAILS LIQUID APPLIED AT ROOF

A112 ROOF DETAILS - TPO AT NEW ROOFTOP

A122 DIMENSIONED PLANS 2ND AND 3RD

A501 ENLARGED FLOOR PLANS AT ELEVATOR

A502 ENLARGED STAIR PLANS AND STAIR

A504 ENLARGED PLAN AT ADA UNIT

A503 ENLARGED SECTION AT STAIR AND ELEV

M100 BASEMENT FLOOR PLAN - MECHANICAL

M101 FIRST FLOOR PLAN - MECHANICAL

M103 THIRD FLOOR PLAN - MECHANICAL

M301 SCHEDULES - MECHANICAL M302 CODE ANALYSIS - MECHANICAL


M102 SECOND FLOOR PLAN - MECHANICAL


M104 FOURTH FLOOR PLAN - MECHANICAL

M105 PENTHOUSE ROOF PLAN - MECHANICAL M201 ASSEMBLY DIAGRAMS - MECHANICAL

A123 DIMENSIONED PLAN 4TH FLOOR


3111 STRUCTURAL MISC. DETAILS







0.25 SHGC NEW WINDOWS

U-0.61 NEW SWINGING DOORS








This drawing as an instrument of service is the property of the Architect and may be used only on he project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.


NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.


WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION DATE 2020-03-29 **BID SET** ADD#1 4-22-2020 PERMIT SET 10-8-2020

COVER SHEET


DRAWN BY: SJW








CODE 02 SECOND FLR NFPA 13 THROUGHOUT





TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND ADDITION

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

> > 505 TRAVIS BAUDHAUS LLC



Area Schedule (IBC Gross Building)

SECOND FLOOR GROSS AREA 3,546 SF R1 OCCUPANCY THIRD FLOOR GROSS AREA 3,546 SF R1 OCCUPANCY
FOURTH FLOOR ADDITION 1,368 SF A2 OCCUPANCY Grand total: 5 15,830 SF

CODE SUMMARY AND LIST OF SPECIAL INSPECTIONS Provide the contact information for the Registered Design Professional in Responsible Charge RDPiRC, and List of Special Inspections if required – See Information Bulletin 132

CODE PLAN LEGEND

CODE NOTE: FIRE PARTITIONS DO NOT REQUIRE

FIRE DAMPERS PER IBC 717.5.4 EXCEPTION 1 1/2 HR RATING AT CORRIDOR (FIRE PARTITION REDUCTION) 1 HR WALL FIRE PARTITION 2 HR FIRE BARRIER

> RESIDENTIAL DWELLING UNITS (R1) COMMERCIAL WHITE BOX

MERCANTILE (M) OR ASSEMBLEY WITH TABLES AND CHAIRS **EGRESS AREAS**

EXIT PASSAGEWAY 2HR RATED AT FLOOR, WALLS, CEILINGS

ASSEMBLY SPACE A2

SERVICE AREAS

VERTICAL SHAFTS

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE:

REV. # REVISION DESCRIPTION BID SET ADD#1

PERMIT SET

CODE SUMMARY PLANS

DRAWN BY: SJW

G100

OCTOBER 8, 2020

DATE 2020-03-29


4-22-2020

10-8-2020

CODE 01 FIRST FLR NFPA 13 THROUGHOUT

CODE 00.1 BASEMENT NFPA 13 THROUGHOUT

34 OCCUPANTS AT BASEMENT LEVEL



505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



DEMOLITION NOTES

3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

D1 DEMO HATCHED WALLS AND ASSOCIATED COMPONENTS D2 DEMO HATCHED DOORS AND FRAMES (TYPICAL)

D3 DEMO STAIRS AND HANDRAILS D4 D4 DEMO ELEVATOR D5 D5 REMOVE EXISTING STOREFRONT SYSTEM. PREPARE OPENING FOR

NEW STOREFRONT D6 D6 REMOVE EXISTING ALUM. WINDOWS. PREPARE OPENING FOR NEW WINDOWS, TYP. D7 DEMO PLUMBING AND ALL ASSOCIATED PIPING.

D8 DEMO FLOOR SYSTEM IN THIS LOCATION. COORDINATE WITH STRUCTURAL. COORDINATE WITH STAIR SHOP DRAWINGS PRIOR TO STARTING ANY DEMOLITION.

D9 REPAIR EXISTING BRICK WALL. REPOINT MASONRY D10 D10 DEMO EXISTING METAL FLUE D11 D11 DEMO EXISTING ROOFTOP MECHANICAL EQUIPMENT (TYPICAL)

D12 D12 DEMO EXISTING SIGNAGE. REPAIR ANY DAMAGED MASONRY AND D13 D13 DEMO EXISTING EXTERIOR DOOR. PREPARE FOR NEW OPENING. D14 D14 DEMO EXISTING ATTIC VENTS. PREPARE OPENING FOR NEW ROOF OVERFLOW SCUPPER

D15 DEMO EXISTING WOOD FRAMED ROOFING DOWN TO EXISTING CONCRETE ROOF/ATTIC SLAB. PREPARE SLAB FOR NEW WORK. D16 D16 DEMO EXISTING BRICK FOR SALVAGED WINDOWS. VERIFY SIZE PRIOR TO DEMO

D17 D17 EXISTING SIDEWALK TO REMAIN. REWORK SIDEWALK TOPPING. SEE STRUCTURAL DETAILS AND NOTES ON S114 D18 MASONRY CLEANING TO REMOVE GRAFITTI

D19 REMOVE EXISTING WALL AND PIPING. REPAIR/REPLACE STONE TO MATCH ADJACENT SURFACES D20 STONE CLEANING AND RESTORATION D21 REMOVE EXISTING ROOFTOP ADDITION.

D22 REMOVE EXISTING METAL FLUE AND SUPPORT STRUCTURE D23 D23 DEMO EXISTING MECHANICAL AND ELECTRICAL ITEMS WITHIN D24 COORDINATE DUCT PENETRATION WITH STRUCTURAL AND MECHANICAL. CUT MIN. REBAR

D25 DEMO FLOOR TILE D26 D26 DEMO EXISTING FLOOR SLAB FOR UNDERGROUND PLUMBING. LOCATIONS SHOWN ARE SCHEMATIC IN NATURE. COORDINATE FINAL SLAB CUTS WITH PLUMBING PRIOR TO PERFORMING WORK. REFER TO STRUCTURAL FOR SLAB REPAIR DETAILS (MIN. WIDTH OF

D27 DEMO EXISTING ATTIC VENTS. INFILL OPENING WITH BRICK TO MATCH EXISTING (TYP. AT 4) D28 D28 REMOVE EXISTING WINDOWS. SALVAGE WINDOW FOR REUSE IN EAST FACADE. INFILL OPENING WITH SOLID BRICK TO MATCH

EXISTING. RECESS BRICK 1" FROM FACE. D29 D29 INFILL EXISTING SCUPPER LOCATION. RELOCATE HOLE FOR NEW LOWER SCUPPER D30 D30 REMOVE EXISTING WINDOWS AT FRONT FACADE. PREPARE FOR

GD1 EXISTING TERRAZZO FLOOR TO REMAIN. PROTECT DURING THE COURSE OF PROJECT. PREPARE FOR RESTORATION. GD2 EXISTING WOOD PANELING TO REMAIN. PROTECT DURING COURSE OF

WORK. PREPARE FOR REFINISHING. GD3 TYP. EXISTING STEEL DOUBLE HUNG WINDOW TO REMAIN. EXIST. TRIM TO REMAIN. RESTORE TO WORKING CONDITION. REMOVE EXISTING GLAZING AND PREPARE FOR NEW GLAZING.

GD4 GD4 EXISTING MAIN ELECTRICAL CONDUIT TO REMAIN GD5 GD5 EXISTING SIDEWALK BEAMS ABOVE. SEE STRUCTURAL FOR

DEMO LEGEND

EXISTING WALL TO REMAIN

DEMO IN PHASE 1 (INTERIOR DEMO WORK) WORK COMPLETED PRIOR TO THIS PROJECT

> DEMO IN PHASE 2 (INCLUDING EXTERIOR ABATEMENT WORK)

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION 2020-03-29

ADD#1 4-22-2020 PERMIT SET

DEMO BASEMENT AND FIRST FLOOR PLAN

DRAWN BY: SJW

D100

HISTORIC RENOVATION AND **ADDITION**

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



WELTY ARCHITECTURE, LLC Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

DEMOLITION NOTES

DESCRIPTION
TCHED WALLS AND ASSOCIATED COMPONENTS

(TYPICAL) D2 DEMO HATCHED DOORS AND FRAMES (TYPICAL)

D3 DEMO STAIRS AND HANDRAILS

D4 D4 DEMO ELEVATOR D5 D5 REMOVE EXISTING STOREFRONT SYSTEM. PREPARE OPENING FOR

NEW STOREFRONT D6 REMOVE EXISTING ALUM. WINDOWS. PREPARE OPENING FOR NEW

WINDOWS, TYP. D7 DEMO PLUMBING AND ALL ASSOCIATED PIPING.

D8 DEMO FLOOR SYSTEM IN THIS LOCATION. COORDINATE WITH STRUCTURAL. COORDINATE WITH STAIR SHOP DRAWINGS PRIOR TO

STARTING ANY DEMOLITION. D9 REPAIR EXISTING BRICK WALL. REPOINT MASONRY

D10 D10 DEMO EXISTING METAL FLUE D11 D11 DEMO EXISTING ROOFTOP MECHANICAL EQUIPMENT (TYPICAL)

D12 D12 DEMO EXISTING SIGNAGE. REPAIR ANY DAMAGED MASONRY AND D13 DEMO EXISTING EXTERIOR DOOR. PREPARE FOR NEW OPENING.

ROOF OVERFLOW SCUPPER D15 DEMO EXISTING WOOD FRAMED ROOFING DOWN TO EXISTING

CONCRETE ROOF/ATTIC SLAB. PREPARE SLAB FOR NEW WORK. D16 D16 DEMO EXISTING BRICK FOR SALVAGED WINDOWS. VERIFY SIZE

PRIOR TO DEMO D17 EXISTING SIDEWALK TO REMAIN. REWORK SIDEWALK TOPPING.

SEE STRUCTURAL DETAILS AND NOTES ON S114 D18 MASONRY CLEANING TO REMOVE GRAFITTI

D19 REMOVE EXISTING WALL AND PIPING. REPAIR/REPLACE STONE TO MATCH ADJACENT SURFACES D20 STONE CLEANING AND RESTORATION

D21 REMOVE EXISTING ROOFTOP ADDITION.

D22 REMOVE EXISTING METAL FLUE AND SUPPORT STRUCTURE D23 D23 DEMO EXISTING MECHANICAL AND ELECTRICAL ITEMS WITHIN

THE SPACE. D24 D24 COORDINATE DUCT PENETRATION WITH STRUCTURAL AND MECHANICAL. CUT MIN. REBAR

D25 DEMO FLOOR TILE

D26 DEMO EXISTING FLOOR SLAB FOR UNDERGROUND PLUMBING. LOCATIONS SHOWN ARE SCHEMATIC IN NATURE. COORDINATE FINAL SLAB CUTS WITH PLUMBING PRIOR TO PERFORMING WORK. REFER

TO STRUCTURAL FOR SLAB REPAIR DETAILS (MIN. WIDTH OF

D27 DEMO EXISTING ATTIC VENTS. INFILL OPENING WITH BRICK TO MATCH EXISTING (TYP. AT 4) D28 D28 REMOVE EXISTING WINDOWS. SALVAGE WINDOW FOR REUSE IN

EXISTING. RECESS BRICK 1" FROM FACE. D29 D29 INFILL EXISTING SCUPPER LOCATION. RELOCATE HOLE FOR NEW LOWER SCUPPER

D30 REMOVE EXISTING WINDOWS AT FRONT FACADE. PREPARE FOR

GD1 EXISTING TERRAZZO FLOOR TO REMAIN. PROTECT DURING THE COURSE OF PROJECT. PREPARE FOR RESTORATION.

GD2 EXISTING WOOD PANELING TO REMAIN. PROTECT DURING COURSE OF WORK. PREPARE FOR REFINISHING.

GD3 TYP. EXISTING STEEL DOUBLE HUNG WINDOW TO REMAIN. EXIST. TRIM TO REMAIN. RESTORE TO WORKING CONDITION. REMOVE EXISTING GLAZING AND PREPARE FOR NEW GLAZING.

GD4 GD4 EXISTING MAIN ELECTRICAL CONDUIT TO REMAIN GD5 GD5 EXISTING SIDEWALK BEAMS ABOVE. SEE STRUCTURAL FOR

EXISTING WALL TO REMAIN

DEMO IN PHASE 1 (INTERIOR DEMO WORK)

WORK COMPLETED PRIOR TO THIS PROJECT

(INCLUDING EXTERIOR ABATEMENT WORK)

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020

REV. # REVISION DESCRIPTION

ADD#1

DEMO SECOND AND THIRD FLOOR PLAN

DRAWN BY: SJW

D101





DEMO 04 ROOF SLAB

DEMOLITION GENERAL NOTES

A. These demolition plans are provided for the convenience of the contractor and only generally indicate these building elements which must be demolished to complete the work.

B. Drawings showing existing construction and utilities are based on casual field observation and existing record documents only. C. Remove finishes and components as required to complete new work whether or not such removal is specifically noted herein. Refer to the remaining documents, including those pertaining to civil, structural, HVAC, plumbing, electrical, and fire protection systems, and to the

remaining project manual for a complete description of the finished work. In locations where new finished ceilings are not required to be installed, patch and repair to match existing. Notify architect if existing conditions deviate from that shown prior to executing the work. E. Contractor shall patch and repair as necessary all floor, wall, and ceiling surfaces damaged

during demolition and during temporary shoring. F. Cut and patch slabs on grade, supported slabs, walls, floors, and ceilings as required to complete work as shown in the documents. G. Prior to removal or modification of walls or other potentially loadbearing elements, the actual

size and locations of structural components and loadbearing conditions shall be field verified by the contractor by means of selective finish demolition. The contractor shall notify the A/E of any unusual or potentially hazardous concealed conditions. H. Provide all temporary bracing and shoring necessary to safely support all loads, including roof loads, and to maintain existing framing in its existing location while making modifications

required under this contract. I. Where patching exposed masonry, provide full units toothed into existing adjacent masonry. Saw cut masonry joints will not be accepted. J. All dimensions shown on demolition drawings are approximate and shall be coordinated with finish work and shop drawings prior to cutting and patching.

1.02 SUBMITTALS A. Schedule: Submit selective demolition schedule, including schedule and methods for capping utilities to be abandoned and maintaining existing utility service. B. Project Record Documents: Accurately record actual locations of capped and active utilities and subsurface construction.

PART 3 EXECUTION

2.01 GENERAL PROCEDURES AND PROJECT CONDITIONS A. Comply with applicable codes and regulations for demolition operations and safety of Obtain required permits.

2. Shoring and Bracing: Provide and maintain interior and exterior shoring and bracing as required to complete demolition work. 3. Take precautions to prevent catastrophic or uncontrolled collapse of structures to be removed; do not allow worker or public access within range of potential collapse of unstable

4. Provide, erect, and maintain temporary barriers and security devices. B. Do not begin removal until built elements to be salvaged or relocated have been removed. If hazardous materials are discovered during removal operations, stop work and notify Architect and Owner; hazardous materials include regulated asbestos containing materials, lead,

D. Security: Provide adequate protection against accidental trespassing. Secure project after

E. Hazardous Materials: Comply with 29 CFR 1926 and state and local regulations.

2.02 EXISTING UTILITIES

A. Coordinate work with utility companies; notify before starting work and comply with their requirements; obtain required permits.

B. Protect existing utilities to remain from damage. 2.03 SELECTIVE DEMOLITION FOR ALTERATIONS A. Services (Including but not limited to HVAC, Plumbing, Fire Protection, Electrical, and Telecommunications: Remove existing systems and equipment to prepare for new work.

B. Protect existing work to remain. 2.04 **DEBRIS AND WASTE REMOVAL** A. Remove debris, junk, and trash from site.

2.05 **SCHEDULE** A. Items for Protection During Demolition and Construction:

Existing Terrazzo Floor and Granite Base in Entry Existing Wood Paneling in Entry Existing Decorative Wall medallions in Entry (8 Panels)

4. Existing Black Granite at Entries 5. Existing Main stair, and handrails from basement to roof.

6. Existing Windows at sides and rear of building, except where otherwise noted. Existing elevator jambs


8. Adjacent buildings construction. B. Items to be Salvaged for Reinstallation: 1. Existing Wood trim at doors and windows.

Elevator Jambs C. Items to be Salvaged for Delivery to Owner:

None

END OF SECTION

MAMAMAMAMAMATAN TERRETAKAN TERRET



TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND **ADDITION**

505 TRAVIS BAUDHAUS LLC

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205



DEMOLITION NOTES

DESCRIPTION D1 D1 DEMO HATCHED WALLS AND ASSOCIATED COMPONENTS

D2 DEMO HATCHED DOORS AND FRAMES (TYPICAL)

D3 DEMO STAIRS AND HANDRAILS D4 D4 DEMO ELEVATOR

D5 D5 REMOVE EXISTING STOREFRONT SYSTEM. PREPARE OPENING FOR NEW STOREFRONT D6 D6 REMOVE EXISTING ALUM. WINDOWS. PREPARE OPENING FOR NEW

WINDOWS, TYP. D7 DEMO PLUMBING AND ALL ASSOCIATED PIPING. D8 DEMO FLOOR SYSTEM IN THIS LOCATION. COORDINATE WITH STRUCTURAL. COORDINATE WITH STAIR SHOP DRAWINGS PRIOR TO

STARTING ANY DEMOLITION. D9 REPAIR EXISTING BRICK WALL. REPOINT MASONRY

D10 D10 DEMO EXISTING METAL FLUE D11 D11 DEMO EXISTING ROOFTOP MECHANICAL EQUIPMENT (TYPICAL) D12 D12 DEMO EXISTING SIGNAGE. REPAIR ANY DAMAGED MASONRY AND

D13 DEMO EXISTING EXTERIOR DOOR. PREPARE FOR NEW OPENING. D14 D14 DEMO EXISTING ATTIC VENTS. PREPARE OPENING FOR NEW ROOF OVERFLOW SCUPPER D15 D15 DEMO EXISTING WOOD FRAMED ROOFING DOWN TO EXISTING

CONCRETE ROOF/ATTIC SLAB. PREPARE SLAB FOR NEW WORK. D16 D16 DEMO EXISTING BRICK FOR SALVAGED WINDOWS. VERIFY SIZE PRIOR TO DEMO D17 D17 EXISTING SIDEWALK TO REMAIN. REWORK SIDEWALK TOPPING.

SEE STRUCTURAL DETAILS AND NOTES ON S114 D18 MASONRY CLEANING TO REMOVE GRAFITTI D19 REMOVE EXISTING WALL AND PIPING. REPAIR/REPLACE STONE TO

MATCH ADJACENT SURFACES D20 STONE CLEANING AND RESTORATION D21 REMOVE EXISTING ROOFTOP ADDITION.

D22 REMOVE EXISTING METAL FLUE AND SUPPORT STRUCTURE D23 D23 DEMO EXISTING MECHANICAL AND ELECTRICAL ITEMS WITHIN

D24 D24 COORDINATE DUCT PENETRATION WITH STRUCTURAL AND MECHANICAL. CUT MIN. REBAR D25 D25 DEMO FLOOR TILE

D26 D26 DEMO EXISTING FLOOR SLAB FOR UNDERGROUND PLUMBING. LOCATIONS SHOWN ARE SCHEMATIC IN NATURE. COORDINATE FINAL SLAB CUTS WITH PLUMBING PRIOR TO PERFORMING WORK, REFER TO STRUCTURAL FOR SLAB REPAIR DETAILS (MIN. WIDTH OF

D27 DEMO EXISTING ATTIC VENTS. INFILL OPENING WITH BRICK TO MATCH EXISTING (TYP. AT 4) D28 PEMOVE EXISTING WINDOWS. SALVAGE WINDOW FOR REUSE IN EAST FACADE. INFILL OPENING WITH SOLID BRICK TO MATCH

EXISTING. RECESS BRICK 1" FROM FACE. D29 D29 INFILL EXISTING SCUPPER LOCATION. RELOCATE HOLE FOR NEW LOWER SCUPPER

D30 D30 REMOVE EXISTING WINDOWS AT FRONT FACADE. PREPARE FOR GD1 EXISTING TERRAZZO FLOOR TO REMAIN. PROTECT DURING THE

COURSE OF PROJECT. PREPARE FOR RESTORATION. GD2 EXISTING WOOD PANELING TO REMAIN. PROTECT DURING COURSE OF WORK. PREPARE FOR REFINISHING. GD3 TYP. EXISTING STEEL DOUBLE HUNG WINDOW TO REMAIN.

EXIST. TRIM TO REMAIN. RESTORE TO WORKING CONDITION. REMOVE EXISTING GLAZING AND PREPARE FOR NEW GLAZING. GD4 GD4 EXISTING MAIN ELECTRICAL CONDUIT TO REMAIN

GD5 GD5 EXISTING SIDEWALK BEAMS ABOVE. SEE STRUCTURAL FOR DETAILS

DEMO LEGEND

EXISTING WALL TO REMAIN

DEMO IN PHASE 1 (INTERIOR DEMO WORK) WORK COMPLETED PRIOR TO THIS PROJECT DEMO IN PHASE 2

(INCLUDING EXTERIOR ABATEMENT WORK)

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020

REV. # REVISION DESCRIPTION ADD#1 PERMIT SET

DEMO ROOF PLAN

DRAWN BY: SJW

D102

4-22-2020









HISTORIC RENOVATION AND **ADDITION**

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

WELTY ARCHITECTURE, LLC

DEMOLITION NOTES

- D1 D1 DEMO HATCHED WALLS AND ASSOCIATED COMPONENTS
- D2 DEMO HATCHED DOORS AND FRAMES (TYPICAL) D3 DEMO STAIRS AND HANDRAILS
- D4 D4 DEMO ELEVATOR
- D5 REMOVE EXISTING STOREFRONT SYSTEM. PREPARE OPENING FOR
- **NEW STOREFRONT** D6 D6 REMOVE EXISTING ALUM. WINDOWS. PREPARE OPENING FOR NEW
- WINDOWS, TYP. D7 DEMO PLUMBING AND ALL ASSOCIATED PIPING.
- D8 DEMO FLOOR SYSTEM IN THIS LOCATION. COORDINATE WITH STRUCTURAL. COORDINATE WITH STAIR SHOP DRAWINGS PRIOR TO STARTING ANY DEMOLITION.
- D9 REPAIR EXISTING BRICK WALL. REPOINT MASONRY
- D10 D10 DEMO EXISTING METAL FLUE
- D11 D11 DEMO EXISTING ROOFTOP MECHANICAL EQUIPMENT (TYPICAL) D12 D12 DEMO EXISTING SIGNAGE. REPAIR ANY DAMAGED MASONRY AND
- D13 DEMO EXISTING EXTERIOR DOOR. PREPARE FOR NEW OPENING. D14 D14 DEMO EXISTING ATTIC VENTS. PREPARE OPENING FOR NEW
- ROOF OVERFLOW SCUPPER D15 DEMO EXISTING WOOD FRAMED ROOFING DOWN TO EXISTING
- CONCRETE ROOF/ATTIC SLAB. PREPARE SLAB FOR NEW WORK. D16 D16 DEMO EXISTING BRICK FOR SALVAGED WINDOWS. VERIFY SIZE
- PRIOR TO DEMO D17 D17 EXISTING SIDEWALK TO REMAIN. REWORK SIDEWALK TOPPING.
- SEE STRUCTURAL DETAILS AND NOTES ON S114
- D18 MASONRY CLEANING TO REMOVE GRAFITTI D19 REMOVE EXISTING WALL AND PIPING. REPAIR/REPLACE STONE TO
- MATCH ADJACENT SURFACES D20 STONE CLEANING AND RESTORATION
- D21 REMOVE EXISTING ROOFTOP ADDITION. D22 REMOVE EXISTING METAL FLUE AND SUPPORT STRUCTURE
- D23 DEMO EXISTING MECHANICAL AND ELECTRICAL ITEMS WITHIN
- D24 COORDINATE DUCT PENETRATION WITH STRUCTURAL AND
- MECHANICAL. CUT MIN. REBAR D25 DEMO FLOOR TILE
- D26 D26 DEMO EXISTING FLOOR SLAB FOR UNDERGROUND PLUMBING.
- LOCATIONS SHOWN ARE SCHEMATIC IN NATURE. COORDINATE FINAL SLAB CUTS WITH PLUMBING PRIOR TO PERFORMING WORK. REFER TO STRUCTURAL FOR SLAB REPAIR DETAILS (MIN. WIDTH OF
- D27 DEMO EXISTING ATTIC VENTS. INFILL OPENING WITH BRICK TO
- MATCH EXISTING (TYP. AT 4) D28 D28 REMOVE EXISTING WINDOWS. SALVAGE WINDOW FOR REUSE IN
- EAST FACADE. INFILL OPENING WITH SOLID BRICK TO MATCH EXISTING. RECESS BRICK 1" FROM FACE. D29 D29 INFILL EXISTING SCUPPER LOCATION. RELOCATE HOLE FOR NEW
- LOWER SCUPPER D30 REMOVE EXISTING WINDOWS AT FRONT FACADE. PREPARE FOR
- NEW WORK GD1 EXISTING TERRAZZO FLOOR TO REMAIN. PROTECT DURING THE
- COURSE OF PROJECT. PREPARE FOR RESTORATION. GD2 EXISTING WOOD PANELING TO REMAIN. PROTECT DURING COURSE O WORK. PREPARE FOR REFINISHING.
- EXIST. TRIM TO REMAIN. RESTORE TO WORKING CONDITION. REMOVE
- EXISTING GLAZING AND PREPARE FOR NEW GLAZING. GD4 GD4 EXISTING MAIN ELECTRICAL CONDUIT TO REMAIN
- GD5 GD5 EXISTING SIDEWALK BEAMS ABOVE. SEE STRUCTURAL FOR

DEMO LEGEND

EXISTING WALL TO REMAIN

DEMO IN PHASE 1 (INTERIOR DEMO WORK)
WORK COMPLETED PRIOR TO THIS PROJECT

DEMO IN PHASE 2 (INCLUDING EXTERIOR ABATEMENT WORK)

This drawing as an instrument of service is the property of the Architect and may be used only on

the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and

is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.


WA PROJECT NO: PROJECT ISSUE DATE:

DEMO ELEVATION ALAMO ST.

DRAWN BY: SJW

D103

OCTOBER 8, 2020



HISTORIC RENOVATION AND **ADDITION**

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



DEMOLITION NOTES

D1 D1 DEMO HATCHED WALLS AND ASSOCIATED COMPONENTS

D2 DEMO HATCHED DOORS AND FRAMES (TYPICAL) D3 DEMO STAIRS AND HANDRAILS

D4 D4 DEMO ELEVATOR

D5 D5 REMOVE EXISTING STOREFRONT SYSTEM. PREPARE OPENING FOR NEW STOREFRONT

D6 D6 REMOVE EXISTING ALUM. WINDOWS. PREPARE OPENING FOR NEW

D7 DEMO PLUMBING AND ALL ASSOCIATED PIPING. D8 D8 DEMO FLOOR SYSTEM IN THIS LOCATION. COORDINATE WITH

STRUCTURAL. COORDINATE WITH STAIR SHOP DRAWINGS PRIOR TO STARTING ANY DEMOLITION.

D9 D9 REPAIR EXISTING BRICK WALL. REPOINT MASONRY D10 D10 DEMO EXISTING METAL FLUE

D12 D12 DEMO EXISTING SIGNAGE. REPAIR ANY DAMAGED MASONRY AND

D13 DEMO EXISTING EXTERIOR DOOR. PREPARE FOR NEW OPENING. D14 D14 DEMO EXISTING ATTIC VENTS. PREPARE OPENING FOR NEW ROOF OVERFLOW SCUPPER

D15 DEMO EXISTING WOOD FRAMED ROOFING DOWN TO EXISTING CONCRETE ROOF/ATTIC SLAB. PREPARE SLAB FOR NEW WORK.

D16 D16 DEMO EXISTING BRICK FOR SALVAGED WINDOWS. VERIFY SIZE PRIOR TO DEMO

D17 D17 EXISTING SIDEWALK TO REMAIN. REWORK SIDEWALK TOPPING. SEE STRUCTURAL DETAILS AND NOTES ON S114

D18 MASONRY CLEANING TO REMOVE GRAFITTI D19 REMOVE EXISTING WALL AND PIPING. REPAIR/REPLACE STONE TO MATCH ADJACENT SURFACES

D20 STONE CLEANING AND RESTORATION D21 REMOVE EXISTING ROOFTOP ADDITION.

D22 REMOVE EXISTING METAL FLUE AND SUPPORT STRUCTURE D23 D23 DEMO EXISTING MECHANICAL AND ELECTRICAL ITEMS WITHIN

D24 D24 COORDINATE DUCT PENETRATION WITH STRUCTURAL AND

MECHANICAL. CUT MIN. REBAR D25 D25 DEMO FLOOR TILE

D26 D26 DEMO EXISTING FLOOR SLAB FOR UNDERGROUND PLUMBING. LOCATIONS SHOWN ARE SCHEMATIC IN NATURE. COORDINATE FINAL

SLAB CUTS WITH PLUMBING PRIOR TO PERFORMING WORK. REFER TO STRUCTURAL FOR SLAB REPAIR DETAILS (MIN. WIDTH OF

D27 DEMO EXISTING ATTIC VENTS. INFILL OPENING WITH BRICK TO

MATCH EXISTING (TYP. AT 4) D28 D28 REMOVE EXISTING WINDOWS. SALVAGE WINDOW FOR REUSE IN EAST FACADE. INFILL OPENING WITH SOLID BRICK TO MATCH

EXISTING. RECESS BRICK 1" FROM FACE. D29 D29 INFILL EXISTING SCUPPER LOCATION. RELOCATE HOLE FOR NEW LOWER SCUPPER

D30 D30 REMOVE EXISTING WINDOWS AT FRONT FACADE. PREPARE FOR **NEW WORK** GD1 EXISTING TERRAZZO FLOOR TO REMAIN. PROTECT DURING THE

COURSE OF PROJECT. PREPARE FOR RESTORATION.

GD2 EXISTING WOOD PANELING TO REMAIN. PROTECT DURING COURSE OF WORK. PREPARE FOR REFINISHING.

GD3 TYP. EXISTING STEEL DOUBLE HUNG WINDOW TO REMAIN. EXIST. TRIM TO REMAIN. RESTORE TO WORKING CONDITION. REMOVE

EXISTING GLAZING AND PREPARE FOR NEW GLAZING. GD4 GD4 EXISTING MAIN ELECTRICAL CONDUIT TO REMAIN

GD5 GD5 EXISTING SIDEWALK BEAMS ABOVE. SEE STRUCTURAL FOR

EXISTING WALL TO REMAIN

DEMO IN PHASE 1 (INTERIOR DEMO WORK)

DEMO IN PHASE 2 (INCLUDING EXTERIOR ABATEMENT WORK)

WORK COMPLETED PRIOR TO THIS PROJECT

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and


is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.


WA PROJECT NO:

PROJECT ISSUE DATE:

OCTOBER 8, 2020

DEMO WEST ELEVATION





• 1/2" SHEETROCK FIRECODE C Core gypsum

2-1/2" USG C-H Studs 25 gauge 24" o.c.

panels, face layer joints finished

1" SHEETROOK gypsum liner panels

UL Des U415,

USG-040912

RAL-0T-04-022

RAL-0T-04-019

Based on 4" C-H studs 25 gauge

Based on 1" sound batts in cavity

3" mineral fiber insulation

Based on 4" C-H studs 25 gauge with

System B

or **U438**

RAL-TL-11-176

STC-120309

RAL-TL11-176

R-11 fiberglass sound bat

3" mineral fiber insulation

Based on 5/8" SHEETROCK FIRECODE panels,

Based on 5/8" SHEETROCK FIRECODE core

panels, 4" 20 gauge steel studs 16" o.c.,

Based on 5/8" SHEETROCK UltraLight Panels

FIRECODE X, R-11 fiberglass sound bat

or 5/8" SHEETROCK UltraLight Panels FIRECODE X

- 3-5/8" 25 gauge steel studs 24" o.c.

- optional insulation

corridor ceiling, and stair soffit 1" SHEETROCK brand gypsum liner panels 1/2" SHEETROCK FIRECODE C Core gypsum . USG steel C-H Stud spanning horizontally 24" o.c. USG steel J-runner - joints finished

This drawing as an instrument of service is the property of the Architect and may be used only on ne project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

- REFER TO RCP PLAN(S), SCHEDULE FOR

- ACOUSTIC INSULATION AT ALL APARTMENT

FIRE RATING - 1HR @ G6.1 AND 1/2HR @ G6.5

FIRESTOPPING REQ'D AT ALL TOPS, BOTTOMS,

- METAL STUD FRAMING, 16" O.C.

SEAMS, AND PENETRATIONS

DEMISING WALLS

ACOUSTIC SEALANT

| UI U419

APPLICABLE CEILING SYSTEM ASSEMBLY, HEIGHT

TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND

ADDITION

505 E. TRAVIS STREET

SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC

SEAL 10-21-2020

WELTY ARCHITECTURE, LLC

Scott Welty - Architect

3021 42nd St

Metairie, LA 70001

p. 504-931-1665

www.weltyarchitecture.com

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION DATE 2020-03-29 **BID SET** ADD#1 4-22-2020 PERMIT SET 10-8-2020

SCHEDULES - ROOM AND WALL TYPES

DRAWN BY: SJW

A00²

• 1/2" SHEETROCK FIRECODE C Core gypsum panels UL Des U419

- 3-5/8" 25 gauge steel studs 24" o.c.

RC-1 channel or equivalent one side spaced

3" THERMAFIBER SAFB


optional veneer plaste


24" o.c.

RAL-TL-87-156

RAL-TL-83-216

Based on 5/8" thick panels





)00R	SCHEDU	LE - STOR	EFRONT	
			DOOR			FRAME			
NO.	TYPE	HEIGHT	WIDTH	MATERIAL	FIRE RATING	MATERIAL	Operation	Hardware	Comments
11 FIRS	T FLR				·				
טוווווט	STOREFRONT	8'-1"	6'-0"	ALUM. GL.	-	ALUM.			
101	STUNLINUINI								
	STOREFRONT	8'-1"	3'-0"	ALUM. GL.	-	ALUM.			

					DO	OR SCHE	DULE - FOI	LDING	
			DOOR			FRAME			
NO.	TYPE	неіснт	WIDTH	MATERIAL	FIRE RATING	MATERIAL	Operation	Hardware	Comments
04.1 FOU	JRTH FLOOR SL	AB							
401C	FOLDING	8'-0"	19'-10"	ALUM. CLD	_				

GENERAL DOOR NOTES

- 1. ALL HARDWARE SHALL BE CLASS 2 OR BETTER
- ALL APARTMENT ENTRY DOORS SHALL BE OPENABLE WITH A SINGLE RELEASING MECHANISM. EVERY CLOSET DOOR LATCH SHALL BE OPERABLE FROM BOTH INSIDE AND OUTSIDE BATHROOM DOOR LOCKS SHALL PERMIT UNLOCKING FROM OUTSIDE IN THE EVENT OF AN EMERGENCY
- 5. NO DOOR IN ANY MEANS OF EGRESS SHALL BE LOCKED AGAINST EGRESS WHEN THE BUILDING IS OCCUPIED. 6. ALL HARDWARE TO BE INSTALLED BY A LICENSED LOCKSMITH.
- ANY SPECIAL LOCKING ARANGEMENTS SHALL BE SUBMITTED BY THE INSTALLER TO THE PERMIT OFFICE FOR REVIEW AND APPROVAL PRIOR TO INSTALATION.
- 8. CONTRACTOR SHALL ENGAGE A HARDWARE SPECIALIST TO SCHEDULE ALL DOOR HARDWARE. 9. ALL HARDWARE TO BE INSTALLED IN FIRE RATED DOORS SHALL BE FIRE-RATED HARDWARE AND
- DESIGNATED AS SUCH. 10. ALL DOOR FRAMES INSTALLED WITH FIRE RATED DOORS ARE TO BE LABELED, FIRE RATED FRAMES MATCHING THE LABELD RATING OF THE DOOR. ALL RATED DOORS SHALL RECEIVE DOOR CLOSERS OR
- SPRING HINGES. 11. COORDINATE DOOR UNDERCUTS WITH MECHANICAL REQUIREMENTS.

12. ADA UNIT SHALL HAVE ADA PEEPHOLE IN ENTRY DOOR.

				DO	00R S	CHEDULE	E - COMMI	ERCIAL HM						D00	R SC
			DOOR			FRAME							DOOR		
NO.	ТҮРЕ	HEIGHT	WIDTH	MATERIAL	FIRE RATING	MATERIAL	Operation	Hardware	Comments	NO.	TYPE	HEIGHT	WIDTH	MATERIAL	FIRE RATING
00.1 BAS	SEMENT									00.1 BAS	SEMENT				
2	STORAGE	7'-0"	3'-0"	METAL	_	HOLLOW METAL	STOREROOM			10	20MIN	7'-0"	3'-0"	WOOD	20M
3	FULLGLASS	7'-0"	3'-0"	WOOD	-	HOLLOW METAL				11	2-PANEL	7'-0"	3'-0"	WOOD	-
4	STORAGE	7'-0"	3'-0"	METAL	-	HOLLOW METAL			W/ PANIC HARDWARE	12	BARN	7'-0"	3'-0"	WOOD	-
5	STORAGE	7'-0"	3'-0"	METAL	90M	HOLLOW METAL			-	12A	2-PANEL	7'-0"	2'-0"	WOOD	-
6	STORAGE	7'-0"	3'-0"	METAL	-	HOLLOW METAL	STOREROOM			20	20MIN	7'-0"	3'-0"	WOOD	20M
S1-B1	STAIR	7'-0"	3'-0"	METAL	90M	HOLLOW METAL	STAIR		WITH NARROW LIGHT	21	2-PANEL	7'-0"	3'-0"	WOOD	-
S2-B	STAIR	7'-0"	3'-0"	METAL	90M	HOLLOW METAL	STAIR		WITH NARROW LIGHT	22	BARN	7'-0"	3'-0"	WOOD	-
00.1 BAS	SEMENT: 7									22A	2-PANEL	7'-0"	2'-0"	WOOD	-
										30	20MIN	7'-0"	3'-0"	WOOD	20M
01 FIRST		_	1				T			31	2-PANEL	7'-0"	3'-0"	WOOD	-
102A	FLUSH	7'-0"	3'-0"	WOOD	-	HOLLOW METAL				32	BARN	7'-0"	3'-0"	WOOD	-
102B	FLUSH	7'-0"	3'-0"	WOOD	-	HOLLOW METAL			OTAINED MOOD VENEED TO MATCH DANIELING	32A	2-PANEL	7'-0"	2'-0"	WOOD	-
103	CORRIDOR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	PASSAGE		STAINED WOOD VENEER TO MATCH PANELING	40	20MIN	7'-0"	3'-0"	WOOD	20M
103A 104	EXT.NL TRASH	7'-0" 7'-0"	3'-0" 3'-6"	METAL METAL	90M	HOLLOW METAL				41	2-PANEL BARN	7'-0" 7'-0"	3'-0" 3'-0"	WOOD WOOD	-
110	90MIN	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	ADADTMENT			42A	2-PANEL	7'-0"	2'-0"	WOOD	-
120	90MIN	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL				50	20MIN	7'-0"	3'-0"	WOOD	20M
S1-1	STAIR FLUSH	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	ALAITIMENT		STAINED WOOD VENEER TO MATCH PANELING	51	2-PANEL	7'-0"	3'-0"	WOOD	20101
S1-8	CORRIDOR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	PASSAGE		CITAINED WOOD VEHEER TO MATERIA MEERICA	52	BARN	7'-0"	3'-0"	WOOD	-
S2-1	STAIR	7'-0"	3'-0"	METAL	90M	HOLLOW METAL			WITH NARROW LIGHT	52A	2-PANEL	7'-0"	2'-0"	WOOD	-
01 FIRST	FLR: 10									60	20MIN	7'-0"	3'-0"	WOOD	20M
										61	2-PANEL	7'-0"	3'-0"	WOOD	-
02 SECO	ND FLR				_			_		62	BARN	7'-0"	3'-0"	WOOD	-
201A	STORAGE	7'-0"	3'-0"	WOOD	-	HOLLOW METAL				70	20MIN	7'-0"	3'-0"	WOOD	20M
201B	STORAGE	7'-0"	3'-0"	WOOD	-	HOLLOW METAL				72	2-PANEL	7'-0"	3'-0"	WOOD	-
S1-2	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL			WITH NARROW LIGHT	00.1 BAS	SEMENT: 25				
S2-2	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	STAIR		WITH NARROW LIGHT	04 51003	. ELD				
UZ 3EUU	ND FLR: 4									01 FIRST 121	2-PANEL	7'-0"	3'-0"	WOOD	Ī
03 THIRI	O FLOOR									121	2-PANEL	7'-0"	3'-0"	WOOD	_
301A	STORAGE	7'-0"	3'-0"	WOOD	_	HOLLOW METAL	STOREROOM			122A	BI-FOLD	7'-0"	5'-0"	WOOD	
302	STORAGE	7'-0"	3'-0"	WOOD	_	HOLLOW METAL				310C	2-PANEL	7'-0"	3'-0"	WOOD	-
S1-3	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL			WITH NARROW LIGHT	310D	PRIVACY	7'-0"	3'-0"	WOOD	
S2-3	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL			WITH NARROW LIGHT	310F	2-PANEL	7'-0"	2'-0"	WOOD	-
03 THIRE	FL00R: 4			11	1			•		310M	POCKET	7'-0"	2'-10"	WOOD	-
										310R	2-PANEL	7'-0"	2'-8"	WOOD	-
	JRTH FLOOR SLA		0.00			T	T			01 FIRST	FLR: 8				
402	FLUSH	7'-0"	3'-0"	WOOD	-	HOLLOW METAL				00.0500	ND ELD				
403	FLUSH	7'-0"	3'-0"	WOOD	-	HOLLOW METAL	CTODEDOOM			02 SEC0		71.011	21 011	WOOD	2014
405 406	STORAGE STORAGE	7'-0" 7'-0"	3'-0" 3'-0"	WOOD WOOD	-	HOLLOW METAL				210 210A	20MIN 2-PANEL	7'-0" 7'-0"	3'-0" 2'-6"	W00D W00D	20M
419	FLUSH	7'-0"	3'-0"	METAL	-	HOLLOW METAL	OTUNENUUN			210A 211	PRIVACY	7'-0"	3'-0"	WOOD	
S1-4	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL	STAIR		WITH NARROW LIGHT	211A	2-PANEL	7'-0"	2'-6"	WOOD	<u> </u>
S2-4	STAIR	7'-0"	3'-0"	WOOD	90M	HOLLOW METAL			WITH NARROW LIGHT	212	POCKET	7'-0"	2'-10"	WOOD	-
	JRTH FLOOR SLA			.,,,,,,	1 00111	1.02207 MEI/IE	1	ı		213	PRIVACY	7'-0"	3'-0"	WOOD	
										213A	2-PANEL	7'-0"	2'-6"	WOOD	-
										214	2-PANEL	7'-0"	3'-0"	WOOD	-
										220	OUMINI	7: 0"	21 011	WOOD	2014

)00R	SCHEDU	LE - STOR	EFRONT	
			DOOR			FRAME			
NO.	TYPE	HEIGHT	WIDTH	MATERIAL	FIRE RATING	MATERIAL	Operation	Hardware	Comments
01 FIRS	FLR								
404	STOREFRONT	8'-1"	6'-0"	ALUM. GL.	-	ALUM.			
101		8'-1"	3'-0"	ALUM. GL.	-	ALUM.			
101	STOREFRONT	0 1							

240A	2-PANEL	7'-0"	2'-10"	WOOD	-	WOOD	CLOSET	
241	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
241A	BYPASS	7'-0"	4'-0"	WOOD	-	WOOD	CLOSET SLIDE	
242	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
243	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
243A	BYPASS	7'-0"	4'-0"	WOOD	-	WOOD	CLOSET SLIDE	
244	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
02 SECON	ND FLR: 29	•		I.	•		"	
03 THIRD	FL00R							
310	20MIN	7'-0"	3'-0"	WOOD	20M	WOOD	APARTMENT	
310A	2-PANEL	7'-0"	2'-10"	WOOD	-	WOOD	CLOSET	
310B	POCKET	7'-0"	2'-10"	WOOD	-	WOOD	POCKET	
311	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
311A	BYPASS	7'-0"	4'-0"	WOOD	-	WOOD	CLOSET SLIDE	
312	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
313	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
313A	BYPASS	7'-0"	4'-0"	WOOD	-	WOOD	CLOSET SLIDE	
314	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
320	20MIN	7'-0"	3'-0"	WOOD	20M	WOOD	APARTMENT	
321	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
321A	POCKET	7'-0"	2'-10"	WOOD	-	WOOD	POCKET	
322	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
330	20MIN	7'-0"	3'-0"	WOOD	20M	WOOD	APARTMENT	
330A	2-PANEL	7'-0"	2'-6"	WOOD	-	WOOD	PRIVACY	
331	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
331A	POCKET	7'-0"	2'-10"	WOOD	-	WOOD	POCKET	
332	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
333	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
333A	2-PANEL	7'-0"	2'-6"	WOOD	-	WOOD	PRIVACY	
334	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
340	20MIN	7'-0"	3'-0"	WOOD	20M	WOOD	APARTMENT	
340A	2-PANEL	7'-0"	2'-6"	WOOD	-	WOOD	PRIVACY	
341	2-PANEL	7'-0"	3'-0"	WOOD	-	WOOD	PRIVACY	
342	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
342A	2-PANEL	7'-0"	2'-6"	WOOD	-	WOOD	PRIVACY	
343	POCKET	7'-0"	2'-10"	WOOD	-	WOOD	POCKET	
344	PRIVACY	7'-0"	3'-0"	WOOD		WOOD	PRIVACY	
344A	2-PANEL	7'-0"	2'-6"	WOOD	-	WOOD	PRIVACY	
	2-PANEL FLOOR: 29	/'-0"	2'-6"	MOOD	-	WOOD	PRIVACY	

DOOR SCHEDULE - RESIDENTIAL WD

APARTMENT

APARTMENT

PRIVACY

CLOSET

PRIVACY

CLOSET

APARTMENT

PRIVACY

APARTMENT

BARN

CLOSET

PRIVACY

BARN

CLOSET

APARTMENT

PRIVACY

APARTMENT

BARN

WOOD PRIVACY

WOOD PRIVACY

WOOD PRIVACY

WOOD POCKET WOOD CLOSET

PRIVACY

APARTMENT

PRIVACY

PRIVACY

POCKET

PRIVACY

PRIVACY

PRIVACY

PRIVACY

PRIVACY

POCKET

PRIVACY

WOOD PRIVACY

WOOD PRIVACY

WOOD PRIVACY

WOOD APARTMENT

WOOD POCKET

PRIVACY

APARTMENT

PRIVACY

POCKET

APARTMENT

CLOSET

BARN

APARTMENT

PRIVACY

BARN

WOOD

HOLLOW METAL WOOD

7'-0" 3'-0" WOOD 20M

7'-0" 3'-0" WOOD 20M

7'-0" 3'-0"

7'-0" 2'-10"

7'-0" 2'-10" 7'-0" 2'-6" 7'-0" 2'-10"

7'-0" 3'-0"

223A 2-PANEL 7'-0" 2'-6" WOOD

224 2-PANEL 7'-0" 3'-0" WOOD

2-PANEL 20MIN 2-PANEL

PRIVACY

POCKET

PRIVACY

20MIN

POCKET 2-PANEL

7'-0" 3'-0" WOOD

7'-0" 2'-6" WOOD

7'-0" 3'-0" WOOD

7'-0" 3'-0" WOOD

7'-0" 2'-6" WOOD

7'-0" 3'-0" WOOD

7'-0" 3'-0" WOOD

7'-0" 3'-0" WOOD 20M

WOOD

WOOD

WOOD

WOOD


WOOD

TRAVIS ST. APARTMENTS


HISTORIC RENOVATION AND ADDITION

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



WELTY ARCHITECTURE, LLC Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com



NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably


This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

inferable from them as being necessary to produce the indicated results. WA PROJECT NO: OCTOBER 8, 2020

PROJECT ISSUE DATE: REV. # REVISION DESCRIPTION DATE 2020-03-29 **BID SET** ADD#1 4-22-2020 PERMIT SET 10-8-2020

SHEET TITLE: DOOR AND WINDOW SCHEDULE

DRAWN BY: SJW



HISTORIC RENOVATION AND ADDITION

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

 WA PROJECT NO:
 19-001

 PROJECT ISSUE DATE:
 OCTOBER 8, 2020

 REV. #
 REVISION DESCRIPTION DATE

 BID SET
 2020-03-29

 1
 ADD#1


 2
 PERMIT SET


 10-8-2020


SHEET TITLE:
SITE PLAN


DRAWN BY: SJW



















- 1. THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL, SEE DETAIL LA-7 FOR EXPANSION JOINT AT A DECK AND WALL LOCATION. 2. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF
- MEMBRANE APPLICATION. 3. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR COPINGS.

BASE FLASHING AT PARAPET WALL WITH METAL COPING

4. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.



- 1. THIS DETAIL ILLUSTRATES ANOTHER METHOD OF ELIMINATING PITCH POCKETS AND AN OPTIONAL METHOD OF GROUPING PIPING THAT MUST COME ABOVE THE ROOF SURFACE. 2. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF
- MEMBRANE APPLICATION. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING,
 CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL
- 4. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION. BASE FLASHING AT SHEET-METAL HOOD FOR PIPING THROUGH ROOF DECK




NOTES:

DETAIL DEPICTS THE WEATHERPROOFING PROTECTION AND DOES NOT REPRESENT LIGHTNING PROTECTION DESIGN.
 REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF

REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.


CABLE PENETRATION



NOTES:


- 1. THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL. SEE DETAIL LA-7 FOR EXPANSION JOINT AT A DECK AND WALL LOCATION. 2. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF
- MEMBRANE APPLICATION. 3. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR COPINGS. 4. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

BASE FLASHING WITH SURFACE-MOUNTED COUNTERFLASHING AT CONCRETE WALL



- VENT STACKS AND OTHER PIPES SHOULD HAVE A MINIMUM OF 12 INCHES OF CLEARANCE ON ALL SIDES FROM WALLS, CURBS AND OTHER PROJECTIONS TO FACILITATE PROPER FLASHING. SEE THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL
- 2. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF MEMBRANE APPLICATION.
 3. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.


PLUMBING VENT OR PIPE PENETRATION



THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL. CONDUCTER HEAD TO BE 1 INCH MINIMUM BELOW BOTTOM OF THROUGH-WALL SCUPPER.

- REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF MEMBRANE APPLICATION.


 4. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SCUPPERS. 5. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.
- THROUGH-WALL SCUPPER



NOTES:


- 1. AN AREA DIVIDER SHOULD NEVER RESTRICT THE FLOW OF WATER. 2. FLASHING REQUIREMENTS TYPICAL FOR BOTH SIDES OF THE EXPANSION JOINT.
- 3. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF 4. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING,
- CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL 5. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

BASE FLASHING AT AREA DIVIDER IN ROOF SYSTEM



- 1. THIS DETAIL IS DESIGNED TO ELIMINATE ROOF DAMAGE DUE TO EXPANSION AND CONTRACTION OF PIPES, PIPE SUPPORT PROFILES VARY. 2. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL
- . REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

PIPE SUPPORT CURB




THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL.
 ELEVATION OF SCUPPER MAY VARY.
 REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF

5. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

- MEMBRANE APPLICATION.
 4. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL; ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SCUPPERS.

OVERFLOW SCUPPER



ALL SKYLIGHTS.

APPLICATION.

RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF MEMBRANE

REFER TO THE ARCHITECTURAL METAL FLASHING

SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN,


JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL

REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

- BASE OF UNIT EXTENDS 1/2" MINIMUM BEYOND TOP OF - SEALING MATERIAL-MUST BE CONTINUOUS ON TOP OF THE CURB 1" MINIMUM BELOW TOP OF CURB WOOD NAILER - FASTENERS FLASHING RECEIVER - COUNTERFLASHING - BASE FLASHING - RAISED CURB


SEAL 10-21-2020 HAVE BEEN INSTALLED. WHERE THE SKYLIGHT, SCUTTLE OR SMOKE VENT FRAME OVERLAPS THE BASE FLASHING AT LEAST 3 INCHES, THE REMOVABLE SHEET-METAL COUNTERFLASHING IS NOT NRCA RECOMMENDS DESIGNERS CONSIDER PERMANENT INTERNAL OR EXTERNAL FALL-PROTECTION DEVICES AT REFER TO THE MANUFACTURER FOR

BASE FLASHING AT PREFABRICATED METAL CURB



THIS DETAIL IS DESIGNED TO ELIMINATE ROOF DAMAGE DUE TO EXPANSION AND CONTRACTION OF PIPES. PIPE SUPPORT PROFILES VARY, REFER TO THE MANUFACTURER FOR LOAD CAPACITY AND RECOMMENDED SPACING OF SUPPORTS.

REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION. PIPE SUPPORT



NOTES:

- 1. IN CLIMATES WHERE THE WINTER TEMPERATURE REMAINS BELOW FREEZING FOR EXTENDED PERIODS OF TIME, NRCA SUGGESTS INTERIOR DRAINS TO DRAIN THE ROOF.

 GUTTER BRACKETS ARE RECOMMENDED TO BE AT LEAST ONE GAUGE HEAVIER THAN GUTTER STOCK.
- 3. REFER TO THE MANUFACTURER FOR RECOMMENDATIONS ON ACCEPTABLE SUBSTRATE MATERIALS FOR THE LIQUID-APPLIED ROOF

5. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

- REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR PERIMETER
- **GUTTER WITH PERIMETER EDGE METAL**

the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJE	19-0	
PROJECT I	OCTOBER 8, 20	
REV. #	REVISION DESCRIPTION BID SET	DATE 2020-03-29
1	ADD#1	4-22-2020
2	PERMIT SET	10-8-2020

ROOF DETAILS LIQUID APPLIED AT ROOF DECK

Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

WELTY ARCHITECTURE, LLC

Scott Welty - Architect

3021 42nd St

TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND

ADDITION

505 E. TRAVIS STREET


SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC

This drawing as an instrument of service is the property of the Architect and may be used only on

DRAWN BY: SJW








NOTES:

- 1. THIS DETAIL DOES NOT ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN THE DECK AND WALL. SEE DETAIL SP-7 FOR EXPANSION JOINT AT A DECK-TO-WALL LOCATION.
- 2. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ALTERNATIVE BASE SECUREMENT OPTIONS.

 3. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING. CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR COPINGS. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.
- BASE FLASHING AT PARAPET WALL WITH METAL COPING








NOTES:

DETAIL DEPICTS THE WEATHERPROOFING PROTECTION AND DOES NOT REPRESENT LIGHTNING PROTECTION DESIGN.


REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

CABLE PENETRATION




- 1. REFER TO MANUFACTURERS' SPECIFICATIONS FOR SPECIFIC REQUIREMENTS FOR BASE MEMBRANE ATTACHMENT AND PLACEMENT. MECHANICALLY ATTACHED SYSTEMS GENERALLY HAVE SPECIFIC ATTACHMENT REQUIREMENTS FOR PERIMETER LOCATIONS. 2. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING,
- CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR GRAVEL STOPS. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

EMBEDDED EDGE-METAL FLASHING [GRAVEL STOP] WITH MEMBRANE COATING




- 1. THIS DETAIL ILLUSTRATES ANOTHER METHOD OF ELIMINATING PITCH POCKETS AND AN OPTIONAL METHOD OF GROUPING PIPING THAT
- 2. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ALTERNATIVE BASE SECUREMENT OPTIONS, REFER TO MANUFACTURERS' SPECIFICATIONS FOR SPECIFIC REQUIREMENTS FOR BASE MEMBRANE ATTACHMENT AND PLACEMENT. MECHANICALLY ATTACHED SYSTEMS GENERALLY HAVE SPECIFIC ATTACHMENT REQUIREMENTS FOR PENETRATION LOCATIONS.
- 3. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL 4. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

BASE FLASHING AT MEMBRANE-COATED SHEET-METAL HOOD FOR PIPING THROUGH ROOF DECK



1. IN CLIMATES WHERE THE WINTER TEMPERATURE REMAINS BELOW FREEZING FOR EXTENDED PERIODS OF TIME, NRCA SUGGESTS INTERIOR DRAINS TO DRAIN THE ROOF. GUTTER BRACKETS ARE RECOMMENDED TO BE AT LEAST ONE GAUGE HEAVIER THAN GUTTER STOCK.


- ON BALLASTED SYSTEMS, A DRAINAGE BAR TO RETAIN BALLAST IS REQUIRED.
- REFER TO MANUFACTURERS' SPECIFICATIONS FOR SPECIFIC REQUIREMENTS FOR BASE MEMBRANE ATTACHMENT AND PLACEMENT. MECHANICALLY ATTACHED SYSTEMS GENERALLY REQUIRE SPECIFIC ATTACHMENT REQUIREMENTS FOR PERIMETER LOCATIONS. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR PERIMETER
- REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.
- **GUTTER WITH MEMBRANE-COATED PERIMETER EDGE METAL**



NOTES:


- 1. AN AREA DIVIDER SHOULD NEVER RESTRICT THE FLOW OF WATER. FLASHING REQUIREMENTS ARE TYPICAL FOR BOTH SIDES OF THE AREA DIVIDER.
- 3. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ALTERNATIVE BASE SECUREMENT OPTIONS. 4. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR SHEET-METAL
- 5. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

BASE FLASHING AT AREA DIVIDER IN ROOF SYSTEM



- 1. VENT STACKS AND OTHER PIPES SHOULD HAVE A MINIMUM OF 12 INCHES OF CLEARANCE ON ALL SIDES FROM WALLS, CURBS AND OTHER PROJECTIONS TO FACILITATE PROPER FLASHING. SEE THE INTRODUCTION TO THE CONSTRUCTION DETAILS FOR ADDITIONAL
- 2. REFER TO MANUFACTURERS' SPECIFICATIONS FOR SPECIFIC REQUIREMENTS FOR BASE MEMBRANE ATTACHMENT AND PLACEMENT. MECHANICALLY ATTACHED SYSTEMS GENERALLY HAVE SPECIFIC ATTACHMENT REQUIREMENTS FOR PENETRATION LOCATIONS.

 REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.
- PLUMBING VENT [FIELD WRAP]




THROUGH ROOF DECK

- THIS DETAIL ILLUSTRATES ANOTHER METHOD OF ELIMINATING PITCH POCKETS AND AN OPTIONAL METHOD OF GROUPING PIPING THAT MUST COME ABOVE THE ROOF SURFACE. 2. MANY MANUFACTURERS OFFER PREFABRICATED BOOTS AND OTHER MATERIALS FOR THIS PURPOSE, SPECIFICS ABOUT THESE
- PROPRIETARY DESIGNS VARY GREATLY, AND INDIVIDUAL MANUFACTURER'S SPECIFICATIONS SHOULD BE CONSULTED FOR THEIR USE.

 3. WHERE THE SHEET-METAL ENCLOSURE OVERLAPS THE BASE FLASHING AT LEAST 3 INCHES, THE REMOVABLE SHEET-METAL COUNTERFLASHING IS NOT REQUIRED.
- 4. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ALTERNATIVE BASE SECUREMENT OPTIONS. REFER TO THE ARCHITECTURAL METAL FLASHING SECTION OF THE NRCA ROOFING MANUAL: ARCHITECTURAL METAL FLASHING, CONDENSATION AND AIR LEAKAGE CONTROL, AND REROOFING FOR DESIGN, JOINERY AND SECUREMENT OPTIONS FOR
- COUNTERFLASHINGS. 6. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.

BASE FLASHING AT SHEET-METAL ENCLOSURE FOR PIPING



NOTES:

- 1. THIS DETAIL IS DESIGNED TO ELIMINATE ROOF DAMAGE DUE TO EXPANSION AND CONTRACTION OF PIPES. PIPE SUPPORT PROFILES VARY, REFER TO THE MANUFACTURER FOR LOAD CAPACITY AND RECOMMENDED SPACING OF SUPPORTS. REFER TO THE INTRODUCTION OF THE CONSTRUCTION DETAILS CHAPTER FOR ADDITIONAL INFORMATION.
- PIPE SUPPORT

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND

ADDITION

505 E. TRAVIS STREET

SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC

SEAL 10-21-2020

WELTY ARCHITECTURE, LLC

Scott Welty - Architect

3021 42nd St

Metairie, LA 70001

p. 504-931-1665

www.weltyarchitecture.com

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and


is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results. WA PROJECT NO:

> PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION 2020-03-29 **BID SET** ADD#1 4-22-2020 PERMIT SET 10-8-2020

ROOF DETAILS - TPO AT NEW ROOFTOP ADDITION

DATE

DRAWN BY: SJW



HISTORIC RENOVATION AND **ADDITION**

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

> > 505 TRAVIS BAUDHAUS LLC



WELTY ARCHITECTURE, LLC Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

GENERAL NOTE:

ON DIMENSIONED PLANS ONLY, MEASUREMENTS SHOWN ARE TO STUD FACE UNLESS NOTED OTHERWISE. VERIFY MEASUREMENTS IN FIELD AND NOTIFY ARCHITECT OF ANY DESCEPENCEIS.

PRIORITIES OF MEASUREMENTS

1. SET STAIR WIDTHS

2. SET CORRIDOR WIDTHS 3. SET BATHROOM WIDTHS
4. REMAINING MEASUREMENTS

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION DATE 2020-03-29 4-22-2020


ADD#1 PERMIT SET

DIMENSIONED PLANS 2ND AND 3RD FLOORS


DRAWN BY: SJW

A122

10-8-2020







HISTORIC RENOVATION AND ADDITION

505 E. TRAVIS STREET

505 TRAVIS BAUDHAUS LLC

SAN ANTONIO, TEXAS 78205



WELTY ARCHITECTURE, LLC Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION ADD#1

PERMIT SET

GENERAL SECTIONS

DRAWN BY: SJW

HISTORIC RENOVATION AND ADDITION

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC

Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com



This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO:

GENERAL SECTIONS


DRAWN BY: SJW

OCTOBER 8, 2020

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC





This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: REV. # REVISION DESCRIPTION

ADD#1 PERMIT SET

GENERAL SECTIONS

OCTOBER 8, 2020

DRAWN BY: SJW

HISTORIC RENOVATION AND ADDITION

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: 19-001
PROJECT ISSUE DATE: OCTOBER 8, 2020

REV. # REVISION DESCRIPTION DATE


BID SET 2020-03-29

1 ADD#1 4-22-2020
2 PERMIT SET 10-8-2020

SHEET TITLE:

ROOFTOP ELEVATIONS

DRAWN BY: SJW



OCTOBER 8, 2020

HISTORIC RENOVATION AND **ADDITION**

> 505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

> > 505 TRAVIS BAUDHAUS LLC

3021 42nd St

Metairie, LA 70001 p. 504-931-1665



This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: OCTOBER 8, 2020 REV. # REVISION DESCRIPTION 4-22-2020 ADD#1 PERMIT SET

ENLARGED FLOOR PLANS AT ELEVATOR AND STAIR

DRAWN BY: SJW

HISTORIC RENOVATION AND **ADDITION**

505 E. TRAVIS STREET

505 TRAVIS BAUDHAUS LLC




WELTY ARCHITECTURE, LLC Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

OCTOBER 8, 2020 REV. # REVISION DESCRIPTION 4-22-2020 ADD#1 PERMIT SET

ENLARGED STAIR PLANS AND







HISTORIC RENOVATION AND ADDITION


505 TRAVIS BAUDHAUS LLC

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205









This drawing as an instrument of service is the property of the Architect and may be used only on the project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

DATE 10-8-2020

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

WA PROJECT NO: PROJECT ISSUE DATE: REV. # REVISION DESCRIPTION

ENLARGED PLAN AT ADA UNIT

required to make the work complete and operational shall be included. Existing Site Conditions and Restrictions: Contractor shall review construction documents and provide necessary site work, and excavation as required to construct said project.

All materials, supplies and equipment shall be installed per manufacturer's recommendations and per

applicable codes and requirements. Material stored on site shall be protected from damage by moisture,

wind, sun, abuse or any other harmful effects. Execution: The execution of all work shall be in strict accordance with these specifications and manufacturer's written specifications or Material's Institute Standards. Where the manufacturer's recommended details are used, the manufacturer shall be responsible for the performance of their product. All work not specifically mentioned that is required to make the work complete and operational shall be

Cleaning and Waste Management: Construction site to be in a clean and orderly condition throughout the construction process. Clean interior spaces prior to the start of finish painting and the application of other finishes. At the conclusion of construction, the project shall be properly cleaned. This should include but not be limited to; cleaning the interior and exterior glass, surfaces exposed to view, remove temporary labels, stains and foreign substances, polish transparent and glossy surfaces, vacuum soft surface areas, sweep and mop all tiled surfaces, etc. Replace filters of operating equipment. Clean equipment and fixtures to a sanitary condition. Remove all waste and surplus materials. Contracting Requirements:

Permits: Contractor to apply and pay for permits. Submit written copy to Architect prior to start of Work. Comply with Owner's requirements for contracts, insurance, security, loading. All bonding and insurance requirements shall be coordinated with the Owner prior to beginning

construction. All contractors shall provide and be solely responsible for necessary barricades and safety precautions, and strictly adhere to all governing codes on safety, including the OSHA Act. 1. Drawings and specifications are complementary and intended to provide the basis for the proper

The Contractor shall check and verify all dimensions and conditions before proceeding with construction. Do not scale drawings. Noted dimensions take precedence. Workmanship shall conform to the best and highest standards of quality in each trade and shall include all items of fabrication, construction and installation. All work shall be completed by skilled tradesmen and mechanics. Installation of all equipment and materials shall be in strict accordance with manufacturers

recommendations. Items not expressly set forth but which are reasonably implied or necessary for the proper performance of this work shall be included.

. Coordinate the work of all trades. Prepare coordination drawings for areas above ceilings where close tolerances are required between building elements and mechanical and electrical work. Verify location of utilities and existing conditions. Notify Architect of conditions differing from those indicated on the Drawings. 4. The Contractor shall check and verify all dimensions and conditions before proceeding with construction.

Cutting and Patching: Provide cutting and patching work to properly complete the Project. Do not remove or alter structural components without written approval.

completion of the Work and suitable for the intended use of the Owner.

Cut with tools appropriate for materials to be cut. Patch with materials and methods to produce patch which is not visible from a distance of five feet. Do not cut and patch in a manner that would result in a failure of the work to perform as intended. decrease fire performance, decrease acoustical performance, decrease energy performance, decrease operational life, or decrease safety factors.

. Verify and locate utilities, existing facilities, and equipment. **Project Meetings:**

Do not scale drawings. Noted dimensions take precedence.

. Arrange for a preconstruction conference prior to start of construction. Meeting shall be attended by Owner, Architect, Contractor, and major subcontractors. . Arrange for progress meetings once a month during construction, prior to application for payment. Record minutes and distribute promptly.

1. Submit a project schedule within 30 days of Project award and update at least monthly. . Submit for approval all submittals listed in individual sections. Submit electronically, in PDF format, maximum size 11x17. Submittals shall clearly indicate deviations from requirements of the Contract Documents. Submittals shall include details of construction and adjacent construction as applicable. For physical samples, submit 3 representative samples. For submittals which require larger paper size for proper review, submit 3 printed copies.

All submittals shall be reviewed and approved by Contractor prior to submitting to the Architect for review. Any submittal not stamped as approved by the Contractor will be returned without review. Timing of Submittals: Submit to allow at least 5 business days for review and handling. Submittals which have to be reviewed by the Architect and one of his consultants require at least 10 business days for review and handling. Add 5 business days for each additional consultant who must review a submission. 4. Architect's Action on Submittals: Architect will review submittals, stamp with "action stamp", mark action, and return to Contractor. Architect will review submittals only for conformance with the design concept of the without limitation, performance requirements, field dimensions, fabrication methods, means, methods, techniques, sequences and procedures of construction, coordination with other work. The Architect's review and approval of submittals shall be held to the limitations stated in the Owner/Architect Agreement and the Conditions of the Contract. In no case shall approval or acceptance by the Architect be interpreted as a release of Contractor of his responsibilities to fulfill all of the requirements of the Contract Documents. 5. Required Resubmittal: Unless submittal is noted "reviewed and approved" or "reviewed and approved

except as noted, resubmission not required," make corrections or changes to original and resubmit to Architect. 6. Distribution: When submittal is noted "approved" or "approved as noted, resubmittal not required," make prints or copies and distribute to Owner, Subcontractors involved, and to all other parties requiring information from the submittal for performance or coordination of related work. Print shop drawings for distribution only from the final approved reproducible. Include details of construction and adjacent construction in shop drawings. Clearly indicate any deviations

from requirements of the contract documents. Fabricate materials from approved shop drawings only. **Request for Interpretation (RFIs)** Procedure: Immediately on discovery of the need for interpretation of the Contract Documents, and if not possible to request interpretation at Project meeting, prepare and submit an RFI in the form specified. RFIs shall originate with Contractor. RFIs submitted by entities other than Contractor will be returned with

3. Content of the RFI shall include a detailed, legible description of item needing interpretation. 4. Architect will review each RFI, determine action required, and return it. Allow three working days for Architect's response for each RFI. RFIs received after 1:00 p.m. will be considered as received the following

 Requests for approval of submittals. Requests for approval of substitutions. c. Requests for coordination information already indicated in the Contract Documents.

5. The following RFIs will be returned without action:

d. Requests for adjustments in the Contract Time or the Contract Sum. e. Requests for interpretation of Architect's actions on submittals. f. Incomplete RFIs or RFIs with numerous errors.

Comply with applicable codes, regulations, ordinances and requirements of authorities having jurisdiction, including accessibility guidelines where applicable. Submit copies of inspection reports, notices and similar documents to Architect Provide products of acceptable manufacturers which have been in satisfactory use in similar service for

3. Use experienced installers. Furnish evidence of experience if requested. 4. Deliver, handle, and store materials in strict accordance with manufacturer's instructions. Use of any supplier or subcontractor is subject to Owner's approval. Engage and pay for testing agencies as required. Refer to individual sections for additional requirements.

Temporary Facilities Provide temporary facilities and connections as required for the proper completion of the project. Meter and pay for utility service.

Provide temporary sanitary facilities Provide temporary barricades as necessary to ensure protection of the public. 8. Provide suitable waste disposal units and empty regularly. Do not permit accumulation of trash and waste

. Maintain legal egress within and around construction areas. 0. Maintain fire alarm systems in operation during construction. . Provide fire extinguishers in work areas during construction. 2. Provide temporary protection for adjacent construction. Promptly repair any damage at no additional cost

Products and Substitutions Provide products and materials specified. Request Architect's selection of colors and accessories in sufficient time to avoid delaying progress of the Work.

Submit requests for substitutions shall be in writing, including reasons. Submit sufficient information for Architect to evaluate proposed substitution. a. A Substitution Request for products, assemblies, materials and equipment constitutes a representation that the submitter:

b. Has investigated proposed product and determined that it meets or exceeds the quality level of the specified product, equipment, assembly, or system. c. Agrees to provide the same warranty for the substitution as for the specified product. d. Agrees to coordinate installation and make changes to other work that may be required for the work to

be complete, with no additional cost to Owner. e. Waives claims for additional costs or time extension that may subsequently become apparent. Remove and replace work which does not conform to the contract documents at no additional expense to

Inspect substrates and report unsatisfactory conditions in writing. Do not proceed until unsatisfactory conditions have been corrected. Take field measurements prior to fabrication where practical. Form to required shapes and sizes with true edges, lines and angles. Provide inserts and templates as needed for work of other trades Install materials in exact accordance with manufacturer's instructions and approved submittals.

Install materials in proper relation with adjacent construction and with proper appearance. Restore units damaged during installation. Replace units which cannot be restored at no additional expense . Refer to additional installation requirements and tolerances specified under individual specification

Submit accurate record documents of building and site. Submit operating manuals, maintenance manuals, and warranty information. Obtain and submit copy of occupancy permits.

Remove temporary facilities and provide final cleaning and touch up. Restore portions of building, site improvements, landscaping and other items damaged by construction operations to the satisfaction of the Architect at no additional expense to the Owner.

The following are prerequisites to substantial completion. Provide the following:

Complete punchlist items promptly at no additional expense to the Owner.

Punch list prepared by Contractor and subcontractors as applicable. Supporting documentation. Warranties.

. Prepare punchlist for remaining work for review by the Architect.

Occupancy permit. Start-up and testing of building systems. Change over of locks. Meter readings. Commissioning documentation

Certifications.

10. Final Acceptance: Provide the following prerequisites to final acceptance: 11. Final payment request with supporting affidavits. **12.** Completed punch list.

SECTION 012100 - ALLOWANCES Include scheduled allowances in the project cost; allowance is for cost of materials only. Installation and all other costs are to be included in base price and separate from allowance amounts. 2. Submit invoices to indicate actual quantities of materials delivered and costs. Indicate amounts of

pplicable trade discounts. 1. Allowance #1: None at this time. **SECTION 012300 - ALTERNATES**

1. Submit price for each alternate. Include cost of modifications to other work to accommodate alternate. Include statement of impact on schedule, if any. Architect and Owner will determine which alternates are

1. Alternate No. 1: Additive Alternate to include supply and install of window shades in all residential apartment areas. Blackout shades in bedroom and bathrooms, Standard shades in remaining areas.

SECTION 019000 - ABATEMENT

1. Hazardous material testing has been completed by an independent laboratory. Request report from Owner. Abatement work will be completed as part of the work based on the independent laboratory results and directives. 2. Selective Abatement work has been completed under a separate contract. Request abatement report from the Owner to identify items that have been abated and items that will still require abatement.

SECTION 024100 - DEMOLITION

1. Provide selective demolition of interior partitions, systems, and components designated to be removed. 2. Selective demolition work has been completed under a separate contract. Review site conditions to verify

3. Provide selective demolition of portion of the exterior facade, structures, and components designated to be 4. Protect portions of building, site and adjacent structures affected by demolition operations. . Provide site demolition including designated paving, curbing, site walls, and utility structures. 6. Provide demolition of below grade foundations and site improvements to depth to avoid conflict with new

construction and site work. Remove hollow items or items which could collapse. Remove abandoned utilities and wiring systems. 9. Provide temporary protection for the public from demolition operations. 10. Provide pollution control during demolition operations as required by the City.

11. Provide removal and legal disposal of materials. 12. Refer to Construction Documents for additional demolition requirements. 14. Removal of hazardous materials has been indicated in report by independent laboratory. Notify Owner in writing if additional hazardous materials are encountered or suspected and stop work in that area until determination is made.

1. Submit demolition schedule. Include methods for protecting adjacent work and location of temporary

. Submit proposed location for legal disposal of materials, and permit if applicable. 1. Survey existing conditions and correlate with Drawings and specifications to verify extent of demolition

2. Verify conditions at site to determine whether demolition methods proposed for use will not endanger existing structures by overloading, failure, or unplanned collapse 3. Perform demolition operations by methods which do not endanger adjacent spaces, structures, or the

4. Perform demolition operations to prevent dust and pollutant hazards. Provide chutes as required to control dust and debris. 5. Historic items, relics, and other objects of interest or value found during demolition remain the property of

1. Comply with applicable codes and regulations for demolition operations and safety of adjacent structures and the public

Obtain required permits. Take precautions to prevent catastrophic or uncontrolled collapse of structures to be removed; do not allow worker or public access within range of potential collapse of unstable structures. 4. Provide, erect, and maintain temporary barriers and security devices.

1. Items to be Salvaged for Reinstallation: Refer to the Drawings and including but not limited to the items listed below. 2. Entry lobby terrazzo flooring, base, wood wall panels, wall medallions, and lighting cove.

SECTION 042000 - UNIT MASONRY

 Masonry restoration exterior and interior at damaged masonry and damaged joints per NPS guidelines. Section includes spot cleaning (water and/or chemical); replacement/repair of stone units; repointing mortar joints; parapet rebuilding; and repair of damaged masonry. For repointing, resetting, relaying of historic masonry as shown on the Drawings and as specified in the construction documents and Preservation Briefs 1, 2 revised, and 6, U.S. Department of the Interior, National Park Service, **Technical Preservation Services.**

2. Masonry patch and infill at doors and windows. 1. Mockup 4'x4' section. Can be used as part of the work. Face Brick:

Existing steel windows and exterior finish elements.

a. Size, Grade and Type: Match existing b. Bond Pattern: Match existing bond pattern c. Joint Type: Match existing 2. Concrete Masonry Units: a. Concrete Masonry Units: ASTM C 90, 1500 psi compressive strength, normal weight.

b. Size: Standard modular size by width required for application. c. Concrete Building Brick: ASTM C 55. d. Finish: Standard finish. e. Finish: Standard aggregate, split face finish.

Special Shapes: As required by building configuration. Bond Pattern: Running. h. Bond Pattern: Special, as indicated.

Bond Pattern: Match existing bond pattern. 4. Mortar and Grout: a. The repointing mortar shall match the original in color, grain size, and texture. The compressive strength of the repointing mortar shall be equal or less than the compressive strength of the original mortar and surrounding brick or stone. The replacement mortar shall contain approximately the same ingredient proportions of the original mortar.

b. Mortar Mix for new work: ASTM C 270, Type S, for reinforced masonry, masonry below grade and masonry in contact with earth and ASTM C 270, Type N, for above grade loadbearing and nonloadbearing walls and parapet walls and for interior loadbearing and nonloadbearing partitions.

c. Mortar Materials: Portland cement, ASTM C 150, Type I or II. d. Mortar Materials: Ready mixed, ASTM C 207, Type S materials.

e. Mortar Aggregate: Natural, ASTM C 144. f. Grout Aggregate: ASTM C 404. Hydrated Lime: ASTM C 207, Type S. ı. Color: Natural. Color: Colored pigmented mortar.

5. Reinforcing Steel: a. Reinforcing Bars: ASTM A 615, Grade 60. b. Deformed Reinforcing Wire: ASTM A 496. c. Plain Welded Wire Fabric: ASTM A 185.

Joint Reinforcing: Welded wire with deformed side rods, ladder or truss type.

Ties and Anchors:

 Bent Wire Ties: Galvanized steel. b. Rigid Anchors: Galvanized steel straps. c. Masonry to Concrete Frame: Two piece galvanized steel anchor.

d. Masonry to Steel Frame: Anchor with crimped wire anchor section for welding to steel. e. Adjustable Masonry Veneer Anchors: Screw attached two piece galvanized triangular or rectangular

 f. Screws for Steel Studs: ASTM C 954 organic polymer coated steel drill screws. Unit Type Masonry Inserts in Concrete: Malleable iron. h. Dovetail Slots: Galvanized sheet metal. i. Anchor Bolts: ASTM A 307, Grade A, galvanized.

Post installed Anchors: Chemical or expansion anchors. Masonry Accessories: Nonmetallic expansion joint strips. b. Preformed control joint gaskets.

c. Bond breaker strips.

 d. Weep sash and tubes 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements

2. Comply with PCA Recommended Practices for Laying Concrete Block, Brick Institute of America Tech Notes, and NCMA TEK Bulletins. 3. Comply with cold weather and warm weather protection procedures as recommended in BIA Tech

4. Provide fire rated assemblies complying with ASTM E 119. 5. Sawcut units when required. Maintain uniform joint width. Provide full bed, head and collar joints except at weepholes

6. Provide masonry weepholes above flashing in masonry cavity walls at 16" o.c. Install lintels and accessories in masonry construction.

Comply with applicable codes and regulations for spacing of ties and horizontal reinforcing. 10. Provide expansion and control joints in accordance with referenced publications.

11. Remove and replace damaged units. 12. Clean brick using bucket and brush method, BIA Tech Note 20. 13. Clean concrete masonry by dry brushing, NCMA TEK No. 28.

SECTION 051200 - STRUCTURAL STEEL FRAMING

Refer to Structural drawings and Specifications.

METAL FRAMING Refer to Structural Drawings for additional requirements

. Provide Cold Formed Metal Framing Units: a. Exterior load bearing steel stud walls. Design for deflection criteria not to exceed L/360 for stucco walls. Tolerances: Fabrication tolerance 1/8 inch in 10 feet; erection tolerance, 1/16 inch.

. Submit product data, shop drawings. Submit signed and sealed shop drawings for any work not fully detailed on the Construction Documents. 1. Studs and Track: ASTM C955; studs formed to channel, "C", or "Sigma" shape with punched web; Ushaped track in matching nominal width and compatible height.

2. Units 16 gage (0.598 inch) and heavier: ASTM A 446, yield point 50,000 psi. 4. Units 18 gage (0.0358 inch): ASTM A 446, yield point 37,000 psi. 6. Framing accessories, including bracing, bridging, solid blocking, plates, hangers, closers, reinforcement plates, anchors, clips, fasteners.

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications 2. Comply with AISC codes and specifications and with AWS Structural Welding Code.

SECTION 055100 - STEEL STAIR

Selection Includes: This Section specifies prefabricated metal stairs and railings. 1. General: Submit listed submittals in accordance with Contract Conditions.

2. Product data: Submit specified products as follows: Manufacturer's product data. Manufacturer's installation instructions 3. Shop Drawings: Indicate information on shop drawings as follows: 4. Stair plans, elevations, details, methods of installation and anchoring.

Furnish setting diagrams for anchorage installation as required.

Include calculations stamped by a structural engineer registered in the jurisdiction where the project the project is located. QUALITY ASSURANCE a. American Institute of Steel Construction (AISC) Certified Fabricator, having a minimum of 5 years'

Show members, sizes and thickness, anchorage locations and accessory items.

experience manufacturing components similar to or exceeding requirements specified in scope of 1. METAL STAIRS a. Basis of Design: Pre-Engineered Steel Stair System as manufactured by the Pacific Stair Corporation

b. Single Source Responsibility: Provide components, products and materials specified in this section from a single American Institute of Steel Construction (AISC) certified manufacturer. Unitized Flight Assemblies. Unitized Landing Frames. c. Manufactures standard rail products Picket as detailed or indicated on drawings. d. Treads (Noise Reduction Tread Assemblies as detailed or indicated on drawings.

2. Design Criteria: a. Structural Performance of Stairs: Stairs shall withstand the following structural loads without exceeding the allowable design working stress of materials, including anchors and connections. Apply each load to produce the maximum stress in each component: b. Treads and Platforms of Metal Stairs: Capable of withstanding a uniform load of 100 psf (4.8kM/m²) and concentrated load of 300 lbf (1.33kN) applied on an area of 4 square inches (2581 square mm). Concentrated and uniform loads need not be assumed to act concurrently

c. Stair Framing: Capable of withstanding stresses resulting from loads specified, in addition to stresses resulting from railing system loads. d. Limit Deflection of Treads, Platforms and Framing Members: To L/240. e. Structural Performance of Handrails and Railings: Handrails and railings shall withstand the following structural loads without exceeding the allowable design working stress of materials, including handrails, railings, anchors and connections. f. Top rail of Guardrail: Capable of withstanding a concentrated load of 200 lbf (0.89 kN) applied in any direction and a uniform load of 50 psf (2.39 kN/m²) applied in any direction. Concentrated and

uniform loads need not be assumed to act concurrently. Standard Stair and Rail System: a. Manufacturer's standard prefabricated, pre-engineered straight run stair and landing system, consisting of hot rolled steel sheet risers, treads, landings and structural plate, channel or angle frames, stringers or connection devices with fasteners/supports and railings.

a. Steel plate or channel with side mounted and/or top mounted railing frame attachment as detailed on drawings and/or in accordance with manufactures system recommendations b. Minimum thickness or weight as determined by structural design calculations, structural grade steel

Risers: Closed riser, minimum 14 gage (1.9mm) hot rolled mild steel sheet, sloped maximum 1 ½ inches (38.1mm) and conforming to Americans with Disabilities Act (ADA) nosing requirements. 6. Treads: Manufacturer's standard tread system, 14 gage (1.9mm) minimum hot rolled mild steel sheet or as determined by structural design calculations. All welds on the underside of tread assemblies to be exposed for proper inspection during the service life and/or after seismic, fire, flood, or potentially damaging event. Provide treads as indicated and noted on drawings for each stair

a. Checker Plate Tread: Pattern per manufacturer's standard. b. Quiet Tread: Factory applied sound absorption material bonded to underside of tread and intermediate landing surface for checker plate tread systems. Landings: A combination of structural plate, channel and angles for the frame with 1 ½" B-36 Composite Floor Decking x 20 gage and 10 gage (minimum) bent sheet lateral pour stops. Decking to be attached to

frame by plug welding or other mechanical means provided recommended and engineered by the stair a. Flight and landing assemblies fabricated by the stair manufacturer shall be connected by splined "Twist-Off" tension control bolts, grade to be A325 & A490 as engineered and specified by the stair

b. All pre-tensioning methods are to be conformant to the AISC Steel Construction Manual, Chapter 16; Section #3 Bolted Parts. Subsection 3.2.1 "pre-tensioned joints and related sections noted Additional Fastener and Supports: Sized by the manufacturer to meet structural design criteria. If hanger rod connections are applicable to any of the landing connections, they shall be threaded rod type, size and grade as determined by stair manufacturer's structural design calculations.

Railings: Design style as shown on drawings for each stair, selected from manufacturer's standard prefabricated, pre-engineered rail styles. a. Picket Rail: 1.5" x 1.5" x 11 gage HSS Top and Bottom Line Frame and Posts with 1.25" I.D. pipe

Hand Grab with 0.187" x 1.25" flat bar bracket and 0.5" Square Bar Pickets spaced not more than 4" on center. Weld Prep to equal NOMMA #3 or better. 10. Stringer Rail Mounting a. Structural Plate Stringer: Railings to be Side Mounted. Rail Frame: In-Line or Side assembly, see

a. Steel Shapes and Plates: To ASTM A36. b. Steel Pipe: To ASTM A53 Type E or S, Grade B. d. Structural Use: To ASTM A500, Grade B or C.

e. Non-Structural Use: To ASTM A513, hot rolled or coiled rolled (mill option). Steel Sheet: g. Structural Use: To ASTM A1011 (hot rolled), Checker Plate ASTM A786. h. Non-Structural Use: To ASTM A786, ASTM A1008. 12. Fasteners: As recommended by manufacturer.

13. Welding Rods: In accordance with AWS code and AWS filler metal specifications. a. Use same material finish as parts being joined. Use stainless steel between dissimilar metals and

non-corrosive fasteners at exterior connections or joints. b. Provide fasteners of sufficient strength to support connected members and loads, and to develop full strength of parts fastened or connected.

15. Construct stair and rails with all components necessary for support and anchorage, and for a complete

SECTION 055000 - METAL FABRICATIONS Provide metal fabrications: 2. Handrails and railings at existing stair. Delegated Structural Design, fabricate, and test railing assemblies in accordance with the most stringent requirements of applicable local code. Provide railings capable of withstanding structural loads required by ASCE 7.

Elevator pit ladders. Loose steel lintels Slotted channel framing for ceiling suspended items. Remodel existing metal fabrications as required for new construction. Tolerances: Fabrication tolerance 1/8 inch in 10 feet; erection tolerance, 1/16 inch.

1. Submit product data, shop drawings. 2. Submit signed and sealed shop drawings for any work not fully detailed on the Construction 3. Shop Drawings and structural analysis data signed and sealed by a qualified professional engineer registered in the state of Texas.

1. Steel Plates, Shapes and Bars: ASTM A 36. Steel Tubing: ASTM A 500 or A 501. Steel Pipe, Black Finish: ASTM A 53. Aluminum Extruded Bars and Shapes: ASTM B 221 aluminum alloy. Fasteners: noncorrosive, suitable for service intended. 9. Zinc Coating: Hot dip galvanized coating for materials in exterior assemblies or exterior walls. 10. Steel Finish: Primed. . Steel Finish: Baked enamel. 12. Aluminum Finish: Clear anodized.

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements Comply with ASTM E 985 for handrail and railing structural performance. Comply with AISC codes and specifications and with AWS Structural Welding Code. Take field measurements prior to fabrication, where possible. Form to required shapes and sizes with true, straight edges, lines and angles. Provide light-tight, hairline joints.

Install materials and systems in accordance with manufacturer's instructions and approved submittals.

Install materials and systems in proper relation with adjacent construction. Coordinate with work of other 6. Restore damaged finishes and protect work.

SECTION 061000 - ROUGH CARPENTRY

1. Provide Rough Carpentry for limited nailers and blocking. Project is Type II construction and wood members shall not be used for any framing members.

SECTION 071800 - Traffic Coatings (Roof Deck)

Polyurethane methacrylate traffic coatings for pedestrian traffic applications

experience installing similar work, and able to communicate verbally with Contractor

system for purposes of testing, leak investigation, and repair,

Warranty Period: Ten years from date of Substantial Completion.

as a qualified approved applicator for warranted installations.

warranty period specified.

installed cost of the work.

PERFORMANCE REQUIREMENTS

products from single source from single manufacturer.

SUBMITTALS: Shop Drawings: Show locations for traffic coating system components. Show details for each

type of substrate, movement joints, corners, and edge conditions, including penetrations, transitions, and

QUALITY ASSURANCE Installer Qualifications: A manufacturer-approved firm with minimum five years'

experience in installation of specified or similar products in successful use on similar projects, employing

workers trained by manufacturer, including a full-time on-site supervisor with a minimum of [three] years'

WARRANTY Applicator: Company specializing in performing the work of this section qualified by system

manufacturer for warranted membrane installation. Applicator shall submit the following certification for

review: Applicator shall submit documentation from the membrane manufacturer to verify contractor's status

Special Manufacturer's Warranty: Manufacturer's standard form in which traffic coating manufacturer agrees to

Access for Repair: Owner shall provide unimpeded access to the Project and the traffic coating

Basis-of-Design Products: Provide traffic coating products manufactured by Tremco, Inc., Commercial Sealants

General: Traffic coating system shall be capable of performing as a continuous watertight installation and as a

coating shall accommodate normal substrate movement and seal expansion and control joints, construction

Compatibility: Provide traffic coating system materials that are compatible with one another and with adjacent

materials under conditions of service and application required, as demonstrated by traffic coating manufacturer

based on testing and field experience. Specifier: Retain "Fire-Test-Response Characteristics" Paragraph below for

traffic coatings that are roof coverings; revise to suit Project. Indicate class for each traffic coating when tested

Specifier Retain "Energy Performance" paragraph below to specify cool-roof performance for

traffic coatings that are installed on exposed decks. Verify availability of compliant products with

Specifier: Vulkem 950NF Topcoat can be used both as an intermediate coat for the Tremco heavy

duty system and a topcoat for interior applications. Vulkem 951NF is a low-odor topcoat designed

according to ASTM E 108. Verify requirements of authorities having jurisdiction and of Owner's insurer.

for exterior applications and for use over Vulkem 950NF in heavy duty applications.

1. Traffic Coating: Manufacturer's polyurethane methyl methacrylate system for extreme exterior exposure

conditions, traffic-bearing, seamless, high-solids-content, cold liquid-applied, elastomeric, waterproofing

Aggregate: Manufacturer's standard aggregate for each use indicated of particle sizes, shape, and

minimum hardness recommended in writing by traffic-coating manufacturer.

cants, flashings and accessories needed for complete watertight installation.

1. Comply with manufacturer's instructions and recommendations. Prepare and clean substrates. Provide

. Surface Condition: Before applying traffic coating materials, examine substrate and conditions to ensure

other deterrents to adhesion, and conditions comply with manufacturer's written recommendations.

3. Verify concrete surfaces are visibly dry, have cured for time period recommended by traffic coating

manufacturer, and are free from release agents, curing agents, laitance, and other contaminates.

Test for capillary moisture by method recommended in writing by traffic-coating manufacturer.

Remove contaminants, curing compounds, and film-forming coatings from substrates.

with ASTM D 4259 and meeting ICRI Surface Profile CSP 3. Do not acid etch.

substrates are fully cured, smooth, and free from high spots, depressions, loose and foreign particles and

1. Surface Preparation: Clean, prepare, and treat substrates in accordance with ASTM C 1127 and traffic

3. Remove projections and excess materials and fill voids with manufacturer's recommended substrate

4. Mechanically abrade concrete surfaces by method of shot blasting to a uniform profile in accordance

6. Protect adjacent finished surfaces by masking. Mask termination point on vertical surfaces. Protect

9. Verify that wet film thickness of each coat complies with requirements every [100 sq. ft. (9 sq. m)]

10. Apply traffic coatings to prepared wall terminations and vertical surfaces to height indicated; omit

11. Cure traffic coatings. Prevent contamination and damage during application and curing stages.

A. Product Data: Submit manufacturer's product data and installation instructions for each material and

C. Warranty: Submit manufacturer's standard warranty. Include labor and materials to repair or replace

A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have

been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store

1. Manufacturers: Carlisle SynTec Incorporated; Firestone Building Products Co.; GAF Materials Corp.; Johns

A. Inspect substrate and report unsatisfactory conditions in writing. Beginning work means acceptance of

B. Comply with roof system manufacturer's instructions and recommendations; clean, prime and prepare

D. Begin roof installation only in presence of manufacturer's representative. Minimize seams and shingle

E. Where applicable, distribute ballast uniformly to 10 pounds per square foot or more as required by FM.

F. Install walkway protection over an additional layer of membrane at locations indicated and where required

D. Roofing shall meet IECC 2018 3-yr aged SRI min 55 and 3-year thermal emittance of 0.75

6. Cover Board over Insulation: Cementitious backer board, mechanically fastened.

C. Install insulation with tightly butted joints and neatly fitted around penetrations.

G. Restore or replace damaged components. Protect work from damage.

B. Shop Drawings: Submit shop drawings indicating material characteristics, details of construction,

7. Primer: Prime surfaces to receive traffic coating system. Allow to cure before proceeding

TRAFFIC COATING FOR PEDESTRIAN TRAFFIC, EXTREME WEAR SYSTEM (EWS)

membrane system with integral wearing surface for pedestrian traffic.

a. Basis of Design Products: Tremco, Inc., Vulkem EWS System

Tremco PUMA BC or Tremco PUMA BC LM

e. Color: As selected by Architect from manufacturer's full range.

Tremco PUMA Primer

d. Top Coat: Methyl Methacrylate

1. Tremco PUMA TC

EXECUTION

c. Base Coats: Modified polyurethane methacrylate

16-30 Mesh silica sand for the Base coat

30-50 Mesh silica sand for the primer

Test surfaces following cleaning and abrasion specified below.

Notify Architect in writing of unsatisfactory con

aggregate on vertical surfaces.

1. Type: Self-adhering, vapor retarding, 40 mils.

. Transition Materials: Silicone sheet.

A. Provide thermoplastic membrane roofing.

defective materials.

QUALITY ASSURANCE

1. Warranty Period: 10 years.

connections, and relationship with adjacent construction.

materials in accordance with manufacturer's instructions.

B. Listing: UL Class A external fire exposure:

A. Thermoplastic Polyolefin Sheet (TPO) Roofing:

Membrane: TPO, 60 mils, fabric reinforced.

Manville International, Inc.; or approved equal.

Insulation: Polyisocyanurate board.

2. Type: Mechanically fastened.

Walkways: Walkway board

. Type: Fully adhered.

8. Insulation Profile: Flat.

INSTALLATION

Listing: FM Class I construction.

Type: Self-adhering, vapor permeable, 40 mils.

SECTION 072700 - AIR BARRIERS

12. Test for leaks after installation and curing.

Provide continuous air barrier membrane at exterior wall assemblies.

Type: Fluid-applied, vapor retarding, 60 mils dry film thickness.

SECTION 075300 - SINGLE-PLY MEMBRANE ROOFING (Addition Roof)

coating manufacturer's written instructions.

6. Test for traffic coating adhesion per manufacturer's recommended method.

8. Proceed with installation once unsatisfactory conditions have been corrected.

Clean prepared surfaces in accordance with ASTM D 4258.

1. PEDESTRIAN TRAFFIC-COATING APPLICATION

8. Apply traffic coating according to manufacturer's written instructions.

13. Control traffic, protect and maintain work without damage until final acceptance.

b. Primer: Two-component, chemically curing methyl methacrylate

material transitions, opening transitions, penetrations, and perimeter conditions without resultant moisture

moisture drainage plane transitioned to adjacent flashings and discharging water to the structure exterior. Traffic

and Waterproofing Division, Source Limitations: Provide traffic coating system materials and accessory

Cost Limitation: Manufacturer's obligation for repair or replacement shall be limited to the original

furnish traffic coating material to repair or replace those materials installed according to manufacturer's written

instructions that exhibit material defects or otherwise fail to perform as specified under normal use within

1. Submit product data. 1. Lumber Standards and Grade Stamps: PS 20, American Softwood Lumber Standard and inspection

2. Construction Panel Standards: PS 1, U.S. Product Standard for Construction and Industrial Plywood; APA 4. Preservative Treatment for Exterior Carpentry in contact with masonry or concrete: AWPA C2 for lumber and AWPA C9 for plywood; waterborne pressure treatment. 5. Fire Retardant Treatment for All Interior Concealed Rough Carpentry: AWPA C20 for lumber and AWPA

C27 for plywood: noncorrosive type. 7. Miscellaneous Lumber, Blocking and Nailers: a. Moisture Content: 19 percent. b. Grade: Standard grade light framing.

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements 2. Comply with APA Design and Construction Guide, Commercial Construction. B. Provide nailers, blocking and grounds where required. Set work plumb, level and accurately cut. 4. Comply with manufacturer's requirements for treated materials.

5. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction. Coordinate 6. Comply with manufacturer's requirements for cutting, handling, fastening and working treated

SECTION 064023 - INTERIOR ARCHITECTURAL WOODWORK

7. Restore damaged components. Protect work from damage.

1. Provide interior architectural woodwork. 3. Refinish existing interior architectural woodwork at lobby paneling, designated doors and trim. 1. Submit product data, samples, of each type.

1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. AWS Standards: Architectural Woodwork Standards of the Architectural Woodwork Institute. 4. Interior Standing and Running Trim and Rails a. Species for Opaque Finish: Any closed grain hardwood.

b. Grade: Premium. Interior Wood Casework: a. Species for Opaque Finish: Closed grain hardwood. b. Grade: Premium. c. Grain and Veneer Matching: As selected by Architect.

7. Casework Hardware and Auxiliary Materials: a. Hardware Standard: ANSI/BHMA A156.9. b. Hardware Finish and Base Metal: Satin chromium plated steel. c. Glass: Clear tempered glass, ASTM C 1048. 9. Stone Countertops and Trim:

 Marble: See allowances 11. Flush Wood Paneling: a. Species for Transparent Finish: Match existing b. Grade: Premium. c. Core: Fire retardant particleboard.

c. Grade: Premium.

b. Grade: Premium.

13. Interior Frames and Framed Openings:

d. Veneer and Panel Matching: As selected by Architect. 12. Stairwork and Rails: a. Species for Transparent Finish: Match existing. b. Species for Opaque Finish: Any closed grain hardwood.

a. Species for Opaque Finish: Any closed grain hardwood. b. Grade: Premium. 14. Shelving: a. Species for Opaque Finish: Hardwood veneer plywood with solid hardwood edgeband.

c. Shelf Supports: Surface mounted slotted standards. d. Closet poles: Chrome plated steel with intermediate supports. 15. Factory Finishing for Interior Architectural Woodwork: a. Opaque Finish: Premium grade, catalyzed lacquer.

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements. 2. Comply with standards referenced.

4. Provide trim for scribing and site cutting. Install work plumb, level and in proper alignment. Provide work free from tool marks and blemishes. Securely fasten to substrates.

8. Install in lengths to minimize joints and seams. 9. Color match wood for transparent finish at joints for uniform appearance. Touch up damaged or abraded finishes.

<u>SECTION 071616 – CRYSTALLINE WATERPROOFING</u>

Provide crystalline waterproofing. Product Data: Submit manufacturer's product data and installation instructions for each material and product

Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions. 1. Waterproofing at Interior of Elevator and Sump Pits, Crystalline: 2. Manufacturers: American Permaguik, Inc.; Hey'Di; Kryton International, Inc.; Super 200; Tamms

Industries, Inc.; Vandex International Ltd.; Xypex Chemical Corporation; or approved equal Portland cement: ASTM C 150, Type I. Water: Potable. 5. Patching Compound: Ready-mixed cementitious waterproofing and repair mortar. 6. Plugging Compound: Cementitious, ready-mixed, hydrophobic surface waterproofing.

7. Protective Topping: Measure, batch, and mix Portland cement and sand in the proportion of 1:3 and water. Blend together with mechanical mixer to required consistency. INSTALLATION 1. Coordinate required substrate surface finishes and preparation before substrate work is performed 2. Comply with waterproofing manufacturer's written instructions to remove efflorescence, chalk, dust, dirt, mortar spatter, grease, oils, curing compounds, and form-release agents to ensure that waterproofing bonds to concrete or masonry surfaces.

3. Clean masonry surfaces according to ASTM D 4261. 4. Clean concrete surfaces according to ASTM D 4258. 5. Maintain ambient 50 degrees F during work and throughout curing period, unless higher temperatures are required by manufacturer. **6.** Comply with manufacturer's instructions and recommendations. Moist cure and protect work.

SECTION 072100 - BUILDING INSULATION A. Provide thermal insulation and vapor retarders.

A. Product Data: Submit manufacturer's product data and installation instructions for each material and **QUALITY ASSURANCE** A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.

A. Batt Insulation: Manufacturers: Roxul, JM or approved equal. B. Application: Thermal insulation in studs in exterior walls. Application: Sound insulation at interior walls Type: Unfaced mineral woo Standard: ASTM C 665, Type I (unfaced). Exterior Board Insulation at Walls and Roof:

G. Manufacturers: Hunter Panels; Temple-Inland Forest Products Corp. - Engineered Wood Products; or approved equal. H. Application: Exterior roofs and exterior walls. I. Type: Polyisocyanurate.

EXECUTION A. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction. Coordinate with work of other sections. Provide full thickness in one layer over entire area, tightly fitting around

B. Install insulation with continuous coverage to provide optimum performance.

Install thermal insulation snug in cavities to limit air flow.

Protect installed insulation.

SECTION 076200 - SHEET METAL FLASHING AND TRIM

to provide access to roof mounted equipment.

1. Provide Flashing and Sheet Metal: b. Exterior wall flashing.

Obtain approval of ballast weight before loading roof.

 c. Exposed metal trim and fascia units. d. Sheet metal accessories. 1. Submit product data, samples, shop drawings.

5. Follow SMACNA Sheet Metal Manual guidelines.

1. Sheet Metal Flashing and Trim: a. Stainless Steel: AISI Type 302/304, ASTM A 666, 2D annealed finish, 28 gage (.0156 inch). b. Sheet Aluminum: ASTM B 209, alloy 3003, clear anodized, 20 gage (.0359 inch). 2. Fabricated Units: Compliance with SMACNA Architectural Sheet Metal Manual. 3. Auxiliary Materials: a. Solder compatible with metal. b. Bituminous isolation coating.

c. Mastic and elastomeric sealants. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements. 2. Install flashing and sheet metal with provision for expansion and contraction. 3. Install flashing and sheet metal to shed water properly. 4. Isolate dissimilar metals with bituminous coating.

SECTION 077100 - ROOF SPECIALTIES

1. Provide manufactured roof specialties.

SUBMITTALS 1. Product Data: Submit manufacturer's product data and installation instructions for each material and

2. Shop Drawings: Submit shop drawings indicating material characteristics, details of construction, connections, and relationship with adjacent construction.

3. Samples: Submit two representative samples of each material specified indicating visual characteristics and finish. Include range samples if variation of finish is anticipated.

QUALITY ASSURANCE 1. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions. 2. Insurance Requirements: FM approval or acceptance.

MATERIALS

1. Gravity Air Vents: Manufacturers: Berger Building Products, Inc.; or approved equal. Material: Aluminum

9. Materials: 0.60 inch thick, extruded aluminum.

14. Aluminum Finish: Fluoropolymer, 3-coat.

Gutter and Downspout Systems: 5. Manufacturers: Berger Building Products, Inc.; Englert, Inc.; Park City Rain Gutter; The Copper Gutter

6. Material: Aluminum, painted. Fascia Systems, Extruded Aluminum: 8. Manufacturers: ATAS International, Inc.; Metal-Era, Inc.; MM Systems Corporation, or approved equal.

10. Aluminum Finish: Fluoropolymer, 3-coat. 11. Aluminum Coping, Aluminum Sheet: 12. Manufacturers: ATAS International, Inc.; Metal-Era, Inc.; MM Systems Corporation, or approved equal. 13. Interlocking multi-part coping system, 0.063-inch thick aluminum sheet, 24 gauge (.0239 inch) zinccoated steel anchor plate, and formed aluminum gutter.

EXECUTION INSTALLATION 1. Comply with accessory manufacturers' instructions and recommendations. Coordinate installation with roofing system to ensure weathertight performance. Anchor securely to structure to withstand

SECTION 078410 - PENETRATION FIRESTOPPING

Summary: (See code plans) 1. Provide Firestopping at the Following Locations: a. Penetrations through fire resistance rated floor and roof construction. b. Penetrations through fire resistance rated walls and partitions.

. Test and operate units: clean, lubricate and adjust moving parts.

Isolate dissimilar metals to prevent galvanic corrosion.

d. Sealant joints in fire resistance rated construction. . Submit product data, test reports, schedule of products and rating. **Products:** 3M, WR Grace, Hilti, Tremco or approved equal 1. Fire Performance: ASTM E 119, ASTM E 814, and local regulations.

2. Through Penetration Firestop Systems: Ceramic Fiber and Mastic Coating. b. Endothermic, Latex Compounds. c. Intumescent Latex Sealant. 3. Fire Resistive Elastomeric Joint Sealants:

a. Single component, neutral curing, silicone sealant.

b. Single component, nonsag, urethane sealant. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

Provide material thicknesses necessary to provide fire resistance ratings indicated or required by

a. Type: Multi part nonacid curing silicone sealant, ASTM C 920, for vertical and horizontal joints,

. Inspect existing and new work for proper firestopping prior to close in of ceilings and walls.

c. Penetrations through smoke barriers and construction enclosing compartmentalized areas.

nodulus as required for applicatio

SECTION 079200 - JOINT SEALANTS

authorities having jurisdiction.

1. Provide joint sealers at interior and exterior vertical and horizontal joints. . Submit product data, colors, mockup of each joint type. 1. Silicone Elastomeric Joint Sealants:

b. Application: Joints in exterior walls and soffits. 2. Latex Joint Sealants: a. Acrylic Type: Acrylic emulsion, ASTM C 834. b. Application: Interior joints in vertical and overhead surfaces with limited movement. 3. Sanitary Silicone Elastomeric Joint Sealants:

a. Type: One part mildew resistant silicone sealant, ASTM C 920. b. Application: Sanitary applications, interior use. 4. Compression Seals: a. Type: Preformed foam sealant. b. Application: Wide exterior joints in vertical surfaces.

Type: One part fire stopping sealant.

Fire Resistive Joint Sealers:

8. Auxiliary Materials

 a. Plastic foam joint fillers b. Elastomeric tubing backer rods. c. Bond breaker tape. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

b. Application: Penetrations in fire rated floor and wall assemblies.

4. Clean adjacent surfaces soiled with sealant immediately.

. Install in proper relation with adjacent work.

Test sealant adhesion for each substrate required.

SECTION 081110 - HOLLOW METAL DOORS AND FRAMES Provide Steel Doors and Frames a. Interior doors and frames. b. Exterior doors and frames.

1. Submit product data, shop drawings. 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. Standards: ANSI/SDI 100, Recommended Specifications for Standard Steel Doors and Frames.

Fire Rated Assemblies: NFPA 80, and acceptable testing agency listing 4. Provide thermally improved doors with maximum U-value of 0.24 BTU/hr./square foot degree F (ASTM C 236) for all exterior doors. 5. Steel Doors: Standard seamless steel doors with hollow or composite construction. a. Interior Doors: ANSI/SDI 100, Grade II, heavy duty, minimum 18 gage cold rolled steel, 1 3/4 inches

b. Exterior Doors: ANSI/SDI 100, Grade III, extra heavy duty, minimum 16 gage galvanized sheet steel, 1 3/4 inches thick. c. Finish: Factory primed and field painted. a. Interior Frames: Knockdown type typical, sheet steel, mitered or coped corners, 16 gage, 14 gage for

frames wider than 5 feet. b. Exterior Frames: Welded type, galvanized sheet steel, mitered or coped corners, 14 gage. c. Accessories: Door silencers and plaster guards. d. Finish: Factory primed and field painted.

1. Fabricate work to be rigid, neat and free from seams, defects, dents, warp, buckle, and exposed fasteners.

2. Install doors and frames in compliance with SDI-100, NFPA 80, and requirements of authorities having

<u>SECTION 081400 - WOOD DOORS</u>

Fitting and Finish:

1. Provide interior solid core 2-panel wood doors. Submit product data, samples, shop drawings, warranty. 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements.

. AWI Quality Standards: NWWDA I.S. 1 A, and AWI Architectural Quality Standards.

Fire Rated Wood Doors: Meeting ASTM E 152 requirements. 4. Interior Solid Core Doors: a. Grade: Jeldwen or Similiar. b. Construction: Molded wood composite c. Core: Solid Core

d. Species and Grain Matching: As selected by Architect.

a. Fitting: Factory prefit and premachine doors.

required. Verify undercuts with mechanical.

b. Fitting: Remodel existing doors as required. c. Shop-Applied Opaque Finish: AWI Premium Grade, catalyzed lacquer. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications 2. Comply with NWMA IS 1 and AWI Quality Standards.

4. Install with not more than 1/8 inch clearance at top and sides, 1/4 inch at bottom unless undercut is

SECTION 083110 - ACCESS DOORS AND FRAMES

3. Prefit doors to frames, premachine doors for hardware, and factory bevel.

1. Provide access doors for walls and ceilings. Verify required locations with Arch, Mechanical, Plumbing, and Electrical drawings. 1. Submit product data. Products: 1. Basis-of-Design Products: J.L. Industries, Milcor or approved equal

. Frames: 16 gage sheet steel, with flange suitable for adjacent material. B. Doors: 14 gage sheet steel. 4. Door Type: Trimless Locking Devices: Cylinder locks. Fire Rating: NFPA 80 where installed in a rated wall or ceiling partition.

. Finish for Sheet Steel Access Doors: Factory primed. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements.

TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC

SEAL 10-21-2020



19-001

OCTOBER 8, 2020

DATE

2020-03-29

4-22-2020

10-8-2020

DRAWN BY: SJW

SPECIFICATIONS

SHEET TITLE:

This drawing as an instrument of service is the property of the Architect and may be used only on

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution

and completion of the work by the Contractor. The Contract Documents are complementary, and

is what is required by one shall be as binding as if required by all; performance by the Contractor

shall be required only to the extent consistent with the Contract Documents and reasonably

inferable from them as being necessary to produce the indicated results.

BID SET

ADD#1

PERMIT SET

REV. # REVISION DESCRIPTION

any part without written permission of the Architect.

WA PROJECT NO:

PROJECT ISSUE DATE:

ne project named herein. This drawing shall not be reproduced, copied, or used in whole or in

1. Basis-of-Design Products: Pella Architect Series – Traditional Single-hung window 1. Select softwood, immersion treated with Pella's EnduraGuard® wood protection formula in accordance with WDMA I.S.-4. Interior exposed surfaces are clear pine Exterior surfaces are clad with aluminum. Components are assembled with screws, staples and concealed corner locks. Overall frame depth is 5" (127 mm) for a wall depth of 3-11/16" (94 mm). 6. Factory applied jamb extensions available between 4-9/16" (116 mm) and 7-3/16" (183 mm) wall depths. Confirm in field factory-applied EnduraClad® exterior trim. 1. Select softwood, immersion treated with Pella's EnduraGuard® wood protection formula in accordance with WDMA I.S.-4 Interior exposed surfaces are clear pine Exterior surfaces are clad with aluminum and sealed. Corners mortised and tenoned, glued and secured with metal fasteners. Sash thickness is 1-7/8" (47 mm). Sash exterior and interior profile is ogee. Single-Hung: Fixed upper sash has surface-mounted wash locks 8. Lower sash has concealed wash locks in lower check rail. Sashes tilt for easy cleaning. 4. Weatherstripping Water-stop santoprene-wrapped foam at head and sill. Thermoplastic elastomer bulb with slip-coating set into lower sash for tight contact at check rail. Vinyl-wrapped foam inserted into jamb liner to seal against sides of sash. Glazing Quality float glass complying with ASTM C 1036. Silicone-glazed 11/16" dual-seal insulating glass tempered, Advanced Low-E Aluminum-clad exteriors shall be finished with EnduraClad® protective finish, in a multi-step, baked-Color is standard Interior 1. factory primed with one coat acrylic latex B. Hardware Galvanized block-and-tackle balances are connected to self-locking balance shoes which are connected to the sashes using zinc die cast terminals and concealed within the frame. Sash lock is cam-action. Two sash locks on units with frame width 37" and greater. Optional sash lift furnished for field installation. Two lifts on units with frame width 37" and greater. Hardware finish is baked enamel [Champagne] [White] [Brown] [Matte Black]] [Bright Brass] [Satin Nickel] [Oil-rubbed Bronze] [Antique Brass] [Distressed Bronze] [Distressed Nickel]. 9. Options 2. Half-Size black vinyl-coated 18/18 mesh fiberglass screen cloth complying with the performance requirements of SMA 1201, set in aluminum frame fitted to outside of window, supplied complete with all necessary hardware. Full screen spreader bar placed on units > 37" width or > 65" height. Insect screen frame finish is baked enamel, color to match window cladding. Hardware Options 1. Factory applied limited opening device available for vent units in stainless steel; nominal 3-3/4" opening. Limiting device concealed from view SECTION 087100 - DOOR HARDWARE

SECTION 088000 - GLAZING SECTION 092120 - GYPSUM BOARD SHAFT WALL ASSEMBLIES Summary: 1. Provide gypsum board shaft wall assemblies. 1. Provide glass and glazing. SUBMITTALS . Product Data: Submit manufacturer's product data and installation instructions for each material and 1. Submit product data. 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. Shop Drawings: Submit shop drawings indicating material characteristics, details of construction, connections, and relationship with adjacent construction. 2. Cavity Shaft Wall Assemblies: Warranty: Submit manufacturer's standard warranty. Include labor and materials to repair or replace a. Shaftwall Board Thickness: Not less than 1 inch. b. Studs: I, C H or double E studs, not less than, 20 gage (.0329 inch). defective materials. 3. Gypsum Board Shaft Wall Materials: Laminated Glass: Manufacturer's 5-year warranty. a. Steel Framing: ASTM C 645. b. Coated Glass: Manufacturer's 10-year warranty. b. Gypsum Shaftwall Board: ASTM C 442, Type X. c. Insulating Glass: Manufacturer's 10-year warranty. Gypsum Wallboard: ASTM C 36, Type X. Mirror Glass: Manufacturer's 5-year warranty. d. Water Resistant Gypsum Backing Board: ASTM C 630, Type X. QUALITY ASSURANCE . Comply with governing codes and regulations. Provide products of acceptable manufacturers which have . Gypsum Wallboard Joint Treatment Materials: ASTM C 475 and ASTM C 840. been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and 4. Auxiliary Materials: store materials in accordance with manufacturer's instructions. a. Cornerbeads, edge trim, and control joints. Glazing for Fire-Rated Assemblies: Glazing for assemblies that comply with NFPA 80. b. Laminating adhesive. c. Gypsum board screws, ASTM C 1002. Safety Glazing Products: Comply with testing requirements in 16 CFR 1201 and, for wired glass, ANSI d. Concealed acoustical sealant. e. Mineral fiber sound attenuation blankets. 4. Glazing Publications: GANA Publications: GANA's "Glazing Manual." and "Laminated Glass Design Guide." b. IGMA Publication for Insulating Glass: SIGMA TM-3000, "Glazing Guidelines for Sealed Insulating 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements. 5. System shall meet 2018 IECC Prescriptive Approach SECTION 093000 - TILING 1. Glass and Glazing: 1. Provide tile for the following applications: a. Manufacturers: AFG Industries; Cardinal IG; Pilkington; Viracon; or approved equal. Type (Glass replacement at existing windows): Lamiinated glass units, tempered at locations as a. Wall tile over gypsum wallboard. b. Wall tile over tile backer board at wet areas. required by Code. Glass shall be clear, colorless non-reflective with a min. LVT of 70%. Type (Glass at new windows and storefront): High-performance insulating glass units with low- c. Floor tile over concrete slab. e coating, tempered at locations as required by code. Glass shall be clear, colorless non-3. Provide floor preparation including leveling and patching. reflective with a min. LVT of 70%. 1. Submit product data, samples, 2 foot by 2 foot mockup of each type and grout color. Type: Mirror glass units. b. Auxiliary Materials: Compression gaskets, Elastomeric glazing sealants, Preformed glazing tapes, 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. Glazing gaskets, Setting blocks, spacers, and compressible filler rods, Mirror adhesive, top and . Tile Materials: ANSI A 118 series standard specifications. bottom angles and clips 3. Tile Accessories: 2. Fire-Rated Glazing: UL rated for required fire resistance Manufacturers: Pilkington; Saint-Gobain; or approved equal. a. Matching trim units. b. Marble thresholds. b. Type: Fire-rated glazing as vision lights in fire-rated door assemblies. 4. Setting Materials: Latex Portland cement mortar, ANSI A118.4. Material: Transparent ceramic. . Grout: Portland cement grout with integral color, ANSI A118.7. d. Fire Rating: As required for application. 6. Setting Accessories: a. Membrane waterproofing under tile. ANSI A 118.10. b. Crack suppression membrane. ANSI A 118.10 Elastomeric Sealants: a. One part mildew resistant silicone sealant for non traffic areas. b. Multi part pourable urethane sealant for traffic areas. c. Chemical resistant sealant at chemical resistant flooring. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements 2. Comply with ANSI 108 series standard specifications and Tile Council of North America, Handbook for Ceramic Tile Installation. Provide sealant joints where recommended by TCA and approved by Architect. Layout tile in grid pattern with alignment of grids, to provide uniform joint width, and to minimize cutting. 4. Grout, cure, clean and protect tile surfaces. . Submit product data, samples, shop drawings, warranty, maintenance data. 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. SECTION 095100 - ACOUSTICAL CEILINGS Aluminum Extrusions: ASTM B 221, alloy 6063-T5 or T6. Blades: Horizontal drainable blades. 1. Provide acoustical lay in ceilings, trim, and metal suspension system at commercial space restrooms. Blade Type: Fixed. . Anchors, Clips, and Accessories: Aluminum, nonmagnetic stainless steel, or galvanized steel. 1. Submit product data, samples. 11. Aluminum Finish: 2-coat fluoropolymer to match wall colors, or selected by manufacturers full color range. . Attic stock, 2 percent of each type of ceiling tile and grid; store where directed by Owner. a. Screens: Bird. 1. Basis-of-Design Products: Armstrong World Industries; USG; or approved equal. b. Screens: Insect. 2. Acoustical Panel Ceilings: c. Panels: Blank-off. a. Type: Mineral Fiber 24"x24" with square edge, and exposed flush grid d. Panels: Insulated blank-off. 3. Suspension Systems: a. Concealed grid suspension system, ASTM C 635 intermediate duty classification. Material: Extruded aluminum. b. Fire Rating: Non fire resistance rated suspension system. Material: Cast aluminum. c. Suspension System Accessories: Attachment devices and hangers, ASTM C 635. Blades: Fixed. d. Cap Material: Painted steel. d. Blades: Adjustable. e. Edge molding and trim. . Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications . Measure and layout acoustical ceilings to avoid less than 1/2 panel units whenever practical. . Install suspension systems in accordance with ASTM C 636. Provide Gypsum Board Assemblies 4. Install panels with pattern or grain running one way. Interior walls, partitions, and ceilings for tape and joint compound finish. b. Insulation and vapor barrier systems in gypsum drywall systems. Cementitious backer units for application of tile. Glass reinforced gypsum fabrications. SECTION 096620 - TERRAZZO FLOORING e. Remodeling gypsum drywall systems at areas of new construction. Submittals: 1. Refinish existing terrazzo flooring, thresholds, and wall base. 1. Submit product data 2. Patch existing terrazzo crack in entry lobby. . Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. 1. Submit product data, samples Gypsum Wallboard: ASTM C 1329, regular, and fire rated types, 5/8 inch typical thickness. Glass Mat Water Resistant Gypsum Backing Board: ASTM C 1178, Type X, 5/8 inch thick. 1. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements. . Cementitious Backer Units: ANSI A 118.9, cement coated Portland cement panels, 5/8 inch nominal. Cementitious Terrazzo: . Impact Resistant Board: ASTM C 1629, Level 2 resistance. a. Type: Monolithic. 6. Trim Accessories: b. Type: Bonded. a. Material: Metal. c. Portland Cement: ASTM C 150, Type I. b. Types: Cornerbead, edge trim, and control joints. d. Sand: ASTM C 33. Decorative Profiles: Aluminum reveals and channels. Aggregate: Sound crushed marble chips Steel Framing for Walls and Partitions: (Non-structural) Matrix Pigments: Mineral or synthetic type. a. Steel Studs and Runners: ASTM C 645, 25 gage unless heavier gage required by span. Double 22 g. Underbed Reinforcement: Welded wire fabric, 2 by 2 inch, 16 gage (.0598 inch). gage at door jambs. Depth as shown on plans. Isolation Membrane: Polyethylene film, 4 mils, b. Furring Channels: ASTM C 645, 25 gage unless heavier gage required by span. 5. Auxiliary Materials: c. Auxiliary Framing Components: Furring brackets, resilient furring channels, Z furring members, and a. Divider strips, Control joint strips, Terrazzo sealer, Abrasive inserts. non-corrosive fasteners. d. Installation Standard: ASTM C 754. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications . Steel Framing for Suspended and Furred Ceilings: ASTM C 645, standard channels. and requirements. a. Steel Studs: Match steel studs used for walls. Accessories: Hangers and inserts. Installation Standard: ASTM C 754 9. Glass Reinforced Gypsum Fabrications: **SECTION 099000 - PAINTING AND COATING** a. Gypsum: ASTM C 22. Provide painting and surface preparation for interior and exterior unfinished surfaces as scheduled. b. Glass Fibers: ASTM D 578, Type E glass. c. Finish: Surface suitable for high gloss paint. 2. Provide painting and surface preparation of exposed mechanical and electrical piping, conduit, ductwork, Gypsum board screws, ASTM C 1002 B. Provide repainting and surface preparation at areas of remodeling. b. Fastening adhesive. 4. Provide painting of entire surface where patch painting is required. c. Concealed acoustical sealant Fiberglass or mineral fiber sound attenuation blankets. 1. Submit product data, samples, 4 foot by 4 foot mockup of each color. e. Polyethylene vapor retarder, 6 mils, at exterior walls without air/vapor retarder. 2. Attic stock, two unopened gallons of each type and color; store where directed by Owner. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications 1. Basis-of-Design Products: Benjamin Moore; PPG, Inc; Sherwin-Williams; or approved equal. Regulations: Compliance with VOC and environmental regulations. Steel Framing: Install steel framing in compliance with ASTM C 754. Install with tolerances necessary to . Commercial quality products for all coating systems. produce substrate for gypsum board assemblies with tolerances specified. Include blocking for items such as railings, grab bars, casework, toilet accessories, window treatment and similar items. a. Gypsum board and plaster walls, eggshell finish, 1 coat latex primer and 2 coats latex finish. Fire Resistance for Fire-Rated Assemblies: ASTM E 119. b. Gypsum board and plaster ceilings, flat finish, 1 coat latex primer and 2 coats latex finish. . Comply with standards referenced above and ASTM C 840 and GA 216. . Gypsum board in bathrooms, kitchens and wet areas, semigloss finish, 1 coat latex primer, 2 coats 5. Install joints only over framing members. Do not allow butt to butt joints. alkyd finish. d. Ferrous metals, semigloss finish, 1 coat primer, 2 coats alkyd enamel. audiovisual equipment and similar items. Galvanized metal. semigloss finish, 1 coat galvanized metal primer, 2 coats alkyd enamel. Provide acoustical sealant at runner tracks, wall perimeters, openings, expansion, and control joints. Wood for transparent finish, 2 coats polyurethane. . Install gypsum board assemblies true, plumb, level and in proper relation to adjacent surfaces. g. Wood for opaque finish, 1 coat alkyd semi-gloss finish. 9. Where new partitions meet existing construction, remove existing cornerbeads to provide smooth 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements A. GA Level 1: Ceiling plenum areas and concealed areas not exposed to view. Provide field applied mock ups of each color and finish selected on actual surfaces to be painted. B. GA Level 2: Panels that are substrate for tile. Test sample area for adhesion for each type of paint. Remove cover plates and protect hardware and adjacent surfaces. GA Level 4: Panel surfaces that will be exposed to view (typical panels). 5. Sand before painting until smooth and flat and sand between coats. 11. Caulk at door frames, cabinets, penetrations, and leave ready for finish painting and wall treatment. Apply paint to achieve manufacturer's recommended dry film thicknesses. Paint entire surface where patch painting is required. Recoat areas which show bleed through or defects. 9. Clean paint spatter from adjacent surfaces and glass. 10. Touch up damaged surfaces at completion of construction. 1. Provide plaster assemblies. 1. Product Data: Submit manufacturer's product data and installation instructions for each material and SECTION 101400 - SIGNAGE Comply with governing codes and regulations. Provide products of acceptable manufacturers which 1. Provide building signage to comply with code and accessibility regulations. have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, 2. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and handle, and store materials in accordance with manufacturer's instructions. store materials in accordance with manufacturer's instructions. . Portland Cement Plaster: Manufacturers: Multicoat Corp.; Stuc-O-Flex International, Inc.; or approved equal. Submit product data, samples. Type: 3 coats over substrate. Cement: Portland cement, ASTM C 150, Type I or II. 1. Basis-of-Design Products: ASI Sign Systems; Best Sign Systems.; InPro Corporation or approved equal. Finish Coat: Factory-prepared finish coat. . Panel Signs: Unframed. . Materials: Plastic Auxiliary Materials: Corner beads, casing bead, and control joints, Bonding compounds and agents. 4. Copy: Raised text, Braille and English Lath and Plaster Support Systems: Manufacturers:, Dietrich Industries, National Gypsum Co., Unimast or approved equal. 1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications Metal Supports for Suspended and Furred Ceilings: For Portland cement plaster. and requirements. Standard: ASTM C 1063. Steel Studs and Runners, Non-Load (Axial) Bearing: ASTM C 645. Typical Thickness: 20 gauge (.0329 inch). **SECTION 102800 - TOILET ACCESSORIES** Typical Depth: 3-5/8 inches. Vertical Metal Furring: Channel furring and braces, Z-furring members, and furring brackets. Provide toilet and bath accessories and metal framed mirrors. Expanded Metal Lath: ASTM C 847, self-furring galvanized steel diamond mesh or rib lath. Submittals: Auxiliary Materials: Corner beads, casing bead, and control joints, Bonding compounds and agents, 1. Submit product data, samples. Acoustical sealant, Sound attenuation blankets, mineral-fiber type, Thermal insulation, mineral-fiber 1. Basis-of-Design Products: American Specialties, Inc.; Bobrick Washroom Equipment; Bradley Corp or approved equal.. Comply with ASTM C 754, ASTM C 842, ASTM C 84, ASTM C 844, ASTM C 926 and manufacturer's Toilet Accessories: instructions and recommendations. Maintain environmental conditions within the limits prescribed by Toilet tissue dispensers. b. Grab bars. At plaster patching, prepare surface to sound substrate, apply bonding agent and patching materials in c. Mop and broom holders. accordance with manufacturer's instructions. Mirrors and Frames: Install metal trims at perimeters and joints. At scratch coat form full keys, Ensure tight contact between a. Glazing: Mirror glass, 1/4 inch thick, ASTM C 1036. coats. Tool edges at windows, doors, other openings to small vee to control spalling. b. Frames: Stainless steel. 4. Clean adjacent surfaces soiled during installation. Touch up damaged surfaces. Protect work from damage. c. Type: Standard wall unit. 4. Materials and Finishes: a. Material and Finish: Stainless steel, No. 4 finish. b. Baked Enamel on Steel: Factory applied finish from manufacturers full line of colors.

 Rating: Sized for project requirements. L. Cabinets: See drawings a. Mounting: Recessed h Trim Flush c. Doors: Painted steel and requirements. SECTION 104400 - FIRE PROTECTION SPECIALTIES 1. Provide fire extinguishers and cabinets: a. Fire extinguishers b. Fire extinguisher cabinets at public areas c. Fire extinguisher mounting brackets at service areas. . Submit product data. Standards: UL and FM listed products. NFPA10 and ADAAG Fire Extinguishers b. Type: Multipurpose dry chemical. c. Rating: Sized for project requirements. 4. Cabinets: See drawings a. Mounting: Recessed. b. Trim: Flush. c. Doors: Painted steel. and requirements. SECTION 113100 – APPLIANCES (provided by Owner, installed by Contractor) Provide kitchen area appliances. a. Ranges, electric. . Ranges, gas. d. Range hoods, recirculating type Refrigerators/Freezers k. Microwave ovens. Dishwashers. m. Garbage Disposals . Submit product data, shop drawings, warranty, maintenance data. and requirements. <u> Section 122000 – Window Treatmen</u> 1. Provide window treatments. and finish. Include range samples if variation of finish is anticipated. store materials in accordance with manufacturer's instructions. . Roller Shades: Shadecloth: Transparent at residential living rooms and kitchens Shadecloth: Blackout at residential bedrooms and bathrooms Operation: cordless lift Mount: Inside mount with Headrail Roll Position: Standard 8. Fabric: To be selected from standard available finishes EXECUTION SECTION 142000 - HYDRAULIC PASSENGER ELEVATORS A. Hydraulic passenger elevators. DESIGN REQUIREMENTS dismantling or removing other equipment components. complete a fully operational system. MANUFACTURER Schindler Elevator Corporation, Alliance Elevator or approved equal. **ELEVATOR SYSTEM AND COMPONENTS** Hydraulic Passenger Elevators: Schindler Model 330A or Alliance Advantage-Twin Jack . Elevator Equipment Summary: a. Application: Holeless Dual Piston Service: General Purpose Passenger- Class A Loading Quantity: 1 Unit Capacity: 2100 Lbs Speed: 125 Fpm Travel: 51' 6" Landings: 5 Front Openings: 5 Operation: Microprocessor Single Car Automatic Operation Machine Room: Adjacent To Elevator Hoistway Platform Size: 6'-0" Wide X 5'-1" Deep Door Type: Single Speed Side Opening m. Cab Height: 8' 0" n. Guide Rails: Equivalent to 16 lb. per foot Hoistway Entrances: 3' 0" Wide X 7' 0" High doors Power Supply: 208 Volts 3 Phase 60 Hz Elevator Components: **Access Control**: Access control limiting access to basement, 2nd and 3rd floors. Anti-stall feature. Braille and audible signals. Door open and close stall protection Emergency lighting. Independent service feature Infrared light curtain door protection Low oil return. Overload sensors Phase protection Soft Start Electronic Starting Locking Service Panel in Car Operating Panel. m. Pressure Switch. n. Telephone (ADA compliant). **ELEVATOR MATERIALS** a. Stainless Steel and Bronze: #4 satin or #8 mirror finish. Baked Enamel Colors: Manufacturer/installer's standard color selections. Exposed Aluminum Frames in Suspended Ceilings: Anodized. Plastic Laminates: a. Type: General purpose. b. Flame Spread Ratings: As required by code. Pattern: Select from elevator manufacturer/installer's standard selection. Muffler: Reduce noise transmission Telescopic Holeless Jack System: and provides smooth ride. ELEVATOR CABS Height: 8' 0" from finished floor to underside of canopy. a. Elevator Car Enclosure Wall Sections: Cab Wall: Steel - #4 Stainless Steel Finish Base, Frieze, and Reveals: #4 Stainless Steel. a. Suspended with Concealed Frame Finished In #4 Stainless Steel. 4. Cab Returns: Integral construction. a. Finish: #4 Stainless Steel. Transoms: a. Run full width of cab. b. Finish: #4 Stainless Steel. 6. Cab Doors: a. Flush design both sides. b. Rib construction. c. Finish: #4 Stainless Steel. Exhaust Fan: Single speed. b. Mount in cab transom or canopy. 8. Handrail: a. 1/2" X 2" Flat In #4 Stainless Steel. b. Mount on Rear Wall. **9.** Threshold: Aluminum.

HOISTWAY ENTRANCES . Hoistway Doors and Frames: a. UL rated with required fire rating. b. Doors: Rigid flush panel construction with sound-deadening material. c. Frames: Securely fasten at corners to form unit frame. Frames shall be Bolted. 2. Exposed Areas of Corridor Frames: Painted Primer - All Floors a. Doors: Painted Primer - All Floors b. Sills: Aluminum CAB FIXTURES Main Car Operating Panel a. Mount in return. b. Comply with handicap requirements. c. Include pushbuttons and illuminating indications for each floor served. d. Emergency Buttons and Switches: Provide in accordance with code. e. Switches for car light and accessories. Cab Fixtures: a. Car Lantern(s). b. Digital Car Position Indicator. c. Locking Service Panel in Car Operating Panel. d. Telephone (ADA compliant). HALL FIXTURES Pushbuttons: a. Up button and down button at intermediate floors. b. Single button at each terminal floor. c. Height: Comply with handicap requirements. Hall Fixture Finish: Black Lexan. Fixture Cover Plates: Mount with tamper-resistant screws in same finish as fixture. 1. Examine hoistways, hoistway openings, pits, and machine rooms before starting elevator installation. a. Verify hoistway, pit, machine room, and openings are of correct size, within tolerances, and are ready for work of this section. b. Verify walls and sill supports are plumb, where openings occur. c. Verify hoistway is clear and plumb, with maximum variation of 1/2" at any point. Verify minimum 2-hour fire-resistance rating of hatch walls. e. Notify Architect in writing of dimensional discrepancies or other conditions detrimental to proper installation or performance of elevators. f. Do not proceed with elevator installation until unsatisfactory conditions have been corrected in a manner acceptable to manufacturer/installer.

REFER TO STRUCTURAL, PLUMBING, MECHANICAI ELECTRICAL FOR ADDITIONAL SPECIFICATION

Notes terior Work Exterior Building Mounted Signage Exterior Bike Racks Exterior Keypad Access Exterior Camera System Exterior Storefront and Overhead Doors Exterior Windows Interior Door Access Control Hardware at Apartment Doors Kitchen Cabinets Kitchen Cabinet Hardware (Pulls) Kitchen and Bathroom Counters Allowance of \$2500 per unit Kitchen Tile at Backsplash Bathroom Cabinets Bathroom Cabinet Hardware (Pulls) Bathroom Tile Floor Bathroom Wall Tile Interior Residential Doors (see schedule) with Casing (no trim) nterior Residential Door Hardware (handleset) Interior Commercial Doors (see sched.) including hardware nterior Wood Trim Apartment Closet Shelf and Rod Residential Bathroom Accessories (Toilet Paper Dispenser, Towel Rods) Residential Shower Rods nterior ADA Signage at all stairs, exits, and Apartment entry doors. Apartment Appliances (Washer, Dryer, Refrigerator, Dishwasher, Range, Microwave/Hood) amsung or Similar Commerical and Apartment Furniture Apartment Window Shades All residential windows. 4th Floor Kitchen Equipment 4th Floor Bar Millwork and Equipment Apartment Plumbing Fixtures Bathroom (Tub, Toilet, Sink...) Apartmnet Plumbing Hardware Bathroom (Sink, Tub, Shower) Apartment Plumbing Fixtures Kicthen (Sink, Garbage Disposal) Apartment Plumbing Hardware Kitchen (Sink) Commercial Bathroom, Fixtures and Hardware (1st and 4th floor) Residential Interior Light Fixtures Residential Interior Decorative Light Fixtures (Pendants) Residential Interior Fans Commercial Interior Lights (Corridor, Stairs, Commercial Spaces) Commercial Decorative Lights (Corridor Pendant) Building Exterior Light Fixtures

Utility service will be by CPS Energy. Connection fee excluded from

I required onsite coordination meetings with CPS Energy.

uctured Cabling (wiring and equipment)

Contractor's price and paid by Owner. Contractor shall, •Initiate all required

stems that comply with CPS Energy Service Standards. •Schedule and oversee

tility service applications with CPS Energy. •Provide and install materials and

RESPONSIBILITY MATRIX

ITEMS LISTED BELOW ARE FOR CLARIFY. NOT ALL CONTRACTOR RESPONSIBLE ITEMS ARE LISTED BELOW. CONTRACTOR ITEMS LISTED BELOW ARE TO PROVIDE ADDITIONAL CLARITY FOR SOME OF THE ITEMS.

NOTE: All Items to be furnished and installed by the Contractor, except for as listed below:

TRAVIS ST. APARTMENTS

HISTORIC RENOVATION AND

505 E. TRAVIS STREET SAN ANTONIO, TEXAS 78205

505 TRAVIS BAUDHAUS LLC



VELTY ARCHITECTURE, LI Scott Welty - Architect 3021 42nd St Metairie, LA 70001 p. 504-931-1665 www.weltyarchitecture.com

NOTE: The intent of the Contract Documents is to include all items necessary for proper execution and completion of the work by the Contractor. The Contract Documents are complementary, and

WA PROJECT NO: 19-001 PROJECT ISSUE DATE: OCTOBER 8, 2020

BID SET ADD#1 PERMIT SET

DRAWN BY: SJW

DATE

2020-03-29

4-22-2020

10-8-2020

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications and requirements. 2. Comply with DHI "Recommended Locations for Builder's Hardware" and hardware manufacturers 3. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance.

Coordinate with work of other sections.

Provide hardware for swinging doors

d. Quality Level: Commercial.

Lock Cylinders: Integral type.

Keying: As required by Owner.

8. Closers: High frequency type.

9. Exit Devices: High frequency type.

Hardware Finishes: To be selected

11. Door Trim Units: Kickplates, pulls

13. Silencers: At all frames.

b. Soundstripping.

Thresholds

Special Function Hardware

Weatherstripping

reader/controller

14. Accessory Hardware:

Locksets and Latchsets: Cylinder type.

2. Product Requirements:

Comply with code and accessibility requirements.

1. Submit product data, samples, proposed hardware schedule, maintenance data.

Handicapped Accessibility: ANSI A117.1. ADAAG, and local requirements.

Dorma Architectural Hardware; Yale Locks and Hardware; or approved equal.

Materials and Application: ANSI A156 series standards.

a. Flush bolts with dustproof strikes, automatic door bottoms.

Manufacturers: **Salto KS** https://saltoks.com/

a. Hardware for Fire Rated Openings: NFPA 80, and local requirements.

Hardware schedule: Consult with hardware supplier to produce hardware schedule for submittal

1. Basis-of-Design Products: ASSA ABLOY Door Security Solutions; Corbin Russwin Architectural Hardware;

Hinges and Butts: Full mortise type with nonremovable pins at security doors; continuous hinges at

12. Stops: For each door; overhead door stops surface mounted and concealed types as applicable.

Electric Standalone Card Access Locking System: Apartment Entry Doors, Exterior Access Doors

3. Components: Electric locks, software package, portable programmer, off-line and on-line card

Shop Drawings: Include outside net frame dimensioning, direction of swing (outswing), number of panels,

folding configuration of panels left or right, identify main entry swing panel, typical head, side jamb, sill and

Manufacturer Qualifications: Provide complete, engineered and high quality folding door system by a single

Installer Qualifications: Installer with documented experienced in the installation of manufacturer's folding door

1. Aluminum Thermally Controlled Folding Doors: Aluminum Thermally Controlled Outswing Bi-Fold Doors.

thermally controlled panels to sizes indicated on the Drawings. Provided with thermal struts that create a

5. Weatherstripping: Weather seal inserted in frame and sill to provide perimeter seal, as well as between door

Verify that the maximum deflection of the header with the live load does not exceed the lesser of L/720 of

the span and 1/4 inch. Structural support for lateral loads including both wind load and when the panels

Verify that dimensions of rough opening will fit the net frame dimensions of door system; verify that rough

Provide adequate anchorage devices. Securely fit frame in place, level, straight, plumb and square. Install

frame in proper elevation, plane and location, and in proper alignment with other work. Head section of

9. Hardware: Push/pulls, door stops, overhead holders, and deadlocks, weatherstripping and thresholds, exit

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have

Performance: Comply with AAMA/NWWDA 101/I.S.2 for performance class and grade of window

been in satisfactory use in similar service for three years. Use experienced installers, Deliver, handle, and

. If necessary for tracks recessed into finish floors, drill weep holes in the floor track and provide drain

5. Properly flash and waterproof around the perimeter of the opening and frame. Adequate overhangs to

frame must be installed with a 1/8 inch upward crown at the center of the opening.

1. Provide Aluminum-Framed Entrances and Storefront: Storefront type framing system.

Glass: All glass to comply with safety glazing requirements of ANSI Z97.1 and CPSC 16CFR 1201.

2. Frame and Panels: Complete folding door system including head, side jambs, threshold and aluminum

Section 08 35 00.2 - FOLDING DOORS

Weather Resistant Sill

FOI DING GLASS DOORS

DESIGN / PERFORMANCE REQUIREMENTS

3. Thermal Performance: U-Factor of 0.65

A. Aluminum Thermally Controlled Folding Glass Doors.

1. Aluminum Thermally Controlled Folding Doors:

Folding Door Systems to comply with the performance requirements specified

panel details and type of glazing material per vertical plan and elevations view drawings.

source manufacturer with at least 7 years documented experience

systems or similar and screen system to the products specified.

WARRANTY: Manufacture's limited warranty including; 10 years

MANUFACTURERS: Acceptable Manufacturer: LaCantina Doors, Inc.

4. Frame and Sill: Thermally broken, extruded aluminum.

4. Install in accordance with manufacturer's instructions.

connectors to ensure water can escape from the tracks.

2. System shall meet 2018 IECC Prescriptive Approach

2. Door Style: 2" sightline x 4 ½" frame, center glazed

4. Aluminum Members: ASTM B 221, B 209 and B 211

Products: Kawneer, EFCO, Pacific Aluminum or approved equal

1. Basis-of-Design Products: Kawneer Trifab VG 451T or equal.

5. Steel Reinforcement: ASTM A 36, ASTM A 611, and ASTM A 570.

2. Anchor securely in place; install plumb, level and in true alignment.

Provide aluminum clad wood single-hung windows at front façade.

store materials in accordance with manufacturer's instructions.

1. Submit product data, samples, proposed hardware schedule, maintenance data.

4. System shall meet 2018 IECC Prescriptive Approach

1. Submit product data, shop drawings.

3. Storefront Frames: Thermal break type.

6. Door Hanging Devices: Continuous hinge.

8. Closer Operation: Single acting closers.

devices. Refer to Hardware Sets on drawings

10. Aluminum Finish: Clear anodized.

2. Warranty: Five Years

7. Closers: surface mounted

3. Isolate dissimilar metals.

SECTION 085200 - WINDOWS

and requirements.

'. Threshold: ADA Compliant ramp sill.

are stacked open) must be provided.

non-conductive bridge between the outside and the inside of the door.

Do not begin installation until substrates have been properly prepared.

openings are level, plumb, and square, with no unevenness in the floor.

prevent the effects of sheeting water from above are recommended.

SECTION 084110 - ALUMINUM-FRAMED ENTRANCES AND STOREFRONTS

3. Panel: Thermally broken, extruded aluminum stile and rail panels with standard one lite.

MATERIALS

EXECUTION A. Inspect framing and report unsatisfactory conditions in writing.

B. Comply with GANA "Glazing Manual" and manufacturer's instructions and recommendations. Use manufacturer's recommended spacers, blocks, primers, sealers, gaskets and accessories. C. Install sealants to provide complete wetting and bond and to create a substantial wash away from glass. D. Set mirrors on stainless steel clips and adhere to wall with mirror adhesive. E. Remove and replace damaged glass and glazing. Wash, polish and protect all glass supplied under this

SECTION 089000 - LOUVERS AND VENTS 1. Provide aluminum louvers.

12. Louver Accessories:

13. Wall Vents:

SECTION 092110 - GYPSUM BOARD ASSEMBLIES

10. Auxiliary Materials:

6. Provide blocking for items such as railings, grab bars, casework, toilet accessories, wall mounted

10. Provide joint treatment such that, after finishing, joints are not visible.

SECTION 092113- PLASTER ASSEMBLIES

SUBMITTALS **QUALITY ASSURANCE**

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

2. Fully comply with local code and accessibility requirements.

Basis-of-Design Products: J. L. Industries; Larsen's Manufacturing; Potter-Roemer; or approved equal Standards: UL and FM listed products. NFPA10 and ADAAG b. Type: Multipurpose dry chemical.

. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

SECTION 104400 - FIRE PROTECTION SPECIALTIES

b. Fire extinguisher cabinets at public areas.

c. Fire extinguisher mounting brackets at service areas.

. Provide fire extinguishers and cabinets:

a. Fire extinguishers.

1. Submit product data

. Basis-of-Design Products: J. L. Industries; Larsen's Manufacturing; Potter-Roemer; or approved equal

1. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

. Basis-of-Design Products: Refer to the Finish Schedule and the Drawings for requirements.

. Comply with requirements of Section 011000 - Project Requirements and manufacturer's specifications

. Product Data: Submit manufacturer's product data and installation instructions for each material and Samples: Submit two representative samples of each material specified indicating visual characteristics

Comply with governing codes and regulations. Provide products of acceptable manufacturers, which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and

Manufacturers: Select Blinds, Smith and Noble, Hunter Douglas Contract Window Coverings; or approved

. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance. Restore damaged finishes and test for proper operation. Clean and protect work from damage.

A. Arrange elevator components in machine room so equipment can be removed for repairs or replaced without B. Contractor to coordinate with the elevator supplier to complete all remaining work required in order to

B. UL or CSA Approved: Motors, pumps, valves, fluid tank, hydraulic fluid, microprocessor controller, controls, Spring Buffers, Attachment Brackets, and Anchors: Design and size according to building code with safety

5. Pump: Positive displacement screw type, design for steady discharge with minimal pulsations. a. Jack Cylinder: Two jacks, one located at each side of the car and mounted to the elevator car structure. b. Synchronization of Jack Stages: Direct mechanical means to ensure elevator moves at steady speed

This drawing as an instrument of service is the property of the Architect and may be used only on he project named herein. This drawing shall not be reproduced, copied, or used in whole or in any part without written permission of the Architect.

is what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

REV. # REVISION DESCRIPTION

SPECIFICATIONS