

HISTORIC AND DESIGN REVIEW COMMISSION

November 04, 2015

Agenda Item No: 18

HDRC CASE NO: 2015-435
ADDRESS: 411 CEDAR ST
LEGAL DESCRIPTION: NCB 2968 BLK 3 LOT 3
ZONING: RM4 H
CITY COUNCIL DIST.: 1
DISTRICT: King William Historic District
APPLICANT: Manny Garcia
OWNER: Robert Garcia
TYPE OF WORK: Column capital replacement and door replacement
REQUEST:

The applicant is requesting a Certificate of Appropriateness for approval to install three new doors as well as three column capitals at 411 Cedar.

APPLICABLE CITATIONS:

Historic Design Guidelines, Chapter 2, Guidelines for Exterior Maintenance and Alterations

1. Materials: Woodwork

A. MAINTENANCE (PRESERVATION)

- i. Inspections*—Conduct semi-annual inspections of all exterior wood elements to verify condition and determine maintenance needs.
- ii. Cleaning*—Clean exterior surfaces annually with mild household cleaners and water. Avoid using high pressure power washing and any abrasive cleaning or stripping methods that can damage the historic wood siding and detailing.
- iii. Paint preparation*—Remove peeling, flaking, or failing paint surfaces from historic woodwork using the gentlest means possible to protect the integrity of the historic wood surface. Acceptable methods for paint removal include scraping and sanding, thermal removal, and when necessary, mild chemical strippers. Sand blasting and water blasting should never be used to remove paint from any surface. Sand only to the next sound level of paint, not all the way to the wood, and address any moisture and deterioration issues before repainting.
- iv. Repainting*—Paint once the surface is clean and dry using a paint type that will adhere to the surface properly. See General Paint Type Recommendations in Preservation Brief #10 listed under Additional Resources for more information.
- v. Repair*—Repair deteriorated areas or refasten loose elements with an exterior wood filler, epoxy, or glue.

B. ALTERATIONS (REHABILITATION, RESTORATION, AND RECONSTRUCTION)

- i. Façade materials*—Avoid removing materials that are in good condition or that can be repaired in place. Consider exposing original wood siding if it is currently covered with vinyl or aluminum siding, stucco, or other materials that have not achieved historic significance.
- ii. Materials*—Use in-kind materials when possible or materials similar in size, scale, and character when exterior woodwork is beyond repair. Ensure replacement siding is installed to match the original pattern, including exposures. Do not introduce modern materials that can accelerate and hide deterioration of historic materials. Hardiboard and other cementitious materials are not recommended.
- iii. Replacement elements*—Replace wood elements in-kind as a replacement for existing wood siding, matching in profile, dimensions, material, and finish, when beyond repair.

6. Architectural Features: Doors, Windows, and Screens

A. MAINTENANCE (PRESERVATION)

- i. Openings*—Preserve existing window and door openings. Avoid enlarging or diminishing to fit stock sizes or air conditioning units. Avoid filling in historic door or window openings. Avoid creating new primary entrances or window

openings on the primary façade or where visible from the public right-of-way.

ii. Doors—Preserve historic doors including hardware, fanlights, sidelights, pilasters, and entablatures.

iii. Windows—Preserve historic windows. When glass is broken, the color and clarity of replacement glass should match the original historic glass.

iv. Screens and shutters—Preserve historic window screens and shutters.

v. Storm windows—Install full-view storm windows on the interior of windows for improved energy efficiency. Storm window may be installed on the exterior so long as the visual impact is minimal and original architectural details are not obscured.

B. ALTERATIONS (REHABILITATION, RESTORATION, AND RECONSTRUCTION)

i. Doors—Replace doors, hardware, fanlight, sidelights, pilasters, and entablatures in-kind when possible and when deteriorated beyond repair. When in-kind replacement is not feasible, ensure features match the size, material, and profile of the historic element.

ii. New entrances—Ensure that new entrances, when necessary to comply with other regulations, are compatible in size, scale, shape, proportion, material, and massing with historic entrances.

iii. Glazed area—Avoid installing interior floors or suspended ceilings that block the glazed area of historic windows.

iv. Window design—Install new windows to match the historic or existing windows in terms of size, type, configuration, material, form, appearance, and detail when original windows are deteriorated beyond repair.

v. Muntins—Use the exterior muntin pattern, profile, and size appropriate for the historic building when replacement windows are necessary. Do not use internal muntins sandwiched between layers of glass.

vi. Replacement glass—Use clear glass when replacement glass is necessary. Do not use tinted glass, reflective glass, opaque glass, and other non-traditional glass types unless it was used historically. When established by the architectural style of the building, patterned, leaded, or colored glass can be used.

vii. Non-historic windows—Replace non-historic incompatible windows with windows that are typical of the architectural style of the building.

viii. Security bars—Install security bars only on the interior of windows and doors.

ix. Screens—Utilize wood screen window frames matching in profile, size, and design of those historically found when the existing screens are deteriorated beyond repair. Ensure that the tint of replacement screens closely matches the original screens or those used historically.

x. Shutters—Incorporate shutters only where they existed historically and where appropriate to the architectural style of the house. Shutters should match the height and width of the opening and be mounted to be operational or appear to be operational. Do not mount shutters directly onto any historic wall material.

7. Architectural Features: Porches, Balconies, and Porte-Cocheres

A. MAINTENANCE (PRESERVATION)

i. Existing porches, balconies, and porte-cocheres—Preserve porches, balconies, and porte-cocheres. Do not add new porches, balconies, or porte-cocheres where not historically present.

ii. Balusters—Preserve existing balusters. When replacement is necessary, replace in-kind when possible or with balusters that match the originals in terms of materials, spacing, profile, dimension, finish, and height of the railing.

iii. Floors—Preserve original wood or concrete porch floors. Do not cover original porch floors of wood or concrete with carpet, tile, or other materials unless they were used historically.

B. ALTERATIONS (REHABILITATION, RESTORATION, AND RECONSTRUCTION)

i. Front porches—Refrain from enclosing front porches. Approved screen panels should be simple in design as to not change the character of the structure or the historic fabric.

ii. Side and rear porches—Refrain from enclosing side and rear porches, particularly when connected to the main porch or balcony. Original architectural details should not be obscured by any screening or enclosure materials. Alterations to side and rear porches should result in a space that functions, and is visually interpreted as, a porch.

iii. Replacement—Replace in-kind porches, balconies, porte-cocheres, and related elements, such as ceilings, floors, and columns, when such features are deteriorated beyond repair. When in-kind replacement is not feasible, the design should be compatible in scale, massing, and detail while materials should match in color, texture, dimensions, and finish.

iv. Adding elements—Design replacement elements, such as stairs, to be simple so as to not distract from the historic character of the building. Do not add new elements and details that create a false historic appearance.

v. *Reconstruction*—Reconstruct porches, balconies, and porte-cocheres based on accurate evidence of the original, such as photographs. If no such evidence exists, the design should be based on the architectural style of the building and historic patterns.

FINDINGS:

- a. The applicant is requesting a Certificate of Appropriateness to install three new doors to the façade of the house at 411 Cedar; two to the front façade at the second level balcony and one on the north façade of the house. According to the Guidelines for Exterior Maintenance and Alterations 6.B., historic doors should be preserved and if replaced, should be replaced with doors that are of appropriate materials and style. Staff recommends the applicant provide additional information regarding any replacement doors as well as information regarding to condition of the original doors.
- b. The original front porch featured 5 Corinthian column capitals, two of which the applicant has preserved, however, the applicant has replaced the front three capitals with replacement capitals that are not matching in profile, detail, nor material. Per the Guidelines for Exterior Maintenance and Alterations 1.A.ii., wood elements should be replaced in kind, matching the existing profile, dimensions, material and finish of the historic element. The applicant's replacement capitals are not consistent with the Guidelines. Staff recommends the applicant repair the original, damaged column capitals. If the original columns are beyond repair, the applicant should replace them with wood columns that are consistent with the Guidelines for Exterior Maintenance and Alterations that match in profile, material, dimension and finish as the original capitals.

RECOMMENDATION:

Staff recommends the applicant provide additional information regarding any replacement doors as well as information regarding to condition of the original doors and that the applicant replace the current, non original column capitals with column capitals that are consistent with the original.

CASE MANAGER:

Edward Hall





Flex Viewer

Powered by ArcGIS Server

Printed: Oct 27, 2015

The City of San Antonio does not guarantee the accuracy, adequacy, completeness or usefulness of any information. The City does not warrant the completeness, timeliness, or positional, thematic, and attribute accuracy of the GIS data. The GIS data, cartographic products, and associated applications are not legal representations of the depicted data. Information shown on these maps is derived from public records that are constantly undergoing revision. Under no circumstances should GIS-derived products be used for final design purposes. The City provides this information on an "as is" basis without warranty of any kind, express or implied, including but not limited to warranties of merchantability or fitness for a particular purpose, and assumes no responsibility for anyone's use of the information.

















