

HISTORIC AND DESIGN REVIEW COMMISSION

October 17, 2018

HDRC CASE NO: 2018-495
ADDRESS: 143 SEXAUER DR
LEGAL DESCRIPTION: NCB 7670 BLK LOT 12 & N 10.5 FT OF 11
ZONING: R-6, H
CITY COUNCIL DIST.: 3
DISTRICT: Mission Historic District
APPLICANT: Leticia Huerta
OWNER: Leticia Huerta
TYPE OF WORK: Construction of a single family residential structure
APPLICATION RECEIVED: September 24, 2018
60-DAY REVIEW: November 23, 2018
REQUEST:

The applicant is requesting a Certificate of Appropriateness for approval to construct a one story, single family residential structure at 143 Sexauer, located within the Mission Historic District.

APPLICABLE CITATIONS:

Historic Design Guidelines, Chapter 4, Guidelines for New Construction

1. Building and Entrance Orientation

A. FAÇADE ORIENTATION

i. Setbacks—Align front facades of new buildings with front facades of adjacent buildings where a consistent setback has been established along the street frontage. Use the median setback of buildings along the street frontage where a variety of setbacks exist. Refer to UDC Article 3, Division 2. Base Zoning Districts for applicable setback requirements.

ii. Orientation—Orient the front façade of new buildings to be consistent with the predominant orientation of historic buildings along the street frontage.

B. ENTRANCES

i. Orientation—Orient primary building entrances, porches, and landings to be consistent with those historically found along the street frontage. Typically, historic building entrances are oriented towards the primary street.

2. Building Massing and Form

A. SCALE AND MASS

i. Similar height and scale—Design new construction so that its height and overall scale are consistent with nearby historic buildings. In residential districts, the height and scale of new construction should not exceed that of the majority of historic buildings by more than one-story. In commercial districts, building height shall conform to the established pattern. If there is no more than a 50% variation in the scale of buildings on the adjacent block faces, then the height of the new building shall not exceed the tallest building on the adjacent block face by more than 10%.

ii. Transitions—Utilize step-downs in building height, wall-plane offsets, and other variations in building massing to provide a visual transition when the height of new construction exceeds that of adjacent historic buildings by more than one-half story.

iii. Foundation and floor heights—Align foundation and floor-to-floor heights (including porches and balconies) within one foot of floor-to-floor heights on adjacent historic structures.

B. ROOF FORM

i. Similar roof forms—Incorporate roof forms—pitch, overhangs, and orientation—that are consistent with those predominantly found on the block. Roof forms on residential building types are typically sloped, while roof forms on nonresidential

building types are more typically flat and screened by an ornamental parapet wall.

ii. Façade configuration—The primary façade of new commercial buildings should be in keeping with established patterns. Maintaining horizontal elements within adjacent cap, middle, and base precedents will establish a consistent

street wall through the alignment of horizontal parts. Avoid blank walls, particularly on elevations visible from the street. No new façade should exceed 40 linear feet without being penetrated by windows, entryways, or other defined bays.

D. LOT COVERAGE

i. Building to lot ratio—New construction should be consistent with adjacent historic buildings in terms of the building to lot ratio. Limit the building footprint for new construction to no more than 50 percent of the total lot area, unless adjacent historic buildings establish a precedent with a greater building to lot ratio.

3. Materials and Textures

A. NEW MATERIALS

i. Complementary materials—Use materials that complement the type, color, and texture of materials traditionally found in the district. Materials should not be so dissimilar as to distract from the historic interpretation of the district. For example, corrugated metal siding would not be appropriate for a new structure in a district comprised of homes with wood siding.

ii. Alternative use of traditional materials—Consider using traditional materials, such as wood siding, in a new way to provide visual interest in new construction while still ensuring compatibility.

iii. Roof materials—Select roof materials that are similar in terms of form, color, and texture to traditionally used in the district.

iv. Metal roofs—Construct new metal roofs in a similar fashion as historic metal roofs. Refer to the Guidelines for Alterations and Maintenance section for additional specifications regarding metal roofs.

v. Imitation or synthetic materials—Do not use vinyl siding, plastic, or corrugated metal sheeting. Contemporary materials not traditionally used in the district, such as brick or simulated stone veneer and Hardie Board or other fiberboard siding, may be appropriate for new construction in some locations as long as new materials are visually similar to the traditional material in dimension, finish, and texture. EIFS is not recommended as a substitute for actual stucco.

4. Architectural Details

A. GENERAL

i. Historic context—Design new buildings to reflect their time while respecting the historic context. While new construction should not attempt to mirror or replicate historic features, new structures should not be so dissimilar as to distract from or diminish the historic interpretation of the district.

ii. Architectural details—Incorporate architectural details that are in keeping with the predominant architectural style along the block face or within the district when one exists. Details should be simple in design and should complement, but not visually compete with, the character of the adjacent historic structures or other historic structures within the district. Architectural details that are more ornate or elaborate than those found within the district are inappropriate.

iii. Contemporary interpretations—Consider integrating contemporary interpretations of traditional designs and details for new construction. Use of contemporary window moldings and door surroundings, for example, can provide visual interest while helping to convey the fact that the structure is new. Modern materials should be implemented in a way that does not distract from the historic structure.

5. Garages and Outbuildings

A. DESIGN AND CHARACTER

v. Garage doors—Incorporate garage doors with similar proportions and materials as those traditionally found in the district.

6. Mechanical Equipment and Roof Appurtenances

A. LOCATION AND SITING

i. Visibility—Do not locate utility boxes, air conditioners, rooftop mechanical equipment, skylights, satellite dishes, and other roof appurtenances on primary facades, front-facing roof slopes, in front yards, or in other locations that are clearly visible from the public right-of-way.

ii. Service Areas—Locate service areas towards the rear of the site to minimize visibility from the public right-of-way.

B. SCREENING

- i. Building-mounted equipment*—Paint devices mounted on secondary facades and other exposed hardware, frames, and piping to match the color scheme of the primary structure or screen them with landscaping.
 - ii. Freestanding equipment*—Screen service areas, air conditioning units, and other mechanical equipment from public view using a fence, hedge, or other enclosure.
 - iii. Roof-mounted equipment*—Screen and set back devices mounted on the roof to avoid view from public right-of-way.
- Historic Design Guidelines, Chapter 5, Guidelines for Site Elements

B. NEW FENCES AND WALLS

- i. Design*—New fences and walls should appear similar to those used historically within the district in terms of their scale, transparency, and character. Design of fence should respond to the design and materials of the house or main structure.
 - ii. Location*—Avoid installing a fence or wall in a location where one did not historically exist, particularly within the front yard. The appropriateness of a front yard fence or wall is dependent on conditions within a specific historic district. New front yard fences or wall should not be introduced within historic districts that have not historically had them.
 - iii. Height*—Limit the height of new fences and walls within the front yard to a maximum of four feet. The appropriateness of a front yard fence is dependent on conditions within a specific historic district. New front yard fences should not be introduced within historic districts that have not historically had them. If a taller fence or wall existed historically, additional height may be considered. The height of a new retaining wall should not exceed the height of the slope it retains.
 - iv. Prohibited materials*—Do not use exposed concrete masonry units (CMU), Keystone or similar interlocking retaining wall systems, concrete block, vinyl fencing, or chain link fencing.
 - v. Appropriate materials*—Construct new fences or walls of materials similar to fence materials historically used in the district. Select materials that are similar in scale, texture, color, and form as those historically used in the district, and that are compatible with the main structure.
- Screening incompatible uses—Review alternative fence heights and materials for appropriateness where residential properties are adjacent to commercial or other potentially incompatible uses.

3. Landscape Design

A. PLANTINGS

- i. Historic Gardens*—Maintain front yard gardens when appropriate within a specific historic district.
- ii. Historic Lawns*—Do not fully remove and replace traditional lawn areas with impervious hardscape. Limit the removal of lawn areas to mulched planting beds or pervious hardscapes in locations where they would historically be found, such as along fences, walkways, or drives. Low-growing plantings should be used in historic lawn areas; invasive or large-scale species should be avoided. Historic lawn areas should never be reduced by more than 50%.
- iii. Native xeric plant materials*—Select native and/or xeric plants that thrive in local conditions and reduce watering usage. See UDC Appendix E: San Antonio Recommended Plant List—All Suited to Xeriscape Planting Methods, for a list of appropriate materials and planting methods. Select plant materials with a similar character, growth habit, and light requirements as those being replaced.
- iv. Plant palettes*—If a varied plant palette is used, incorporate species of taller heights, such informal elements should be restrained to small areas of the front yard or to the rear or side yard so as not to obstruct views of or otherwise distract from the historic structure.
- v. Maintenance*—Maintain existing landscape features. Do not introduce landscape elements that will obscure the historic structure or are located as to retain moisture on walls or foundations (e.g., dense foundation plantings or vines) or as to cause damage.

B. ROCKS OR HARDSCAPE

- i. Impervious surfaces*—Do not introduce large pavers, asphalt, or other impervious surfaces where they were not historically located.
- ii. Pervious and semi-pervious surfaces*—New pervious hardscapes should be limited to areas that are not highly visible, and should not be used as wholesale replacement for plantings. If used, small plantings should be incorporated into the design.
- iii. Rock mulch and gravel*—Do not use rock mulch or gravel as a wholesale replacement for lawn area. If used, plantings should be incorporated into the design.

D. TREES

- i. Preservation*—Preserve and protect from damage existing mature trees and heritage trees. See UDC Section 35-523 (Tree Preservation) for specific requirements.
- ii. New Trees* – Select new trees based on site conditions. Avoid planting new trees in locations that could potentially cause damage to a historic structure or other historic elements. Species selection and planting procedure should be done in accordance with guidance from the City Arborist.

5. Sidewalks, Walkways, Driveways, and Curbing

A. SIDEWALKS AND WALKWAYS

- i. Maintenance*—Repair minor cracking, settling, or jamming along sidewalks to prevent uneven surfaces. Retain and repair historic sidewalk and walkway paving materials—often brick or concrete—in place.
- ii. Replacement materials*—Replace those portions of sidewalks or walkways that are deteriorated beyond repair. Every effort should be made to match existing sidewalk color and material.
- iii. Width and alignment*—Follow the historic alignment, configuration, and width of sidewalks and walkways. Alter the historic width or alignment only where absolutely necessary to accommodate the preservation of a significant tree.
- iv. Stamped concrete*—Preserve stamped street names, business insignias, or other historic elements of sidewalks and walkways when replacement is necessary.
- v. ADA compliance*—Limit removal of historic sidewalk materials to the immediate intersection when ramps are added to address ADA requirements.

B. DRIVEWAYS

- i. Driveway configuration*—Retain and repair in place historic driveway configurations, such as ribbon drives. Incorporate a similar driveway configuration—materials, width, and design—to that historically found on the site. Historic driveways are typically no wider than 10 feet. Pervious paving surfaces may be considered where replacement is necessary to increase stormwater infiltration.
- ii. Curb cuts and ramps*—Maintain the width and configuration of original curb cuts when replacing historic driveways. Avoid introducing new curb cuts where not historically found.

7. Off-Street Parking

A. LOCATION

- i. Preferred location*—Place parking areas for non-residential and mixed-use structures at the rear of the site, behind primary structures to hide them from the public right-of-way. On corner lots, place parking areas behind the primary structure and set them back as far as possible from the side streets. Parking areas to the side of the primary structure are acceptable when location behind the structure is not feasible. See UDC Section 35-310 for district-specific standards.
- ii. Front*—Do not add off-street parking areas within the front yard setback as to not disrupt the continuity of the streetscape.
- iii. Access*—Design off-street parking areas to be accessed from alleys or secondary streets rather than from principal streets whenever possible.

B. DESIGN

- i. Screening*—Screen off-street parking areas with a landscape buffer, wall, or ornamental fence two to four feet high—or a combination of these methods. Landscape buffers are preferred due to their ability to absorb carbon dioxide. See UDC Section 35-510 for buffer requirements.
- ii. Materials*—Use permeable parking surfaces when possible to reduce run-off and flooding. See UDC Section 35-526(j) for specific standards.
- iii. Parking structures*—Design new parking structures to be similar in scale, materials, and rhythm of the surrounding historic district when new parking structures are necessary.

FINDINGS:

- a. The applicant is requesting a Certificate of Appropriateness for approval to construct a one story, single family residential structure at 143 Sexauer, located within the Mission Historic District.
- b. SETBACKS & ORIENTATION – According to the Guidelines for New Construction, the front facades of new

buildings are to align with front facades of adjacent buildings where a consistent setback has been established along the street frontage. Additionally, the orientation of new construction should be consistent with the historic example found on the block. The applicant has noted a setback of forty (40) feet from the property line. Setbacks of existing, historic structures on this block range from approximately ten to twenty feet. Staff finds that a setback that is greater than those of the historic structures on the block to be appropriate. To ensure that the proposed new construction is not built forward of the existing structures, staff finds that a site plan that includes the setbacks of adjacent structures should be submitted.

- c. ENTRANCES – According to the Guidelines for New Construction 1.B.i., primary building entrances should be oriented towards the primary street. Per the application documents, the applicant has proposed a primary entrance that faces Sexauer. This is consistent with the Guidelines.
- d. SCALE & MASSING – This block of Sexauer features one story structures with modest footprints. The Guidelines for New Construction 2.A. notes that the height and scale of new construction should not exceed that of the majority of historic buildings by more than one-story. Staff finds the proposed massing of one height to be appropriate and consistent with the Guidelines.
- e. FOUNDATION & FLOOR HEIGHTS – According to the Guidelines for New Construction 2.A.iii., foundation and floor height should be aligned within one (1) foot of neighboring structure’s foundation and floor heights. At this time the applicant has not provided specific information regarding foundation heights.
- f. ROOF FORM – The applicant has proposed a side gabled roof with elongated shed roofs for both the front and rear porch. This form is found commonly on Sexauer and is vernacular to the neighborhood. Staff finds the proposed roof form to be appropriate.
- g. ARCHITECTURAL DETAILS – The applicant has proposed an overall form and massing that are generally appropriate for the immediate surroundings of the vacant lot. Staff finds that an increase in window fenestration would be appropriate.
- h. MATERIALS – The applicant has proposed materials that include stone veneer, composite siding, a composition shingle roof, vinyl windows and wood and vinyl doors. The Guidelines for New Construction 3.A. notes that materials that are complementary of those found historically in the district should be used. The majority of single, family historic structures in the immediate area consist of wood siding. Staff finds that the proposed stone veneer should be eliminated from the proposal.
- i. WINDOW MATERIALS – At this time, the applicant has proposed to install white, vinyl windows. This is not consistent with the Guidelines. Staff finds that a double-hung, one-over-one wood windows or aluminum-clad wood windows be used.. Meeting rails must be no taller than 1.25” and stiles no wider than 2.25”. White manufacturer’s color is not allowed, and color selection must be presented to staff. There should be a minimum of two inches in depth between the front face of the window trim and the front face of the top window sash. This must be accomplished by recessing the window sufficiently within the opening or with the installation of additional window trim to add thickness. Window trim must feature traditional dimensions and architecturally appropriate sill detail (need to add detail here). Window track components must be painted to match the window trim or concealed by a wood window screen set within the opening.
- j. MECHANICAL EQUIPMENT – MECHANICAL EQUIPMENT – Per the Guidelines for New Construction 6., all mechanical equipment should be screened from view at the public right of way. The applicant is responsible for screening all mechanical equipment where it cannot be viewed from the public right of way at Sexauer.
- k. DRIVEWAY – The applicant has proposed a concrete driveway to the south of the proposed new construction. This location and profile are consistent with the Guidelines. The applicant should ensure that the propose driveway does not exceed ten (10) feet in width, per the Guidelines for Site Elements.
- l. LANDSCAPING – At this time, the applicant has not specified landscaping design. A landscaping plan should be included in an application for final approval.

RECOMMENDATION:


Staff recommends approval of the proposed massing and form as noted in findings c, d, f and g. Prior to a receiving a recommendation for final approval, staff finds that the applicant should address the following items.

- i. A setback that is greater than those found historically on this block should be used. The applicant should provide documentation noting that a setback that is greater than those existing is proposed as noted in finding b.
- ii. That a foundation height that is comparable to those found historically on this street be installed as noted in finding e.
- iii. That the proposed stone veneer be removed as noted in finding h.

- iv. That double-hung, one-over-one wood windows or aluminum-clad wood windows be used.. Meeting rails must be no taller than 1.25” and stiles no wider than 2.25”. White manufacturer’s color is not allowed, and color selection must be presented to staff. There should be a minimum of two inches in depth between the front face of the window trim and the front face of the top window sash. This must be accomplished by recessing the window sufficiently within the opening or with the installation of additional window trim to add thickness. Window trim must feature traditional dimensions and architecturally appropriate sill detail (need to add detail here). Window track components must be painted to match the window trim or concealed by a wood window screen set within the opening.
- v. That all mechanical equipment be screened from view at the public right of way as noted in finding j.
- vi. That the driveway not exceed ten (10) feet in width as noted in finding k.
- vii. That a landscaping plan be submitted as noted in finding l.

CASE MANAGER:

Edward Hall



Flex Viewer

Powered by ArcGIS Server

Printed: Oct 10, 2018

The City of San Antonio does not guarantee the accuracy, adequacy, completeness or usefulness of any information. The City does not warrant the completeness, timeliness, or positional, thematic, and attribute accuracy of the GIS data. The GIS data, cartographic products, and associated applications are not legal representations of the depicted data. Information shown on these maps is derived from public records that are constantly undergoing revision. Under no circumstances should GIS-derived products be used for final design purposes. The City provides this information on an "as is" basis without warranty of any kind, express or implied, including but not limited to warranties of merchantability or fitness for a particular purpose, and assumes no responsibility for anyone's use of the information.



143 Sexauer Dr

Sexauer Dr

Floss Rd

VIEW FACING SOUTH TOWARD 143 SEXUAER






VIEW FACING NORTH TOWARD 143 SEXUAER

EXISTING STRUCTURES ON SEXUAER







GENERAL NOTES
FIELD VERIFY ALL DIMENSIONS
PRIOR TO CONSTRUCTION

HUERTA HOUSE
143 SEXAUER DR
SAN ANTONIO, TX 78114

FRONT ELEVATION


DATE:

5/22/2018

SCALE:

1/4" = 12"





GENERAL NOTES
FIELD VERIFY ALL DIMENSIONS
PRIOR TO CONSTRUCTION


HUERTA HOUSE
143 SEMAUER DR
SAN ANTONIO, TX 78114

SIDE ELEVATION

DATE:
5/22/2018

SCALE:
1/4" = 12"





GENERAL NOTES
FIELD VERIFY ALL DIMENSIONS
PRIOR TO CONSTRUCTION

HUERFIA HOUSE
143 ESKAUER DR
SAN ANTONIO, TX 78414

SIDE ELEVATION

DATE:

5/22/2018

SCALE

1/4" = 12"



COMPOSITION SHINGLE ROOF

12" TRIM BOARD

8" LAP FIBER CEMENT SIDING

10" TRIM BOARD @ PERIMETER OF DECK

4" TRIM BOARD @ ALL WINDOWS AND DOORS



GENERAL NOTES
FIELD VERIFY ALL DIMENSIONS
PRIOR TO CONSTRUCTION


HUERTA HOUSE
143 SEXAUJER DR
SAN ANTONIO, TX 78414

REAR ELEVATION

DATE:
5/22/2018

SCALE:
1/4" = 12"





GENERAL NOTES
FIELD VERIFY ALL DIMENSIONS
PRIOR TO CONSTRUCTION

HUERTA HOUSE
145 SEQUOIA DR
SAN ANTONIO, TX 78214

BUILDING CROSS SECTION

DATE:
5/22/2018

SCALE
1/4" = 12"

