

City of San Antonio

ADDENDUM I

SUBJECT: Formal Invitation for Bid (IFB) LIGHT & MEDIUM DUTY SERVICE TRUCKS
(6100011605)
Scheduled to Open: July 8, 2019 at 2:00 PM C.T. Date of Issue: June 19, 2019.

FROM: Norbert Dziuk
Procurement Operations Lead

DATE: July 3, 2019

THE ABOVE MENTIONED INVITATION FOR BID IS HEREBY AMENDED AS FOLLOWS:

THE BID OPENING HAS BEEN EXTENDED TO JULY 10, 2019 AT 2:00 PM CT.

The following were questions received during the Pre-Submittal meeting held on JUNE 26, 2019.

1. 4.1

- Item 10 (2) 1 Ton Regular Cab DRW Truck, 42' 11' Stake Bed w/Lift Gate

2. 4.2.3 Changed to Read:

4.2.3

Delivery to a non-specified location will result in non-acceptance of the equipment by the City. All deliveries must be pre-arranged with a minimum 24-hour notification, NO EXCEPTIONS. Vehicles will be accepted 8:00 A.M. to 3:00 P.M. CST. Class 3 dual rear wheel trucks through class 8 may be allowed up to ~~2500~~ 3000 miles on the vehicle odometer. Class 1 and 2 single wheel rear wheel trucks shall have no more than 500 miles on the vehicle odometer or shall not be accepted. All vehicles are required to have a full tank(s) when delivered to the City specified location.

3. 4.4.9 Changed to Read:

4.4.9 CAB: Truck shall be supplied with a crew cab. Seating; ~~a 40/20/40 front bench seat with console and bench rear seating.~~ shall accept 40/20/40 or 60/40, both are acceptable. Upholstery shall be dark gray cloth or vinyl. Cab shall be equipped with dark vinyl flooring.

4. Question: Is power required for extendable towing mirrors in 4.4.10?
Answer: No

5. Question: Item 5- 4.7.8 Gooseneck Hitch OEM only?
Answer: OEM or work performed by the manufacturer authorized dealer that warrants the work.

6. 4.5.2 Changed to Read:

4.5.2 GVWR: Minimum **6,500 lbs.** ~~6,800 lbs.~~

7. 4.6.2 Changed to Read:

4.6.2 GVWR: Minimum **6,500 lbs.** ~~6,800 lbs.~~

8. 4.6.5 Changed to Read:

4.6.5 DIMENSIONS: Four Full Door cab configuration. Pick-up box length shall be a minimum of **66 inches** ~~67~~. Wheelbase must be a minimum of 140 inches.

9. 4.6.11 Changed to Read:

4.6.11 BED COVER: Unit shall be equipped with a lockable fiberglass bed cover; **Open and Shut type with a lockable handle to secure items.** Bed cover shall be OEM white (same as unit) and have suspension bars to securely hold cover upright when in use.

10. 4.7.1 Changed to Read:

4.7.1 ENGINE: Diesel, ~~8~~ **minimum 6 cylinder** engine capable of producing a minimum of 325 HP rated at manufacturer's RPM.

11. 4.7.8.2 Changed to Read:

4.7.8.2 TRAILER HITCH – Truck shall be supplied with two trailer hitch connections at bumper rear. There shall be OEM rear bumper and tow package to include receiver hitch with 2" adjustable height tow ball. ~~A secondary 4-way round pin adjacent to the 7-way flat pin~~ **A secondary 4 way flat pin connector adjacent to the RV Style 7-way pin** connector shall also be installed to accommodate other tow behind trailers.

12. 4.7.8.3 Changed to Read:

4.7.8.3 CONTROLS - Truck shall include an OEM in-cab mounted trailer brake controller and both a 4-Way flat vehicle connector and ~~7-Way flat pin vehicle~~ **RV Style 7-way pin** connector for the variety of trailers to be used with this truck.

13. 4.7.16 Changed to Read:

4.7.16 CAMERA SYSTEM: Truck shall include a **Back-up Camera** system specifically designed for truck towing; may be an aftermarket addition.

14. Added to read:

4.7.18 COLOR: Truck color shall be **White**.

15. 4.8.4 Changed to Read:

4.8.4 WHEELBASE – Truck shall have **minimum 133"** ~~approximate~~ wheelbase for long truck bed.

16. 4.8.15 Changed to Read:

4.8.15 TOWING: Truck shall be equipped with a weight distributing hitch, with sway control. Tow ball shall be a minimum of 2" and must be height adjustable. Must include a ~~7-way flat pin electrical~~ **RV Style 7-way pin** connector for trailer hook-up.

17. 4.9.4 Changed to Read:

4.9.4 WHEELBASE – Truck shall have an ~~approximate~~ **minimum 133"** wheelbase for long truck bed.

18. 4.10.10 Changes to read:

4.10.10 FUEL TANK – Truck must have a minimum of **32 gallon** ~~40~~ with DEF tank with corresponding dash gauge add/or low level indicator light.

19. 4.11.10 Changed to Read:

4.11.10 FUEL TANK – Truck must have a minimum of **32 gallon** ~~40~~-with DEF tank with corresponding dash gauge add/or low level indicator light.

20, Changed to Read:

4.11.15 TOW BUMPER – This truck shall have a receiver hitch with a 2" adjustable height hitch. Trucks shall also include an OEM in-cab trailer brake controller and a both a 4-way flat vehicle connector and a ~~7-way flat pin round~~ **RV Style 7-way pin connector** vehicle connector.

21. Changed to Read:

4.12	ITEM	QUANTITY	DESCRIPTION
	10	2	1 Ton Regular Cab DRW Trucks, 12' 11' Stake Bed w/Lift Gate

22. 4.12.1 Change to Read:

4.12.1 ENGINE –Diesel powered, minimum 6 ~~liter~~ **cylinder** engine producing a minimum 250 HP rated at manufacturer's RPM.

23. 4.12.11 Changed to Read:


4.12.11 STAKE BED – Trucks shall be provided with a ~~12'~~ **11'** stake bed that is diamond plate with 40" removable stakes, and 1,600 lb. capacity heavy hydraulic electric power lift gate (non-tuck-a-way). All component of stake body must be finished in black paint. Solid black mud flaps (no dealer markings) shall be provided behind rear wheels.

24. 4.13.1 Changed to Read:

4.13.1 ENGINE – Diesel powered, minimum 6 liter ~~liter~~ **cylinder** engine producing a minimum 250 HP rated at manufacturer's RPM.

25. 4.14.11 Changed to Read:

4.14.11 FUEL SYSTEM - Single left or right hand metal tank mounted under cab or dual left and right hand step tanks mounted under cab. Minimum fuel capacity is 70 gallons. Fuel filtration shall include primary and secondary filtering systems with automatic water separator. Diesel Exhaust Fluid (DEF) tank shall have a 9 ½ ~~gallon~~ **gallon** capacity with in dash DEF gauge.



Norbert Dziuk
Procurement Operations Lead
Finance Department, Purchasing Division