

REMOVAL MITIGATION FROM SIGNIFICANT TREE

REMOVAL MITIGATION FROM RIPARIAN BUFFER

TOTAL INCHES REQUIRED TO MEET MITIGATION

ADDITIONAL INCHES FROM OVERSIZING REQUIRED TREES (0.5 INCHES/TREE \* 2 TREES/LOT \* 96 LOTS = 96

OVERALL MITIGATION REQUIREMENT (NO ADDITIONAL MITIGATION REQUIRED)

ENGINEERS + SURVEYING
3421 Paesanos Pkvy, Suite 200, San Antonio, TX 78231

LOCATION MAP N.T.S.

PROTECTED/HERITAGE

PROTECTED/HERITAGE
TREES PRESERVED


EXEMPTED PROTECTED TREES WITHIN
R.O.W. & UTILITY EASEMENTS TO BE
REMOVED
ENERGY CONSERVATION TREES (SEE DETAIL
THIS SHEET)

REMOVED - RIPARIAN BUFFER

OFF-LOT 30'
SANITARY
SEWER
EASEMENT
DOC#

PROPOSED
BUILDING
10' MIN
30' MAX

LOT NUMBERS WITH TRIANGLE SHALL HAVE ONE
(1) MEDIUM 2" CALIPER SPECIES TREE AND ONE
(1) LARGE 2" CALIPER SPECIES TREE IN THE
BACK YARD WITHIN THE ENERGY
CONSERVATION LIMITS. SEE DETAIL THIS SHEET



LOT NUMBERS WITH SQUARE SHALL HAVE
ONE (1) MEDIUM 2" CALIPER SPECIES TREE
AND ONE (1) LARGE 2" CALIPER SPECIES
TREE IN THE BACK YARD NOT RECEIVING
ENERGY CONSERVATION CREDITS. SEE
DETAIL THIS SHEET

## TREE PROTECTION NOTES

PRESERVATION PERCENTAGE

MITIGATION REQUIRED

34.0 INCHES

29.2 INCHES

63.2 INCHES

96.0 INCHES

32.8 INCHES

0%

29.20

THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL

- 1. A ROOT PROTECTION ZONE WILL BE ESTABLISHED AROUND EACH TREE OR ANY VEGETATION TO BE PRESERVED TO MEET THE LANDSCAPE OR TREE PRESERVATION ORDINANCES. THE ROOT PROTECTION ZONE SHALL BE AN AREA DEFINED BY THE RADIUS EXTENDING OUTWARD FROM THE TRUNK OF THE TREE A DISTANCE OF ONE (1) LINEAR FOOT FOR EACH INCH DIAMETER INCH AT BREAST HEIGHT (4.5 ) OF THE TREE. A 10-INCH DIAMETER TREE WILL HAVE A 10 FOOT RADIUS ROOT PROTECTION ZONE.
- 2. NO WORK SHALL BEGIN WHERE TREE PROTECTION FENCING HAS NOT BEEN COMPLETED AND APPROVED. TREE PROTECTION FENCING SHALL BE INSTALLED, MAINTAINED AND REPAIRED BY THE CONTRACTOR DURING CONSTRUCTION. THE FENCING WILL BE A MINIMUM OF 4' HEIGHT.
- 3. ALL ROOTS LARGER THAN ONE-INCH IN DIAMETER ARE TO BE CUT CLEANLY AND OAK WOUNDS PAINTED WITHIN 30 MINUTES.
- 4. EXPOSED ROOTS SHALL BE COVERED AT THE END OF THE WORK DAY USING TECHNIQUES SUCH AS COVERING WITH SOIL, MULCH OR WET BURLAP.
- 5. NO EQUIPMENT, VEHICLES OR MATERIALS SHALL BE OPERATED OR STORED WITHIN THE ROOT PROTECTION ZONE. NO CLEAN-OUT AREAS WILL BE CONSTRUCTED SO THAT THE MATERIAL WILL BE IN OR MIGRATE TO THE ROOT PROTECTION ZONE.
- 6. NO GRADE CHANGE MORE THAN 3" IS ALLOWED WITHIN THE ROOT PROTECTION ZONE.
- 7. ROOTS OR BRANCHES IN CONFLICT WITH CONSTRUCTION SHALL BE CUT CLEANLY ACCORDING TO PROPER PRUNING METHODS. All OAK WOUNDS SHALL BE PAINTED WITHIN 30 MINUTES TO PREVENT OAK WILT INFECTION.
- 8. ANY TREE REMOVAL SHALL BE APPROVED BY THE CITY ARBORIST (210-207-0278).
- 9. TREES WHICH ARE DAMAGED OR LOST DUE TO THE CONTRACTOR'S NEGLIGENCE DURING CONSTRUCTION SHALL BE MITIGATED.
- 10. TREES MUST BE MAINTAINED IN GOOD HEALTH THROUGHOUT THE CONSTRUCTION PROCESS. MAINTENANCE MAY INCLUDE WATERING THE ROOT PROTECTION ZONE AND OR WASHING
- 11. NO WIRES, NAILS OR OTHER MATERIALS MAY BE ATTACHED TO PROTECTED TREES.

PLAT NO. 20-11800502

JOB NO. 314-35-02
DATE: JUNE 2020
DRAWN: NA CHECKED: TI

1 OF 1